
Hoval


CATALOGUE

Storage tanks / domestic water heating


1.10.2026




Calorifiers
Enamelled



Hoval CombiVal ER **200-1000 l**



Hoval CombiVal ESR **200-400 l**



Hoval CombiVal ESSR **500-1000 l**

Coil:




standard

large


specially large

Calorifier charging systems




Hoval charging module TransTherm® aqua L	**50-275 kW**
Hoval charging module TransTherm® aqua L-FW	**50-275 kW**
Hoval charging tank CombiVal E	**300-2000 l**
Hoval charging tank CombiVal C	**200-2500 l**


Fresh water modules




Hoval fresh water module TransTherm® aqua F — **50-275 kW**



Hoval fresh water module TransTherm® aqua F — **350-700 kW**




Hoval fresh water module TransTherm® aqua FS — **50-717 kW**




Hoval fresh water module TransTherm® aqua FT
TransTherm® aqua FTC


Buffer storage tanks



Hoval EnerVal — **100-2000 l**




Hoval EnerVal G — **800-6000 l**



Hoval EnerVal G cool — **800-6000 l**

Combination storage tank



Hoval DuoVal E/C

Electric heating elements



Hoval electric heating elements



Hoval photovoltaic electric heating elements with RemoteControl



Engineering

Hoval

CATALOGUE

Hoval CombiVal ER

Calorifier for combined heating
CombiVal ER (200-1000)



Hoval | Responsibility for energy and environment

Table of contents

- Description 5
- Part numbers 6
- Technical data 8
- Dimensions 17

Hoval calorifier CombiVal ER (200-500)

- Calorifier made of steel enamelled inside
- Plain-tube coil enamelled, permanently installed
- Magnesium protection anode built in
- Flange for electric heating element
- Thermal insulation made of polyurethane hard foam foamed on the calorifier
- Dismantable foil jacket, colour red, ERW (200) colour white
- Including thermometer
- Sensor channel

On request
- Flange-mounted electric heating element

Delivery
- Calorifier with foil jacket completely installed

Hoval calorifier CombiVal ER (800,1000)

- Calorifier made of steel, enamelled inside
- Plain-tube coil enamelled, permanently installed
- 2 magnesium protection anodes built in
- Flange below as cleaning flange or for the installation as flange-mounted electric heating element or dummy flange with immersion sleeve
- Flange above as additional cleaning flange
- Flange for electric heating element or immersion sleeve
- Thermal insulation made of polyester fleece with foil jacket, colour red
- With thermometer
- Two terminal bars for contact sensor

On request
- Flange-mounted electric heating element
- Flange including immersion sleeve

Delivery
- Calorifier and thermal insulation completely installed (can be removed for installation)



ER (200-500) ER (800,1000)

Range

CombiVal type		
ER	(200)	B
ERW	(200)	B
ER	(300)	B
ER	(400)	B
ER	(500)	B
ER	(800)	
ER	(1000)	

A⁺ → F

Calorifier



CombiVal ER (200-1000)


Calorifier made of steel enamelled inside.
With built-in, enamelled plain-tube coil.

CombiVal ER type	Content l	Heating surface m^2	Part No.
(200)	196	0.90	7015 960
(200) ERW (white)	196	0.95	7015 961
(300)	302	1.45	7015 962
(400)	382	1.80	7015 963
(500)	473	1.90	7015 964
(800)	735	3.70	7014 422
(1000)	968	4.50	7014 423

Energy efficiency class
see “Description”

Electric heating elements
see chapter “Electric heating elements”

Accessories



Flange cover 180 – ¾″ — 2077 035
for the installation of the Correx® impressed current anode in flange Ø 180/110 mm, enamelled on the inside with Rp ¾″ sleeve
Seal included



Flange with immersion sleeve — 6028 468
for temperature sensor made of steel. On domestic water side, enamelled inside.
Flange dimensions:
- Outer Ø 180 mm,
- Pitch circle Ø 150 mm, 8 x M10

Immersion sleeve dimensions:
- Installation length = 120 mm,
- Outer Ø: 24 mm, inner Ø: 20 mm



Kit Correx® impressed current anode UP2.3-919-L395/1 — 684 760
for long-term corrosion protection for installation in the enamelled calorifier with reduction R 1¼″ (ET) - Rp 1″ (IT) and R 1″ (ET) - Rp ¾″ (IT)
Installation length: 395 mm
Connection cable length: 1 x 2000 mm
1 Correx® impressed current anode

In every case, either a Correx® impressed current anode or one/two magnesium protection anodes are allowed to be used.

	Part No.
 **Immersion sensor TF/2P/5/6T, L = 5.0 m with plug** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m with plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 788
 **Immersion sensor TF/2P/5/6T, L = 5.0 m** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m without plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2055 888
 **Immersion sensor TF/12N/2.5/6T, L = 2.5 m** for gas boiler with RS-OT Cable length: 2.5 m Sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 791
At TopTronic® E, immersion sensor is included in the boiler controller or in the heating controller set.	
 **Calorifier thermostat control TW 12** Universal thermostat controller for thermostatic pump charge demand, setting in casing, visible from outside. 15 ... 95 °C, switching difference 6 K, capillar length 700 mm incl. fastening material for Hoval calorifier, can be used with integrated immersion sleeve	6010 080
Thermal water mixer see “Various system components”	

Services

Services and associated scope of services see separate catalogue “Hoval Services”	
Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.	

CombiVal ER (200-500)

Type		(200)	(300)	(400)	(500)
• Volume	l	196	302	382	473
• Max. operating/test pressure SVGW	bar	6/12	6/12	6/12	6/12
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13	10/13
• Max. operating temperature	°C	95	95	95	95
• Thermal insulation PU-foam foamed onto calorifier	mm	75	50	75	75
• Thermal insulation λ	W/mK	0.027	0.027	0.027	0.027
• Fire protection class		B2	B2	B2	B2
• Heat loss at 65 °C	W	49	67	65	76
• Transport weight	kg	77	104	134	146
• U value	W/m^2K	0.328	0.404	0.307	0.308
Heating battery (built in)					
• Heating surface	m^2	0.90	1.45	1.80	1.90
• Heating water	l	6.4	9.9	12.2	12.8
• Flow resistance [1)]	z value	7	10	12	13
• Max. operating/test pressure SVGW	bar	8/13	8/13	8/13	8/13
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13	10/13
• Max. operating temperature	°C	110	110	110	110
• Dimensions		see table of dimensions			

[1)] Flow resistance heating battery in mbar = flow rate $(m^3/h)^2$ x z (1 mbar = 0.1 kPa)

CombiVal ER (800,1000)

Type		(800)	(1000)
• Volume	l	735	968
• Max. operating/test pressure SVGW	bar	6/12	6/12
• Max. operating/test pressure DVGW	bar	10/13	10/13
• Max. operating temperature	°C	95	95
• Thermal insulation made of polyester fleece	mm	100	100
• Thermal insulation λ	W/mK	0.040	0.040
• Fire protection class		B2	B2
• Heat loss at 65 °C	W	127	142
• Transport weight	kg	251	324
• U value	W/m^2K	0.376	0.37
Heating battery (built in)			
• Heating surface	m^2	3.7	4.5
• Heating water	l	34.2	40.6
• Flow resistance [1)]	z value	6	8
• Max. operating/test pressure SVGW	bar	8/13	8/13
• Max. operating/test pressure DVGW	bar	10/13	10/13
• Max. operating temperature	°C	110	110
• Dimensions		see table of dimensions	

[1)] Flow resistance heating battery in mbar = flow rate $(m^3/h)^2$ x z (1 mbar = 0.1 kPa)

Performance figure

Selection of the calorifier type
at a hot water temperature of 45 °C

Reading example
see engineering

	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
1	200			200		
2	300	200		300	200	
3			200			200
4	400			400		
5	500	300		500	300	
6			300			300
7						
8						
9	800	400				
10	1000	500		800	400	
11			400	1000	500	
12			500			
13						400
14						500
15						
16						
17						
18						
19						
20						
21						
22		800				
23						
24						
25						
26		1000				
27						
28					800	
29						
30			800			
31						
32						
33					1000	
34						
35			1000			
36						
37						
38						800
39						
40						
41						
42						
43						
44						
45						1000
46						
47						
48						
49						
50						


	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
51						
52						
53						
54						
55						
56						
57						
58						
59						
60						
61						
62						
63						
64						
65						
66						
67						
68						
69						
70						
71						
72						
73						
74						
75						
76						
77						
78						
79						
80						
81						
82						
83						
84						
85						
86						
87						
88						
89						
90						
91						
92						
93						
94						
95						
96						
97						
98						
99						
100						

T = Heating flow
NL = Performance figure
Performance figure NL acc. to DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bathroom – 4 rooms – 3.5 persons)
[1] Calculation with simultaneity factor according to DIN 4708 (preferred for Switzerland)
[2] Calculation with simultaneity factor according to Dresden Technical University

10 min peak output/N number with domestic hot water 45 °C

according to DIN 4708 (Comfort) and Dresden Technical University (Standard)

Reading example
see Engineering



CombiVal ER (200)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ER (300)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C





* Calorifier heated to 60 °C


CombiVal ER (400)

Hot water output
Continuous output


Reading example
see engineering








Pressure drop heating coil – delivery head charging pump





* Calorifier heated to 60 °C

CombiVal ER (500)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ER (800)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ER (1000)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump




Hot water 60 °C




* Calorifier heated to 60 °C


CombiVal ER (200-500)


(Dimensions in mm)





CombiVal ER (800,1000)





1	Cold water	type (200)	G ¾″	(ET)
		type (300-500)	G 1″	(ET)
		type (800,1000)	G 1¼″	(ET)
2	Domestic hot water	type (200)	G ¾″	(ET)
		type (300-500)	G 1″	(ET)
		type (800,1000)	G 1¼″	(ET)
5	Heating flow	type (200-500)	G 1″	(ET)
		type (800,1000)	G 1¼″	(ET)
6	Heating return	type (200-500)	G 1″	(ET)
		type (800,1000)	G 1¼″	(ET)
7	Circulation (removable insulated cap Ø 100 mm)		G ¾″	(ET)
8	Thermometer			

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

10	Sensor channel, inner Ø 11 mm	type (200-500)	
	Sensor terminal strip (zip fastener)	type (800,1000)	
11	Removable cap (Ø 60 mm) for positioning the sensor in the sensor channel	type (200-500)	
12	Hand-hole flange (flange-mounted electric heating element) Ø 180/120 mm, hole circle 150 mm, 8 x M10 (Mounting of a flange-mounted electric heating element: - bottom, possible. - top, not possible.)		
14	Anode sleeve	type (200-500)	Rp 1″ (IT)
		type (800,1000)	Rp 1¼″ (IT)
16	Transport strap	type (800,1000)	

CombiVal ER type	D	d	H	h	a	e	g	i	k	m	n	p	r	s	t	u	v	V**	Tilting dimension
(200)	600	450	1464	-	55	680	902	689	194	1373	249	-	-	-	1229	1060	635	650	1583
(300)	700	597	1326	-	55	609	921	721	221	1229	276	-	-	-	1069	860	795	810	1524
(400)	750	597	1623	-	55	747	1112	909	221	1526	276	-	-	-	1356	1060	795	810	1788
(500)	750	597	1953	-	55	917	1265	966	221	1856	276	-	-	-	1686	1360	795	810	2093
(800)	950	750	2040	1937	105	-	1422	1319	293	1891	383	1408	1348	1478	1648	1400	975	1020	1962
(1000)	1050	850	2063	1962	106	-	1494	1327	301	1905	391	1446	1386	1516	1676	1400	1075	1120	1991

** When using a flange-mounted electric heating element

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval CombiVal ESR

Calorifier with large coil for combined heating CombiVal ESR (200-400)



Hoval | Responsibility for energy and environment

Table of contents

- Description 5
- Part numbers 6
- Technical data 8
- Dimensions 14

Hoval calorifier CombiVal ESR (200-400)

- Calorifier made of steel enamelled inside
- Large plain-tube coil enamelled, permanently installed
- Magnesium protection anode built in
- Flange for electric heating element
- Thermal insulation made of polyurethane hard foam foamed on the calorifier
- Dismantable foil jacket, colour red
- Including thermometer
- Sensor channel

On request
- Flange-mounted electric heating element

Delivery
- Calorifier with foil jacket completely installed



Range
CombiVal type

ESR	(200)	B
ESR	(300)	B
ESR	(400)	B

A⁺ → F

Calorifier



CombiVal ESR (200-400)

Calorifier made of steel, enamelled inside, with permanently installed plain-tube coil.

CombiVal ESR type	Content l	Heating surface m^2	Part No.
(200)	193	1.8	7015 965
(300)	298	2.6	7015 966
(400)	379	3.8	7015 967


Energy efficiency class
see “Description”

Authorisation number

CombiVal ESR (200-400)
SVGW test number 0503-4950

Electric heating elements
see chapter “Electric heating elements”

Accessories



Flange cover 180 – ¾″ 2077 035
for the installation of the Correx® impressed current anode in flange Ø 180/110 mm, enamelled on the inside with Rp ¾″ sleeve
Seal included



Flange with immersion sleeve 6028 468
for temperature sensor made of steel. On domestic water side, enamelled inside.
Flange dimensions:
- Outer Ø 180 mm,
- Pitch circle Ø 150 mm, 8 x M10
Immersion sleeve dimensions:
- Installation length = 120 mm,
- Outer Ø: 24 mm, inner Ø: 20 mm



Kit Correx® impressed current anode UP2.3-919-L395/1 684 760
for long-term corrosion protection for installation in the enamelled calorifier with reduction R 1¼″ (ET) - Rp 1″ (IT) and R 1″ (ET) - Rp ¾″ (IT)
Installation length: 395 mm
Connection cable length: 1 x 2000 mm
1 Correx® impressed current anode

In every case, either a Correx® impressed current anode or one/two magnesium protection anodes are allowed to be used.

		Part No.
	**Immersion sensor TF/2P/5/6T, L = 5.0 m with plug** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m with plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 788
	**Immersion sensor TF/2P/5/6T, L = 5.0 m** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m without plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2055 888
	**Immersion sensor TF/12N/2.5/6T, L = 2.5 m** for gas boiler with RS-OT Cable length: 2.5 m Sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 791
	At TopTronic® E, immersion sensor is included in the boiler controller or in the heating controller set.	
	**Calorifier thermostat control TW 12** Universal thermostat controller for thermostatic pump charge demand, setting in casing, visible from outside. 15 ... 95 °C, switching difference 6 K, capillar length 700 mm incl. fastening material for Hoval calorifier, can be used with integrated immersion sleeve	6010 080
	Thermal water mixer see “Various system components”	

Services

	Services and associated scope of services see separate catalogue “Hoval Services”	
	Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.	

CombiVal ESR (200-400)

Type		(200)	(300)	(400)
• Volume	l	193	298	379
• Max. operating/test pressure SVGW	bar	6/12	6/12	6/12
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13
• Max. operating temperature	°C	95	95	95
• Thermal insulation PU-foam, foamed onto calorifier	mm	75	50	75
• Thermal insulation λ	W/mK	0.027	0.027	0.027
• Fire protection class		B2	B2	B2
• Heat loss at 65 °C	W	48	68	68
• Transport weight	kg	91	118	156
• U value	W/m^2K	0.32	0.41	0.32
Heating battery (built in)				
• Heating surface	m^2	1.8	2.6	3.8
• Heating water content	l	12.2	16	34
• Flow resistance [1)]	z value	13	17	6
• Max. operating/test pressure SVGW	bar	8/13	8/13	8/13
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13
• Max. operating temperature	°C	110	110	110
• Dimensions			see table of dimensions	

[1)] Flow resistance heating battery in mbar = flow rate $(m^3/h)^2$ x z (1 mbar = 0.1 kPa)

Performance figure

Selection of the calorifier type
at a hot water temperature of 45 °C

Reading example
see engineering

	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
1				200		
2	200					
3						
4	300			300		
5		200			200	
6	400		200	400		200
7						
8						
9		300				
10			300		300	
11						300
12						
13						
14		400				
15						
16						
17					400	
18			400			
19						
20						
21						
22						400
23						
24						
25						
26						
27						
28						
29						
30						
31						
32						
33						
34						
35						
36						
37						
38						
39						
40						
41						
42						
43						
44						
45						
46						
47						
48						
49						
50						


	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
51						
52						
53						
54						
55						
56						
57						
58						
59						
60						
61						
62						
63						
64						
65						
66						
67						
68						
69						
70						
71						
72						
73						
74						
75						
76						
77						
78						
79						
80						
81						
82						
83						
84						
85						
86						
87						
88						
89						
90						
91						
92						
93						
94						
95						
96						
97						
98						
99						
100						

T = heating flow
NL = performance figure
Performance figure NL acc. to DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bathroom – 4 rooms – 3.5 persons)
[1] Calculation with simultaneity factor according to DIN 4708 (preferred for Switzerland)
[2] Calculation with simultaneity factor according to Dresden Technical University

10 min peak output/N number with domestic hot water 45 °C

according to DIN 4708 (Comfort) and Dresden Technical University (Standard)

Reading example
see Engineering




CombiVal ESR (200)


Hot water output
Continuous output


Reading example
see engineering


Heat input [kW]


Continuous output [l/h] with heating flow ...











* Calorifier heated to 60 °C

CombiVal ESR (300)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ESR (400)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump




Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ESR (200-400)

(Dimensions in mm)



1	Cold water	type (200)	G ¾″	(ET)	
		type (300,400)	G 1″	(ET)	
2	Domestic hot water	type (200)	G ¾″	(ET)	
		type (300,400)	G 1″	(ET)	
5	Heating flow	type (200,300)	G 1″	(ET)	
		type (400)	G 1¼″	(ET)	
6	Heating return	type (200,300)	G 1″	(ET)	
		type (400)	G 1¼″	(ET)	
7	Circulation (removable insulated cap Ø 100 mm)		G ¾″	(ET)	
8	Thermometer				
10	Sensor channel, inner Ø 11 mm				
11	Removable cap (Ø 60 mm) for positioning the sensor in the sensor channel				
12	Hand-hole flange (flange-mounted electric heating element) Ø 180/120 mm, pitch circle 150 mm, 8 x M10				
14	Anode sleeve	Rp 1″ (IT)			

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

CombiVal ESR type	D	d	H	a	e	g	i	k	m	n	t	u	v	V**	Tilting dimension
(200)	600	450	1464	55	740	789	902	194	1373	249	1229	1060	635	650	1583
(300)	700	597	1326	55	669	850	991	221	1229	276	1069	860	745	760	1524
(400)	750	597	1629	55	807	1112	1324	221	1526	276	1359	1060	795	810	1788

** When using a flange-mounted electric heating element

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval CombiVal ESSR

Calorifier with special coil for combined heating CombiVal ESSR (500-1000)



Hoval | Responsibility for energy and environment

Table of contents

- Description 5
- Part numbers 6
- Technical data 8
- Dimensions 14

Hoval calorifier CombiVal ESSR (500)

- Calorifier made of steel enamelled inside
- Plain-tube coil, with large heating surface, enamelled, permanently installed
- Magnesium protection anode built in
- Flange for electric heating element
- Thermal insulation made of polyurethane hard foam foamed on the calorifier
- Dismantable foil jacket, colour red
- Sensor channel
- Including thermometer

On request
- Flange-mounted electric heating element
- Screw-in electric heating element 1½"

Delivery
- Calorifier with foil jacket completely installed

Hoval calorifier CombiVal ESSR (800,1000)

- Calorifier made of steel, enamelled inside
- Plain-tube coil, with large heating surface, enamelled, permanently installed
- Correx® potentiostat included
- 2 impressed current anodes incl. connecting cable integrated
- Flange below as cleaning flange or for the installation of a flange-mounted electric heating element or dummy flange with immersion sleeve
- Flange above as additional cleaning flange or for the installation of a flange-mounted electric heating element
- Thermal insulation made of polyester fleece with foil jacket, colour red
- Two terminal bars for contact sensor
- Including thermometer

On request
- Flange-mounted electric heating element

Delivery
- Calorifier and thermal insulation completely installed (can be removed for installation)



Range
CombiVal type

ESSR	(500)	B
ESSR	(800)	
ESSR	(1000)	
		A⁺ → F

Calorifier



CombiVal ESSR (500-1000)

Calorifier made of steel enamelled inside.
With built-in, enamelled plain-tube coil.

CombiVal ESSR type	Content l	Heating surface m^2	Part No.
(500)	465	5.90	7015 970
(800)	733	7.00	7018 051
(1000)	961	9.15	7018 052


Authorisation number

CombiVal ESSR (500-1000)
SVGW test number 0503-4950

Energy efficiency class
see “Description”

Electric heating elements
see chapter “Electric heating elements”

Accessories



Flange cover 180 – ¾″
for the installation of the Correx®
impressed current anode in flange
Ø 180/110 mm, enamelled on the
inside with Rp ¾″ sleeve
Seal included

2077 035



Flange with immersion sleeve
for temperature sensor made of steel.
On domestic water side, enamelled
inside.
Flange dimensions:
- Outer Ø 180 mm,
- Pitch circle Ø 150 mm, 8 x M10
Immersion sleeve dimensions:
- Installation length = 120 mm,
- Outer Ø: 24 mm, inner Ø: 20 mm

6028 468



Kit Correx® impressed current anode UP2.3-919-L395/1
for long-term corrosion protection for
installation in the enamelled calorifier
with reduction R 1¼″ (ET) - Rp 1″ (IT)
and R 1″ (ET) - Rp ¾″ (IT)
Installation length: 395 mm
Connection cable length: 1 x 2000 mm
1 Correx® impressed current anode

Included in the scope of delivery
for ESSR (800,1000)

684 760

In every case, either a Correx® impressed current anode or one/two magnesium protection anodes are allowed to be used.

	Part No.
 **Immersion sensor TF/2P/5/6T, L = 5.0 m with plug** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m with plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 788
 **Immersion sensor TF/2P/5/6T, L = 5.0 m** for TopTronic® E controller modules/ module expansions with exception of basic module district heating/fresh water or basic module district heating com, cable length: 5 m without plug sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2055 888
 **Immersion sensor TF/12N/2.5/6T, L = 2.5 m** for gas boiler with RS-OT Cable length: 2.5 m Sensor sleeve diameter: 6 x 50 mm, dewpoint-proof, operating temperature: −20 ... 105 °C, protection class: IP67	2056 791
At TopTronic® E, immersion sensor is included in the boiler controller or in the heating controller set.	
 **Calorifier thermostat control TW 12** Universal thermostat controller for thermostatic pump charge demand, setting in casing, visible from outside. 15 ... 95 °C, switching difference 6 K, capillar length 700 mm incl. fastening material for Hoval calorifier, can be used with integrated immersion sleeve	6010 080
Thermal water mixer see “Various system components”	

Services

Services and associated scope of services see separate catalogue “Hoval Services”	
Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.	

CombiVal ESSR (500-1000)

Type		(500)	(800)	(1000)
• Volume	l	465	733	961
• Max. operating/test pressure SVGW	bar	6/12	6/12	6/12
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13
• Max. operating temperature	°C	95	95	95
• Thermal insulation PU foam, foamed onto calorifier	mm	75	-	-
• Thermal insulation polyester fleece	mm	-	100	100
• Thermal insulation λ	W/mK	0.027	0.027	0.027
• Fire protection class		B2	B2	B2
• Heat loss at 65 °C	W	78	126	144
• Transport weight	kg	232	304	387
• U value	W/m^2K	0.316	0.374	0.375
Heating battery (built in)				
• Heating surface	m²	5.9	7	9.15
• Heating water	l	41	49.4	64.6
• Flow resistance [1)]	z value	10	11	14
• Max. operating/test pressure SVGW	bar	8/13	8/13	8/13
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13
• Max. operating temperature	°C	110	110	110
• Dimensions			see table of dimensions	

[1)] Flow resistance heating battery in mbar = flow rate $(m^3/h)^2$ x z (1 mbar = 0.1 kPa)

Performance figure

Selection of the calorifier type
at a hot water temperature of 45 °C

Reading example
see engineering

	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12	500					
13						
14				500		
15						
16						
17						
18	800					
19						
20						
21		500				
22				800		
23						
24	1000					
25						
26					500	
27						
28			500			
29						
30						
31						
32						
33						
34						
35						
36				1000		500
37						
38		800				
39						
40						
41						
42						
43						
44			800			
45						
46						
47						
48		1000				
49					800	
50						


	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v						
51						
52						
53						
54						
55						
56						
57						800
58			1000			
59						
60						
61						
62						
63					1000	
64						
65						
66						
67						
68						
69						
70						
71						
72						
73						
74						
75						
76						1000
77						
78						
79						
80						
81						
82						
83						
84						
85						
86						
87						
88						
89						
90						
91						
92						
93						
94						
95						
96						
97						
98						
99						
100						

T = heating flow
NL = performance figure
Performance figure NL acc. to DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bathroom – 4 rooms – 3.5 persons)
[1] Calculation with simultaneity factor according to DIN 4708 (preferred for Switzerland)
[2] Calculation with simultaneity factor according to Dresden Technical University

10 min peak output/N number with domestic hot water 45 °C

according to DIN 4708 (Comfort) and Dresden Technical University (Standard)


Reading example
see Engineering





CombiVal ESSR (500)


Hot water output
Continuous output


Reading example
see engineering











* Calorifier heated to 60 °C

CombiVal ESSR (800)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump



Hot water 60 °C



* Calorifier heated to 60 °C

CombiVal ESSR (1000)


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Hot water 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump




Hot water 60 °C




* Calorifier heated to 60 °C

CombiVal ESSR (500)

(Dimensions in mm)



CombiVal ESSR (800,1000)



1	Cold water	type (500)	G 1″	(ET)
		type (800,1000)	G 1½″	(ET)
2	Domestic hot water	type (500)	G 1″	(ET)
		type (800,1000)	G 1½″	(ET)
5	Heating flow	type (500)	G 1¼″	(ET)
		type (800,1000)	G 1½″	(ET)
6	Heating return	type (500)	G 1¼″	(ET)
		type (800,1000)	G 1½″	(ET)
7	Circulation (removable insulated cap Ø 100 mm)		G ¾″	(ET)
8	Thermometer			

10	Sensor channel, inner Ø 11 mm Sensor terminal strip (zip fastener)	type (500) type (800,1000)	
11	Removable cap (Ø 60 mm) for positioning the sensor in the sensor channel	type (500)	
12	Hand-hole flange (flange-mounted electric heating element) Ø 180/120 mm, pitch circle 150 mm, 8 x M10		
13	Connection for screw-in electric heating element (cap Ø 100 mm)	type (500)	Rp 1½″ (IT)
14	Anode sleeve	type (500)	Rp 1¼″ (IT)
15	Correx® impressed current anode sleeve	type (800,1000)	Rp ¾″ (IT)
16	Transport strap	type (800,1000)	

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

CombiVal ESSR type	D	d	H	h	a	e	g	i	k	m	n	p	r	q	s	t	u	v	V**	Tilting dimension
(500)	750	597	1953	-	55	977	920	1235	221	1856	276	-	-	1319	-	1686	1360	795	810	2093
(800)	950	750	2033	1937	104	-	995	1265	292	1890	382	1413	520	-	1497	1647	1400	975	1020	1962
(1000)	1050	850	2063	1963	103	-	1046	1361	298	1902	388	1446	525	-	1486	1653	1400	1075	1120	1991

** When using a flange-mounted electric heating element

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval TransTherm® aqua

Calorifier charging system
TransTherm® aqua L
TransTherm® aqua L-FW



Table of contents

- Description 5
- Part numbers 7
- Technical data 14
- Dimensions 21
- Example 36

Calorifier charging system
Consisting of:
- calorifier charging module TransTherm® aqua L
  TransTherm® aqua L-FW (for indirect connection to the (district) heating network)
- hot water charging tank CombiVal E or CombiVal C (optional)

Calorifier charging module TransTherm® aqua L

- Fully assembled station with plate heat exchanger for the provision of domestic hot water using the tank storage principle
- Intended for wall installation
- The primary side (heating side) contains the three-way valve, high-efficiency pump, air-bleeding, contact sensor and the filling and drain valve, line balancing valve. These components ensure a constant flow temperature at the plate heat exchanger. Pipes made from steel
- The secondary side (DHW side) contains the safety valve (10 bar), non-return valve, filling/drain valve and balancing valve.
  A flow sensor ensures the correct charging temperature for the hot process water storage tank. Pipes made from stainless steel
- Stainless steel plate heat exchanger 1.4404, copper-soldered or copper-free
- EPP insulation, 30 mm, for the heat exchanger
- Switch-on and switch-off of the charging pump is regulated via two sensors (included in the scope of delivery) in the storage tank.
- Mount tank sensor on the tank on site and connect it to the controller
- T-piece with dummy plug for on-site connection of the circulation group. Connect the pump to the controller on site.
- TopTronic® E control with integrated thermal disinfection of the DHW storage tank (anti-legionella circuit)

Calorifier charging module TransTherm® aqua L-FW

- Fully assembled station with plate heat exchanger for the provision of domestic hot water using the tank storage principle
- Intended for wall installation
- The primary side (heating side) includes a flow rate controller with through valve and safety function, ventilation, sensor and fill/drain valve.
  These components ensure a constant flow temperature at the plate heat exchanger. Pipes made from steel
- The secondary side (DHW side) contains the safety valve (10 bar), non-return valve, filling/drain valve and balancing valve.
  A flow sensor ensures the correct charging temperature for the hot process water storage tank. Pipes made from stainless steel
- Stainless steel plate heat exchanger 1.4404, copper-soldered or copper-free
- EPP insulation, 30 mm, for the heat exchanger
- Switch-on and switch-off of the charging pump is regulated via two sensors (included in the scope of delivery) in the storage tank.
- Mount tank sensor on the tank on site and connect it to the controller







Range
Calorifier charging module

TransTherm® aqua L type	Output kW
(1-10)	50
(1-16)	90
(1-20)	115
(1-30)	175
(1-40)	230
(1-50)	275

Calorifier charging module

TransTherm® aqua L-FW type	Output kW
(2-10)	50
(2-16)	90
(2-20)	115
(2-30)	175
(2-40)	230
(2-50)	275

Range
Hot water charging tank

CombiVal E		Content l
(300)	B	301
(500)	B	475
(800)		747
(1000)		968
(1500)		1472
(2000)		2000

A⁺ → F

CombiVal C		Content l
(300)	B	289
(400)	B	411
(500)	B	490
(750)	B	756
(1000)	B	990
(1500)	B	1415
(2000)	B	1975
(2500)	B	2450

A⁺ → F

Delivery
- The storage tank required is not included in the scope of delivery

On site
- Installation of a circulation unit;
  the necessary connection is provided.
- Electrical connection of the controller

Heating network
- Nominal pressure: 16 bar
- Maximum pressure: 13 bar
- Min. differential pressure: 0.6 bar
- Max. differential pressure: 12 bar
- Operating temperature: 70 ... 110 °C
- Maximum temperature: 120 °C

Suitable hot water charging tanks
see next page

TopTronic® E controller

TopTronic® E basic module district heating/ fresh water
- Control unit for controlling district heating transfer stations in non-communicative networks and the corresponding consumers with integrated control functions for
  - primary valve control
  - cascade management
  - 1 heating/cooling circuit with mixer
  - 1 heating/cooling circuit without mixer
  - 1 hot water charging circuit
  - various additional functions
- Various functions for hot water:
  - selection of different basic programs (week programs, economy mode, holiday until, etc.)
  - various operating modes (e.g. accumulator priority or parallel mode)
  - buffer storage circuit on the primary or secondary side
  - adjustable loading criteria (e.g. adjustable loading times, undershooting the minimum nominal value, etc.)
  - adjustable switch-off criteria (e.g. achieving the setpoint valve, achieving the lower sensor setpoint value, etc.)

- adjustable loading block (if the loading flow temperature is too low, the setpoint temperature is not reached, differential temperature-dependent solar circuit control)
- definable switching times for recirculation pump control

- Outdoor sensor
- Immersion sensor (calorifier sensor)
- Contact sensor (flow temperature sensor)
- Complete plug set for DH module
- RPM-regulated pumps

No further module expansions or controller modules can be installed in the control panel!

Option

TopTronic® E control module
- Simple, intuitive operating concept
- Display of the most important operating states
- Configurable start screen
- Operating mode selection
- Configurable day and week programs
- Operation of all connected Hoval CAN bus modules
- Commissioning wizard
- Service and maintenance function
- Fault message management
- Analysis function
- Weather display (with HovalConnect option)
- Adaptation of the heating strategy based on the weather forecast (with HovalConnect option)

Notice
The TopTronic® E control module for operating the basic module district heating/fresh water must be ordered separately!

Further information about the TopTronic® E
see “Controls”

Delivery
- All armatures required for operation, such as flow balancing and shut-off valves, backflow preventer, air-bleeding and drain valve are fitted.

Caution
As a result of thermal disinfection of the domestic hot water for legionella protection, increased water temperatures (at least 65 ... 70 °C) occur. Depending on the water quality, this may result in increased calcification at the installed armatures and heat exchangers and also brings the risk of scalding at the tapping points. Corresponding protective measures must be implemented on site.

CombiVal E (300-2000)
- Charging tank made of steel, enamelled inside (without built-in heating coil) for combination with calorifier charging module TransTherm® aqua L
- (300-1000) with one flange
  (1500,2000) with two flanges
  in each case with installed dummy flange plate for maintenance or installation of a flange-mounted electric heating element
- (300-1000) one magnesium protection anode built in
  (1500,2000) two magnesium protection anodes built in
- Thermal insulation made of
  - (300,500) polyurethane rigid foam, directly foamed, with dismantable foil jacket, 1-part, colour red
  - (800-2000) polyester fleece with foil jacket, completely removable, colour red
    (800-1500) 2-part
    (2000) 3-part
- Including thermometer
- (300,500) sensor channel
  (800-2000) two terminal bars for contact sensor

Delivery
- (300,500) with foil jacket completely installed
- (800-2000) with thermal insulation completely installed (removable)

Design on request
- Flange-mounted electric heating element

On site
- Installation of the thermometer
- Attachment of the glue-on protection rosettes to the thermal insulation

Water quality
see end of this brochure

CombiVal C (300-2500)
- Charging tank made of stainless steel (1.4571/1.4404) (without built-in heating coil) for combination with calorifier charging module
  TransTherm® aqua L
- (300-1000) with one flange
  (1500-2000) with two flanges
  (2500) with one manhole
  in each case with installed dummy flange plate for maintenance or, for types (300-2000), installation of a flange-mounted electric heating element
- Thermal insulation: Neodul® insulation (EPS rigid foam outside and 20 mm polyester fibre fleece inside) with zip, outer jacket made of polypropylene, colour red
  (300-1000) 2-piece
  (1500) 3-piece
  (2000-2500) 4-piece
- Thermometer incl. immersion sleeve loose (packed with the product)
- Sensor terminal bar
- Observe limit values for chloride content in domestic water – see “Engineering”.

Delivery
- (300-1000) with thermal insulation completely installed (can be removed for bringing in)
- (1500-2500) thermal insulation separately packed

Design on request
- (300-2000) Flange-mounted electric heating element

On site
- Installation of immersion sleeve for thermometer
- (1500-2500) Installation of the thermal insulation and attaching the protection rosettes

Calorifier charging module



Authorisation number

TransTherm® aqua L
SVGW test number 2407-7331

TransTherm® aqua L

Fully assembled station with plate heat exchanger for the provision of domestic hot water using the storage tank charging principle and built-in Hoval TopTronic® E control
The required storage tank is not supplied.

TransTherm® aqua L	Output kW	Part No.
(1-10)	50	8005 864
(1-16)	90	8005 865
(1-20)	115	8005 866
(1-30)	175	8005 867
(1-40)	230	8005 868
(1-50)	275	8005 869

Version with copper-free heat exchanger

TransTherm® aqua L

with copper-free heat exchanger

TransTherm® aqua L	Output kW	Part No.
(1-10)	50	8006 491
(1-16)	90	8006 492
(1-20)	115	8006 493
(1-30)	175	8006 494
(1-40)	230	8006 495
(1-50)	275	8006 496

Calorifier charging module



Authorisation number

TransTherm® aqua L-FW
SVGW test number 2407-7331

TransTherm® aqua L-FW

Fully assembled station with plate heat exchanger for the provision of domestic hot water using the storage tank charging principle and built-in Hoval TopTronic® E control
The required storage tank is not supplied.

TransTherm® aqua L	Output kW	Part No.
(2-10)	50	8006 353
(2-16)	90	8006 354
(2-20)	115	8006 355
(2-30)	175	8006 356
(2-40)	230	8006 367
(2-50)	275	8006 368


Version with copper-free heat exchanger

TransTherm® aqua L-FW

with copper-free heat exchanger

TransTherm® aqua L	Output kW	Part No.
(2-10)	50	8006 497
(2-16)	90	8006 498
(2-20)	115	8006 499
(2-30)	175	8006 500
(2-40)	230	8006 501
(2-50)	275	8006 502

Accessories



TopTronic® E control module black with 4.3″ colour touchscreen
For operation of all controller modules connected to the bus system (basic, solar, buffer modules etc.)
Connection to the Hoval bus system via RJ45 plug connection or via plug terminals (max. 0.75 mm²), flat design with flexible installation option
Installation:
- in control panel of the heat generator
- in the Hoval wall casing
- in the control panel front,

black high-gloss cover, customer-specific configurable start screen,
Display of current weather or weather forecast (only possible in combination with HovalConnect)

Consisting of:
- TopTronic® E control module black
- Clamping device set control module
- RJ45-RAST 5 CAN cable, L = 500

6043 844



Return changeover valve set
Consisting of:
- temperature sensor
- changeover valve
- drive (8 sec.) DN 20-40
- drive (30 sec.) DN 50-80
- seals
- screw connections

Nominal diameter	Output kW	k_{vs} m³/h	Part No.
DN 20	50-90	6.3	7010 832
DN 25	115-175	10	7010 836
DN 32	230-275	16	7011 009
DN 40	350	25	7011 025
DN 50	450	40	7016 331
DN 65	580	63	7016 332
DN 80	700	100	7016 333

Notice
When using a circulation set with integration at the heat exchanger (also on-site circulating pump), it is imperative to install a return switching valve set.

Notice
Only for TransTransTherm® aqua L



Circulation set
for TransTherm® aqua L, L-FW, F
Piping of parts in contact with domestic water in stainless steel and gunmetal
Consisting of:
- temperature sensor PT1000
- recirculation pump Wilo Yonos PARA
- recirculation pump Wilo Para MAXO
- regulating valve
- non-return valve

Connection	Flow rate m³/h	Recirculation pump	Part No.
DN 20 ¾″ Rp	1.9	Z15/7.0 RKC	8005 279
DN 25 1″ Rp	3.4	Z25/180/08/F02	8005 280
DN 32 1¼″ Rp	5.8	Z25/180/08/F02	8005 281



Test valve DN 8 G ¼"
for TransTherm® aqua L, L-FW, F, FS
Test valve suitable for flame treatment
for hygienic-microbiologic
tests.

Part No. 2049 861



Sludge separator DM with magnet
made of technopolymer (PO) or
brass with insulation (MS)

Type	Connection inches	Flow rate at 1.2 m/s flow speed m³/h	k_v value m³/h	Part No.
DM PO	Rp 1"	1.3	10.5	2054 376
DM PO	Rp 1¼"	2.1	10.5	2085 523
DM MS	Rp 1½"	5.4	63.2	2085 527
DM MS	Rp 2"	8.2	70.0	2085 528

Additional sludge separators
see "Various system components"



Insulation for sludge separator
DM PO 1"
10 mm insulating caps made of PE-X foam
Thermal conductivity 0.035 W/mK
Fire resistance (DIN 4102): class B2

Part No. 2085 524



Insulation for sludge separator
DM PO 1¼"
10 mm insulating caps made of PE-X foam
Thermal conductivity 0.035 W/mK
Fire resistance (DIN 4102): class B2

Part No. 2086 031



Ball valve
Shut-off valve between heating network
and TransTherm aqua L-FW
Material: steel
Weld end/external thread

Size	Max. operating pressure bar	Max. operating temperature °C	External thread	Part No.
DN 25	25	150	G 1"	2085 081
DN 32	25	150	G 1¼"	2085 082

		Part No.
	**Temperature monitor 0 ... 120 °C** for TransTherm® aqua L, L-FW, F, FS	2048 299
	**Safety temperature monitor 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2048 300
	**Safety temperature limiter 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2049 619
	**Immersion sleeve G ½″ stainless steel for thermostat** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 8 mm, inner Ø: 6.5 mm	2048 285
	**Immersion sleeve G ½″ stainless steel for 2 thermostats** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 15 mm, inner Ø: 13.5 mm	2048 288

Hot water charging tank



CombiVal E

Enamelled charging tank
(without heating coil)

CombiVal E (300-1000) with one flange
CombiVal E (1500,2000) with two flanges
- (300,500) thermal insulation mounted with foil jacket
- (800-2000) Thermal insulation completely installed (removable)

CombiVal type	Content l	Part No.
E (300)	301	6044 187
E (500)	475	6044 188
E (800)	747	6044 189
E (1000)	968	6044 190
E (1500)	1472	6044 191
E (2000)	2000	6044 192



CombiVal C



Stainless steel charging tank
(without heating coil)

CombiVal C (300-1000) with one flange
CombiVal C (1500-2000) with two flanges
CombiVal C (2500) with one manhole thermal insulation
- (300-1000) completely installed (removable)
- (1500-2000) separately packed

CombiVal type	Content l	Part No.
C (300)	289	6065 396
C (400)	411	6065 397
C (500)	490	6065 398
C (750)	756	6065 399
C (1000)	990	6065 400
C (1500)	1415	6065 401
C (2000)	1975	6065 402
C (2500)	2450	6065 543

Energy efficiency class
see “Description”

Electric heating elements
see chapter “Electric heating elements”

	Part No.
For CombiVal E (300-2000)	
 **Flange cover 180** – ¾″ for the installation of the Correx® impressed current anode in flange Ø 180/110 mm, enamelled on the inside with Rp ¾″ sleeve Seal included	2077 035
 **UP 2.3-919** **Kit Correx® impressed current anode UP2.3-919-L395/1** for long-term corrosion protection for installation in the enamelled calorifier with reduction R 1¼″ (ET) - Rp 1″ (IT) and R 1″ (ET) - Rp ¾″ (IT) Installation length: 395 mm Connection cable length: 1 x 2000 mm 1 Correx® impressed current anode	684 760
Either a Correx® impressed current anode or one/two magnesium protection anodes may be used.	
For CombiVal C (300-2500)	
 **Flange cover 180** – 1½″ for the installation of the Correx® impressed current anode in flange Ø 180/110 mm, stainless steel with Rp 1½″ sleeve Seal and screws included	2077 911
 **UP 1.9-924** **Kit Correx® impressed current anode UP1.9-924-L395/1** for long-term corrosion protection for installation in the stainless steel calorifier with reduction R 1½″ - Rp ¾″ and R 1¼″ - Rp ¾″ Installation length: 395 mm Connection cable length: 1 x 3500 mm 1 Correx® impressed current anode (up to 800 l)	6031 813
The flange cover 180 – 1½″ must also be ordered for installation of the impressed current anode set.	
Services	
Services and associated scope of services see separate catalogue “Hoval Services”	
Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.	

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

			Flow temperature heating water											
			55 °C (1-...)						60 °C (1-...)					
Domestic water secondary	**TransTherm® aqua L TransTherm® aqua L-FW**		(10)	(16)	(20)	(30)	(40)	(50)	(10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
55/5 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.25**	**2.04**	**2.51**	**3.71**	**4.76**	**5.66**
	Q max.	kW	-	-	-	-	-	-	43	70	86	127	163	194
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.74**	**1.2**	**1.48**	**2.18**	**2.8**	**3.33**
55/10 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.11**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	-	-	-	-	-	-	38	70	86	127	163	193
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.73**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
55/15 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.76**	**1.46**	**1.95**	**3.06**	**4.23**	**5.4**
	Q max.	kW	-	-	-	-	-	-	26	50	67	105	145	185
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.56**	**1.08**	**1.44**	**2.26**	**3.12**	**3.98**
55/20 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.47**	**0.9**	**1.17**	**1.9**	**2.63**	**3.36**
	Q max.	kW	-	-	-	-	-	-	16	31	40	65	90	115
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.39**	**0.76**	**0.99**	**1.6**	**2.22**	**2.83**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	37	58	72	105	135	162	44	70	86	127	163	193
	V̇ secondary	**m³/h**	**0.71**	**1.11**	**1.37**	**2**	**2.58**	**3.09**	**0.84**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.73**	**4.81**	**5.69**
	Q max.	kW	38	58	72	105	135	162	44	70	86	128	165	195
	V̇ secondary	**m³/h**	**0.82**	**1.25**	**1.77**	**2.26**	**2.9**	**3.48**	**0.95**	**1.51**	**1.85**	**2.75**	**3.55**	**4.19**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.11**	**1.95**	**2.48**	**3.76**	**4.76**	**5.69**
	Q max.	kW	37	58	72	105	135	162	38	67	85	129	163	195
	V̇ secondary	**m³/h**	**0.91**	**1.43**	**1.77**	**2.58**	**3.32**	**3.99**	**0.94**	**1.65**	**2.09**	**3.18**	**4.01**	**4.8**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.15**	**2.03**	**2.55**	**3.7**	**4.75**	**5.69**	**0.96**	**1.69**	**2.13**	**3.24**	**3.63**	**5.16**
	Q max.	kW	33	58	73	106	136	163	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.05**	**3.91**	**4.69**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

			Flow temperature heating water											
			65 °C (1-...)						70 °C (1-...)					
Domestic water secondary	**TransTherm® aqua L TransTherm® aqua L-FW**		(10)	(16)	(20)	(30)	(40)	(50)	(10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.08**	**1.88**	**2.5**	**3.73**	**4.84**	**5.77**	**1.32**	**2.09**	**2.59**	**3.76**	**4.82**	**5.72**
	Q max.	kW	43	75	100	149	193	230	60	95	118	171	219	260
	V̇ secondary	**m³/h**	**0.67**	**1.17**	**1.55**	**2.33**	**3.01**	**3.59**	**0.94**	**1.48**	**1.84**	**2.67**	**3.42**	**4.06**
60/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**1.94**	**2.48**	**3.77**	**4.95**	**5.92**
	Q max.	kW	32	60	80	126	173	215	50	90	115	175	230	275
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.54**	**1.98**	**3.01**	**3.95**	**4.73**
60/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.55**	**1.05**	**1.38**	**2.13**	**3.08**	**3.96**	**0.97**	**1.8**	**2.37**	**3.73**	**4.84**	**5.72**
	Q max.	kW	22	42	55	85	123	158	44	82	108	170	220	260
	V̇ secondary	**m³/h**	**0.42**	**0.8**	**1.05**	**1.63**	**2.35**	**3.02**	**0.84**	**1.57**	**2.08**	**3.24**	**4.21**	**4.98**
60/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.3**	**0.6**	**0.8**	**1.28**	**1.75**	**2.33**	**0.62**	**1.14**	**2.05**	**2.4**	**3.43**	**4.22**
	Q max.	kW	12	24	32	51	70	93	28	52	68	109	156	192
	V̇ secondary	**m³/h**	**0.26**	**0.52**	**0.69**	**1.1**	**1.51**	**2**	**0.6**	**1.12**	**1.47**	**2.36**	**3.36**	**4.14**
55/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**2.09**	**2.53**	**3.74**	**4.84**	**5.76**
	Q max.	kW	32	60	80	126	173	215	50	95	115	170	220	262
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.63**	**1.97**	**2.92**	**3.78**	**4.5**
55/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.3**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.74**	**4.84**	**5.72**
	Q max.	kW	52	82	101	148	192	225	49	85	110	170	220	260
	V̇ secondary	**m³/h**	**0.99**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.24**	**4.21**	**4.98**
55/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.97**	**1.65**	**2.11**	**3.71**	**4.81**	**5.64**	**1.1**	**1.88**	**2.41**	**3.74**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.94**	**1.62**	**2.1**	**3.19**	**4.21**	**5**
55/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.25**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.56**	**4.84**	**5.72**
	Q max.	kW	50	82	101	148	192	225	49	85	110	162	220	260
	V̇ secondary	**m³/h**	**0.95**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.09**	**4.21**	**4.98**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.1**	**1.88**	**2.41**	**3.71**	**4.81**	**5.64**	**0.97**	**1.65**	**2.11**	**3.25**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**5**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.83**	**1.45**	**1.81**	**2.44**	**3.63**	**4.44**	**0.73**	**1.28**	**1.61**	**2.44**	**3.19**	**3.89**
	Q max.	kW	33	58	73	111	145	177	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

Temperature primary 70 °C flow/30 °C return

Domestic water heating

		TransTherm® aqua L	Cold water 10 °C, domestic water 60 °C					
		TransTherm® aqua L-FW	(10)	(16)	(20)	(30)	(40)	(50)
		kW	50	90	115	175	230	275
		m³/h	0.86	1.54	1.97	3.00	3.94	4.71
		l/min	14.3	25.7	32.9	50.0	65.7	78.6
		l/s	0.2	0.4	0.5	0.8	1.1	1.3
Tank size l								
300	**V̇s**	**l/10 min**	443	557	629	800	-	-
	Hourly output	l/h at 60 °C	1157	1843	2271	3300	-	-
	NL index		16	30	39	60	-	-
400	**V̇s**	**l/10 min**	543	657	729	900	-	-
	Hourly output	l/h at 60 °C	1257	1943	2371	3400	-	-
	NL index		18	32	41	64	-	-
500	**V̇s**	**l/10 min**	643	757	829	1000	1157	-
	Hourly output	l/h at 60 °C	1357	2043	2471	3500	4443	-
	NL index		20	34	43	66	88	-
800	**V̇s**	**l/10 min**	943	1057	1129	1300	1457	-
	Hourly output	l/h at 60 °C	1657	2343	2771	3800	4743	-
	NL index		26	40	49	73	96	-
1000	**V̇s**	**l/10 min**	1143	1257	1329	1500	1657	1786
	Hourly output	l/h at 60 °C	1857	2543	2971	4000	4943	5714
	NL index		30	45	54	77	100	119
1500	**V̇s**	**l/10 min**	-	1757	1829	2000	2157	2286
	Hourly output	l/h at 60 °C	-	3043	3471	4500	5443	6214
	NL index		-	56	65	89	112	131
2000	**V̇s**	**l/10 min**	-	2257	2329	2500	2657	2786
	Hourly output	l/h at 60 °C	-	3543	3971	5000	5943	6714
	NL index		-	67	77	101	124	143
2500	**V̇s**	**l/10 min**	-	2757	2829	3000	3157	3286
	Hourly output	l/h at 60 °C	-	4043	4471	5500	6443	7214
	NL index		-	79	89	113	137	160

V̇s **l/10 min** 10 min peak output at 60 °C

NL index Performance figure in accordance with DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bath – 4 rooms – 3.5 persons)

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

Tapping point (mixing temperature)		TransTherm® aqua L	Cold water 10 °C, domestic water 45 °C					
		TransTherm® aqua L-FW	(10)	(16)	(20)	(30)	(40)	(50)
		kW	50	90	115	175	230	275
		m³/h	1.22	2.20	2.82	4.29	5.63	6.73
		l/min	20.4	36.7	46.9	71.4	93.9	112.2
		l/s	0.3	0.6	0.8	1.2	1.6	1.9
Tank size l								
300	**V̇s**	**l/10 min**	633	796	898	1143	-	-
	Hourly output	l/h at 45 °C	1653	2633	3245	4714	-	-
	NL index		16	30	39	60	-	-
400	**V̇s**	**l/10 min**	776	939	1041	1286	-	-
	Hourly output	l/h at 45 °C	1796	2776	3388	4857	-	-
	NL index		18	32	41	64	-	-
500	**V̇s**	**l/10 min**	918	1082	1184	1429	1653	-
	Hourly output	l/h at 45 °C	1939	2918	3531	5000	6347	-
	NL index		20	34	43	66	88	-
800	**V̇s**	**l/10 min**	1347	1510	1612	1857	2082	-
	Hourly output	l/h at 45 °C	2367	3347	3959	5429	6776	-
	NL index		26	40	49	73	96	-
1000	**V̇s**	**l/10 min**	1633	1796	1898	2143	2367	2551
	Hourly output	l/h at 45 °C	2653	3633	4245	5714	7061	8163
	NL index		30	45	54	77	100	119
1500	**V̇s**	**l/10 min**	-	2510	2612	2857	3082	3265
	Hourly output	l/h at 45 °C	-	4347	4959	6429	7776	8878
	NL index		-	56	65	89	112	131
2000	**V̇s**	**l/10 min**	-	3224	3327	3571	3796	3980
	Hourly output	l/h at 45 °C	-	5061	5673	7143	8490	9592
	NL index		-	67	77	101	124	143
2500	**V̇s**	**l/10 min**	-	3939	4041	4286	4510	4694
	Hourly output	l/h at 45 °C	-	5776	6388	7857	9204	10306
	NL index		-	79	89	113	137	160

V̇s **l/10 min** 10 min peak output at 45 °C

NL index Performance figure in accordance with DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bath – 4 rooms – 3.5 persons)

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

Temperature primary 65 °C flow/30 °C return

Domestic water heating

		TransTherm® aqua L	Cold water 10 °C, domestic water 60 °C					
		TransTherm® aqua L-FW	(10)	(16)	(20)	(30)	(40)	(50)
		kW	32	60	80	126	173	215
		m³/h	0.55	1.03	1.37	2.16	2.97	3.69
		l/min	9.1	17.1	22.9	36.0	49.4	61.4
		l/s	0.2	0.3	0.4	0.6	0.8	1.0
Tank size l								
300	**V̇s**	**l/10 min**	391	471	529	660	-	-
	Hourly output	l/h at 60 °C	849	1329	1671	2460	-	-
	NL index		10	19	26	43	-	-
400	**V̇s**	**l/10 min**	491	571	629	760	-	-
	Hourly output	l/h at 60 °C	949	1429	1771	2560	-	-
	NL index		12	21	28	45	-	-
500	**V̇s**	**l/10 min**	591	671	729	860	994	-
	Hourly output	l/h at 60 °C	1049	1529	1871	2660	3466	-
	NL index		14	23	30	47	65	-
800	**V̇s**	**l/10 min**	891	971	1029	1160	1294	-
	Hourly output	l/h at 60 °C	1349	1829	2171	2960	3766	-
	NL index		19	30	36	53	72	-
1000	**V̇s**	**l/10 min**	1091	1171	1229	1360	1494	1614
	Hourly output	l/h at 60 °C	1549	2029	2371	3160	3966	4686
	NL index		24	33	41	59	77	94
1500	**V̇s**	**l/10 min**	-	1671	1729	1860	1994	2114
	Hourly output	l/h at 60 °C	-	2529	2871	3660	4466	5186
	NL index		-	44	52	69	89	106
2000	**V̇s**	**l/10 min**	-	2171	2229	2360	2494	2614
	Hourly output	l/h at 60 °C	-	3029	3371	4160	4966	5686
	NL index		-	56	64	81	102	119
2500	**V̇s**	**l/10 min**	-	2671	2729	2860	2994	3114
	Hourly output	l/h at 60 °C	-	3529	3871	4660	5466	6186
	NL index		-	65	75	93	113	131

V̇s **l/10 min** 10 min peak output at 60 °C

NL index Performance figure in accordance with DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bath – 4 rooms – 3.5 persons)

Performance data

TransTherm® aqua L (1-10 to 1-50) / TransTherm® aqua L-FW (2-10 to 2-50)

Tapping point (mixing temperature)		TransTherm® aqua L	Cold water 10 °C, domestic water 45 °C					
		TransTherm® aqua L-FW	(10)	(16)	(20)	(30)	(40)	(50)
		kW	32	60	80	126	173	215
		m³/h	0.78	1.47	1.96	3.09	4.24	5.27
		l/min	13.1	24.5	32.7	51.4	70.6	87.8
		l/s	0.2	0.4	0.5	0.9	1.2	1.5
Tank size l								
300	**V̇s**	**l/10 min**	559	673	755	943	-	-
	Hourly output	l/h at 45 °C	1212	1898	2388	3514	-	-
	NL index		10	19	26	43	-	-
400	**V̇s**	**l/10 min**	702	816	898	1086	-	-
	Hourly output	l/h at 45 °C	1355	2041	2531	3657	-	-
	NL index		12	21	28	45	-	-
500	**V̇s**	**l/10 min**	845	959	1041	1229	1420	-
	Hourly output	l/h at 45 °C	1498	2184	2673	3800	4951	-
	NL index		14	23	30	47	65	-
800	**V̇s**	**l/10 min**	1273	1388	1469	1657	1849	-
	Hourly output	l/h at 45 °C	1927	2612	3102	4229	5380	-
	NL index		19	30	36	53	72	-
1000	**V̇s**	**l/10 min**	1559	1673	1755	1943	2135	2306
	Hourly output	l/h at 45 °C	2212	2898	3388	4514	5665	6694
	NL index		24	33	41	59	77	94
1500	**V̇s**	**l/10 min**	-	2388	2469	2657	2849	3020
	Hourly output	l/h at 45 °C	-	3612	4102	5229	6380	7408
	NL index		-	44	52	69	89	106
2000	**V̇s**	**l/10 min**	-	3102	3184	3371	3563	3735
	Hourly output	l/h at 45 °C	-	4327	4816	5943	7094	8122
	NL index		-	56	64	81	102	119
2500	**V̇s**	**l/10 min**	-	3816	3898	4086	4278	4449
	Hourly output	l/h at 45 °C	-	5041	5531	6657	7808	8837
	NL index		-	65	75	93	113	131

V̇s **l/10 min** 10 min peak output at 45 °C

NL index Performance figure in accordance with DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bath – 4 rooms – 3.5 persons)

Hot water charging tank CombiVal E (300-2000)


Type		(300)	(500)	(800)	(1000)	(1500)	(2000)
• Volume	l	301	475	747	968	1472	2000
• Max. operating/test pressure SVGW	bar	6/12	6/12	6/12	6/12	6/12	6/12
• Max. operating/test pressure DVGW	bar	10/13	10/13	10/13	10/13	10/13	10/13
• Max. operating temperature	°C	95	95	95	95	95	95
• Thermal insulation PU hard foam, foam-lined	mm	75	75	-	-	-	-
• Thermal insulation polyester fleece	mm	-	-	100	100	120	120
• Thermal insulation λ	W/mK	0.027	0.027	0.040	0.040	0.040	0.040
• Fire protection class		B2	B2	B2	B2	B2	B2
• Heat loss at 65 °C	W	58	75	128	139	170	190
• Transport weight	kg	97	126	205	264	400	600
• U value	W/m^2K	0.290	0.303	0.381	0.362	0.339	0.325


Hot water charging tank CombiVal C (300-2500)

Type		(300)	(400)	(500)	(750)	(1000)	(1500)	(2000)	(2500)
• Volume	l	289	411	490	756	990	1415	1975	2450
• Max. operating/test pressure SVGW	bar	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12
• Max. operating temperature	°C	95	95	95	95	95	95	95	95
• Thermal insulation		Neodul® insulation (EPS rigid foam outside and polyester fibre fleece inside)							
	mm	100	100	100	130	130	150	150	150
• Thermal insulation λ (EPS)	W/mK	0.0316	0.0316	0.0316	0.0316	0.0316	0.0316	0.0316	0.0316
• Fire protection class		B2	B2	B2	B2	B2	B2	B2	B2
• Heat loss at 65 °C	W	59	68	73	84	99	114	135	169
• Weight (only container)	kg	55	65	70	118	155	200	250	430
• Transport weight (incl. thermal insulation and packaging/pallet)	kg	75	90	100	165	210	260	325	510
• U value	W/m^2K	0.327	0.327	0.327	0.249	0.249	0.216	0.216	0.216

Charging module TransTherm® aqua L (1-10)

(Dimensions in mm)





1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(1-10)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)


TransTherm® aqua L	Weight in kg
(1-10)	56


[1] Optional, connection and installation on site


Gp = straight internal thread

Charging module TransTherm® aqua L (1-10)


(Dimensions in mm)







Version incl. circulation set




		(1-10)
1	Safety valve Hot water 10 bar	
2	Filling/drain valve	
3	Heat exchanger	
4	Primary three-way valve	
5	Primary circulating pump	
6	Secondary circulating pump	
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)

[1] Optional, connection and installation on site


Gp = straight internal thread


Charging module TransTherm® aqua L (1-16, 1-20)

(Dimensions in mm)



	A
(1-16)	1059
(1-20)	1073





1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(1-16) (1-20)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)


[1] Optional, connection and installation on site


Gp = straight internal thread


TransTherm® aqua L	Weight in kg
(1-16)	58
(1-20)	60

Charging module TransTherm® aqua L (1-16, 1-20)


(Dimensions in mm)







Version incl. circulation set



	A	B	C
(1-16)	112	166	1078
(1-20)	128	193	1121

1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Three-way valve primary
5 Primary circulating pump
6 Secondary circulating pump


		(1-16) (1-20)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)

[1] Optional, connection and installation on site


Gp = straight internal thread


Charging module TransTherm® aqua L (1-30 to 1-50)

(Dimensions in mm)



	A
(1-30)	1074
(1-40)	1058
(1-50)	1079





1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(1-30) (1-40) (1-50)
7	Circulation [1]	DN 32, Rp 1¼″ (25, Rp 1″) (20, Rp ¾″) (IT)
8	Hot water	DN 32, Rp 1¼″ (IT)
9	Cold water	DN 32, Rp 1¼″ (IT)
10	Flow heating water	DN 32, Rp 1¼″ (IT)
11	Return heating water	DN 32, Gp 1½″ (IT)


TransTherm® aqua L	Weight in kg
(1-30)	66
(1-40)	68
(1-50)	70


[1] Optional, connection and installation on site


Gp = straight internal thread

Charging module TransTherm® aqua L (1-30 to 1-50)


(Dimensions in mm)







Version incl. circulation set



	A	B
(1-30)	224	1185
(1-40)	221	1182
(1-50)	219	1180

1 Safety valve Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Primary three-way valve
5 Primary circulating pump
6 Secondary circulating pump


		(1-30) (1-40) (1-50)
7	Circulation [1]	DN 32, Rp 1¼″ (25, Rp 1″) (20, Rp ¾″) (IT)
8	Hot water	DN 32, Rp 1¼″ (IT)
9	Cold water	DN 32, Rp 1¼″ (IT)
10	Flow heating water	DN 32, Rp 1¼″ (IT)
11	Return heating water	DN 32, Gp 1½″ (IT)


[1] Optional, connection and installation on site


Gp = straight internal thread

Charging module TransTherm® aqua L-FW (2-10)

(Dimensions in mm)







1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(2-10)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)


[1] Optional, connection and installation on site


Gp = straight internal thread


TransTherm® aqua L-FW	Weight in kg
(2-10)	56

Charging module TransTherm® aqua L-FW (2-10)


(Dimensions in mm)







Version incl. circulation set



1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Primary three-way valve
5 Primary circulating pump
6 Secondary circulating pump


		(2-10)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)


[1] Optional, connection and installation on site


Gp = straight internal thread

Charging module TransTherm® aqua L-FW (2-16, 2-20)

(Dimensions in mm)







1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(2-16) (2-20)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)


TransTherm® aqua L-FW	Weight in kg
(2-16)	58
(2-20)	60


[1] Optional, connection and installation on site


Gp = straight internal thread

Charging module TransTherm® aqua L-FW (2-16, 2-20)

(Dimensions in mm)








	A	B	C
(2-16)	1000	245	1134
(2-20)	987	257	1146

Version incl. circulation set



1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Three-way valve primary
5 Primary circulating pump
6 Secondary circulating pump


		(2-16) (2-20)
7	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
8	Hot water	DN 25, Rp 1″ (IT)
9	Cold water	DN 20, Gp 1″ (IT)
10	Flow heating water	DN 25, Rp 1″ (IT)
11	Return heating water	DN 25, Gp 1″ (IT)

[1] Optional, connection and installation on site


Gp = straight internal thread


Charging module TransTherm® aqua L-FW (2-30 to 2-50)

(Dimensions in mm)



	A	B
(2-30)	943	1129
(2-40)	943	1129
(2-50)	992	1146





1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(2-30) (2-40) (2-50)
7	Circulation [1]	DN 32, Rp 1¼″ (25, Rp 1″) (20, Rp ¾″) (IT)
8	Hot water	DN 32, Rp 1¼″ (IT)
9	Cold water	DN 32, Rp 1¼″ (IT)
10	Flow heating water	DN 32, Rp 1¼″ (IT)
11	Return heating water	DN 32, Gp 1½″ (IT)


TransTherm® aqua L-FW	Weight in kg
(2-30)	66
(2-40)	68
(2-50)	70

[1] Optional, connection and installation on site


Gp = straight internal thread


Charging module TransTherm® aqua L-FW (2-30 to 2-50)

(Dimensions in mm)




	A	B	C
(2-30)	106	1109	203
(2-40)	106	1109	203
(2-50)	97	1146	249





Version incl. circulation set



	D	E	F
(2-30)	254	287	1290
(2-40)	254	299	1302
(2-50)	302	299	1348

1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Primary three-way valve
5 Primary circulating pump
6 Secondary circulating pump


		(2-30) (2-40) (2-50)
7	Circulation [1]	DN 32, Rp 1¼″ (25, Rp 1″) (20, Rp ¾″) (IT)
8	Hot water	DN 32, Rp 1¼″ (IT)
9	Cold water	DN 32, Rp 1¼″ (IT)
10	Flow heating water	DN 32, Rp 1¼″ (IT)
11	Return heating water	DN 32, Gp 1½″ (IT)


[1] Optional, connection and installation on site

Gp = straight internal thread


CombiVal E (300,500)

(Dimensions in mm)





CombiVal E (800-2000)



1	Cold water	type (300,500)	G 1¼″	(ET)
		type (800-2000)	G 2″	(ET)
2	Domestic hot water	type (300,500)	G 1¼″	(ET)
		type (800-2000)	G 2″	(ET)
5	Charging flow – hot	type (300,500)	G 1¼″	(ET)
		type (800-2000)	G 2″	(ET)
6	Charging return – cold	type (300,500)	G 1¼″	(ET)
		type (800-2000)	G 2″	(ET)
7	Circulation (removable insulated cap Ø 100 mm)	type (300,500)	G ¾″	(ET)
		type (800-2000)	G 1¼″	(ET)

8	Thermometer			
10	Sensor channel, inner Ø 11 mm	type (300,500)		
	Sensor terminal strip (zip fastener)	type (800-2000)		
11	Removable cap (Ø 60 mm) for positioning the sensor in the sensor channel	type (300,500)		
12	Hand-hole flange (flange-mounted electric heating element) Ø 180/120 mm, pitch circle 150 mm, 8 x M10			
12*	**Attention:** type (800,1000) does not have a second flange			
14	Anode sleeve	type (300,500)	G 1″	(IT)
		type (800-2000)	G 1¼″	(IT)
14*	Anode sleeve	type (1500,2000)	G 1¼″	(IT)
16	Transport strap	type (800-2000)		


Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

CombiVal E type	D	d	H	h	a	k	e	g	m	n	p	r	s	t	u	v	V**	Tilting dimension
(300)	650	500	1850	-	235	-	945	1160	1584	325	-	-	-	1505	1360	745	785	1961
(500)	750	597	1960	-	238	-	996	1225	1674	275	-	-	-	1500	1360	745	785	2082
(800)	950	750	2030	1938	101	347	-	1150	1893	352	-	-	1336	1505	1400	975	1020	1960
(1000)	1050	850	2060	1968	100	355	-	1158	1910	360	-	-	1331	1500	1400	1075	1120	2000
(1500)	1240	1000	2240	2133	105	375	-	1357	2049	390	890	1167	1521	1657	1450	1265	1310	2370
(2000)	1440	1200	2150	2044	118	406	-	1388	1933	421	921	1118	1248	1498	1350	1465	1510	2350

** When using a flange-mounted electric heating element

CombiVal C (300-1000)

(Dimensions in mm)



1	Cold water with baffle plate	type (300)	Rp 1¼″	(IT)
		type (400,500)	Rp 1½″	(IT)
		type (750,1000)	Rp 2″	(IT)
2	Hot water	type (300)	Rp 1¼″	(IT)
		type (400,500)	Rp 1½″	(IT)
		type (750,1000)	Rp 2″	(IT)
3	Charging flow – hot	type (300-500)	Rp 1″	(IT)
		type (750,1000)	Rp 1¼″	(IT)
4	Charging return – cold	type (300-500)	Rp 1″	(IT)
		type (750,1000)	Rp 1¼″	(IT)
5	Circulation with baffle plate	type (300-500)	Rp 1″	(IT)
		type (750,1000)	Rp 1¼″	(IT)
6	Drain	type (300-500)	Rp ½″	(IT)
		type (750,1000)	Rp ¾″	(IT)

7 Sleeve (Rp ½″ (IT)) for mountable immersion sleeve and thermometer (L = 100 mm, inner Ø = 8 mm)

8 Hand-hole flange
Ø 180/120 mm, pitch circle 150 mm, 8 x M10 or optional:
- flange-mounted electric heating element or
- impressed current anode set with flange cover, 180 – 1½″ (IT)

10 Sensor terminal bar 600 x 30 mm
2 x type (300-1000)

11 Immersion sleeve M16 x 1.5 for sensor/thermostat


12	Charging flow – MAGRO	type (300-500)	Rp 1″	(IT)
		type (750,1000)	Rp 1¼″	(IT)
13	Charging return – cold	type (300-500)	Rp 1″	(IT)
		type (750,1000)	Rp 1¼″	(IT)


Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

CombiVal C type	a	b	c	d	D	e	f	g	h	j	k	l	m	n	p	r	s	Tilting dimension
(300)	60	240	375	500	700	840	1050	1285	1680	10	1355	1450	135	205	174	295	820	1720
(400)	70	285	420	600	800	885	1095	1330	1745	10	1368	1495	135	205	187	340	850	1795
(500)	80	295	430	650	850	895	1105	1340	1765	10	1378	1505	130	190	197	350	860	1820
(750)	80	335	470	750	1010	935	1310	1590	2140	60	1674	1595	165	235	203	390	1030	2195
(1000)	80	365	500	900	1160	965	1215	1495	1945	10	1384	1575	165	235	203	420	930	2020


CombiVal C (1500,2000)


(Dimensions in mm)





CombiVal C (2500)





1 Cold water with baffle plate type (1500,2000) Rp 2″ (IT)
type (2500) DN 65/PN 10
2 Hot water type (1500,2000) Rp 2″ (IT)
type (2500) DN 65/PN 10
3 Charging flow – hot type (1500-2000) Rp 1½″ (IT)
4 Charging return – cold type (1500-2000) Rp 1½″ (IT)
5 Circulation with baffle plate type (1500-2000) Rp 1½″ (IT)
6 Drain type (1500-2000) Rp ¾″ (IT)
7 Sleeve (Rp ½″ (IT)) for mountable immersion sleeve and thermometer (L = 100 mm, inner Ø = 8 mm)
8 Hand-hole flange
Ø 180/120 mm, pitch circle 150 mm, 8 x M10 or optional:
- flange-mounted electric heating element or
- impressed current anode set with flange cover, 180 – 1½″ (IT)

9 Manhole flange
Ø 400/480 mm, pitch circle 445 mm, 26 x M14 or optional Flange adapter:
- for electric heating element or
- for impressed current anode set with flange cover, 180 – 1½″ (IT)

10 Sensor terminal bar 600 x 30 mm
2 x type (1500-2500)
11 Immersion sleeve M16 x 1.5 for sensor/thermostat
12 Charging flow – MAGRO type (1500-2000) Rp 1½″ (IT)
13 Charging return – cold type (1500-2000) Rp 1½″ (IT)


Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

CombiVal C type	a	b	c	d	D	e	f	g	h	i	j	k	l	m	n	p	r	s	Tilting dimension
(1500)	80	375	510	1000	1300	975	1350	1755	2250	1580	60	1674	1635	165	260	203	430	1070	2330
(2000)	80	405	530	1100	1400	1005	1580	2035	2555	1860	165	1909	1770	165	260	191	460	1230	2635
(2500)	120	515	790	1300	1600	1115	1580	1930	2500	-	60	1719	1775	190	275	248	570	1180	2620

Water heating

TransTherm® aqua L

- Circulation via storage tank
- Storage tank charging system



TTE-FW	Basic module district heating/fresh water
TW	Flow temperature monitor (if required)
VFP	Primary flow sensor
VFW	Flow sensor domestic hot water
RLF	Primary return sensor
RLF2	Return sensor domestic cold water
SF1	Calorifier sensor 1
SF2	Calorifier sensor 2
RLFZ	Circulation sensor
SLP1	Calorifier charging pump primary
SLP2	Calorifier charging pump secondary
YFW	Flow rate sender with through valve and safety function
ZKP	Recirculation pump

Option


BM	TopTronic® E control module

Notice
A safety valve (6 bar) must be installed in the cold water line. The loading module is already protected with a safety valve (10 bar).

Water heating

TransTherm® aqua L-FW

- Circulation via storage tank
- Storage tank charging system



TTE-FW	Basic module district heating/fresh water
TW	Flow temperature monitor (if required)
VFP	Primary flow sensor
VFW	Flow sensor domestic hot water
RLF	Primary return sensor
RLF2	Return sensor domestic cold water
SF1	Calorifier sensor 1
SF2	Calorifier sensor 2
RLFZ	Circulation sensor
SLP1	Calorifier charging pump primary
SLP2	Calorifier charging pump secondary
YFW	Flow rate sender with through valve and safety function
ZKP	Recirculation pump
Option	
BM	TopTronic® E control module

Notice
A safety valve (6 bar) must be installed in the cold water line. The loading module is already protected with a safety valve (10 bar).

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval TransTherm® aqua

Calorifier continuous flow system TransTherm® aqua F (6-10)-(6-50)



Hoval | Responsibility for energy and environment

Table of contents

- Description 5
- Part numbers 6
- Technical data 10
- Dimensions 17
- Example 21

Calorifier continuous flow system

Consisting of:
- fresh water module TransTherm® aqua F
- buffer storage tank (option)

Fresh water module TransTherm® aqua F

- Fully installed station with plate heat exchanger for the provision of domestic hot water using the continuous flow principle
- Intended for wall installation
- The primary side (heating side) contains the three-way valve, high-efficiency pump, ventilation, filling/drain valve and balancing valve. These components ensure a constant flow temperature at the plate heat exchanger. Pipes made from steel
- The secondary side (DHW side) contains the safety valve (10 bar), non-return valve and a filling/drain valve. A flow sensor ensures the correct hot water temperature. Pipes made from stainless steel
- Stainless steel plate heat exchanger 1.4404, copper-soldered or copper-free
- EPP insulation, 30 mm, for the heat exchanger
- Flow sensor
- Switch-on and switch-off of the charging pump is regulated via two sensors (included in the scope of delivery) in the storage tank
- Mount tank sensor on the tank on site and connect it to the controller
- T-piece with dummy plug for on-site connection of the circulation group. Connect the pump to the controller on site.
- TopTronic® E control with integrated thermal disinfection of the DHW storage tank (anti-legionella circuit)

Delivery
- The buffer storage tank required is not included in the scope of delivery

On site
- Installation of a circulation unit; the necessary connection is provided
- Electrical connection of the controller

TopTronic® E controller

TopTronic® E basic module district heating/fresh water
- Control unit for controlling district heating transfer stations in non-communicative networks and the corresponding consumers with integrated control functions for
  - primary valve control
  - cascade management
  - 1 heating/cooling circuit with mixer
  - 1 heating/cooling circuit without mixer
  - 1 hot water charging circuit
  - various additional functions

- Various functions for hot water:
  - selection of different basic programs (week programs, economy mode, holiday until, etc.)
  - various operating modes (e.g. accumulator priority or parallel mode)
  - buffer storage circuit on the primary or secondary side
  - adjustable loading criteria (e.g. adjustable loading times, undershooting the minimum nominal value, etc.)
  - adjustable switch-off criteria (e.g. achieving the setpoint valve, achieving the lower sensor setpoint value, etc.)
  - adjustable loading block (if the loading flow temperature is too low, the setpoint temperature is not reached, differential temperature-dependent solar circuit control)
- Definable switching times for recirculation pump control
- Outdoor sensor
- Immersion sensor (calorifier sensor)
- Contact sensor (flow temperature sensor)
- Complete plug set for DH module
- speed-controlled pumps

No further module expansions or controller modules can be installed in the control panel!

Option

TopTronic® E control module
- Simple, intuitive operating concept
- Display of the most important operating states
- Configurable start screen
- Operating mode selection
- Configurable day and week programs
- Operation of all connected Hoval CAN bus modules
- Commissioning wizard
- Service and maintenance function
- Fault message management
- Analysis function
- Weather display (with HovalConnect option)
- Adaptation of the heating strategy based on the weather forecast (with HovalConnect option)



Range
Fresh water module

TransTherm® aqua F type	Output kW
(6-10)	50
(6-16)	90
(6-20)	115
(6-30)	175
(6-40)	230
(6-50)	275

Notice
The TopTronic® E control module for operating the basic module district heating/fresh water must be ordered separately!

Further information about the TopTronic® E
see “Controls”

Delivery
- All armatures required for operation, such as flow balancing and shut-off valves, backflow preventer, air-bleeding and drain valve are fitted.

Caution
As a result of thermal disinfection of the domestic hot water for legionella protection, increased water temperatures (at least 65 ... 70 °C) occur. Depending on the water quality, this may result in increased calcification at the installed armatures and heat exchangers and also brings the risk of scalding at the tapping points. Corresponding protective measures must be implemented on site.

Hot water connection for application according to the SVGW (Swiss association for electricity, gas, district heating and water)
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.

Fresh water module



Authorisation number

TransTherm® aqua F (6-10)-(6-50)
SVGW test number 2407-7331

TransTherm® aqua F

Fully assembled station with plate heat exchanger for the provision of domestic hot water using the continuous flow principle and built-in Hoval TopTronic® E control
The required buffer storage tank is not supplied.

TransTherm® aqua F	Output kW	Part No.
(6-10)	50	8006 387
(6-16)	90	8006 388
(6-20)	115	8006 389
(6-30)	175	8006 390
(6-40)	230	8006 391
(6-50)	275	8006 392


Version with copper-free heat exchanger

TransTherm® aqua F

with copper-free heat exchanger

TransTherm® aqua F	Output kW	Part No.
(6-10)	50	8006 521
(6-16)	90	8006 522
(6-20)	115	8006 523
(6-30)	175	8006 524
(6-40)	230	8006 525
(6-50)	275	8006 526

Accessories

	Part No.
	
TopTronic® E control module black with 4.3″ colour touchscreen For operation of all controller modules connected to the bus system (basic, solar, buffer modules etc.) Connection to the Hoval bus system via RJ45 plug connection or via plug terminals (max. 0.75 mm²), flat design with flexible installation option Installation: - in control panel of the heat generator - in the Hoval wall casing - in the control panel front, black high-gloss cover, customer-specific configurable start screen, Display of current weather or weather forecast (only possible in combination with HovalConnect) Consisting of: - TopTronic® E control module black - Clamping device set control module - RJ45-RAST 5 CAN cable, L = 500	6043 844
	
Return changeover valve set Consisting of: - temperature sensor - changeover valve - drive (8 sec.) DN 20-40 - drive (30 sec.) DN 50-80 - seals - screw connections	

Nominal diameter	Output kW	k_{vs} m³/h	Part No.
DN 20	50-90	6.3	7010 832
DN 25	115-175	10	7010 836
DN 32	230-275	16	7011 009
DN 40	350	25	7011 025
DN 50	450	40	7016 331
DN 65	580	63	7016 332
DN 80	700	100	7016 333

Notice
When using a circulation set (also on-site recirculation pump), it is imperative to install a return switching valve set.



Circulation set
for TransTherm® aqua L, L-FW, F
Piping of parts in contact with domestic water in stainless steel and gunmetal
Consisting of:
- temperature sensor PT1000
- recirculation pump Wilo Yonos PARA
- recirculation pump Wilo Para MAXO
- regulating valve
- non-return valve

Connection	Flow rate m³/h	Recirculation pump	Part No.
DN 20 ¾″ Rp	1.9	Z15/7.0 RKC	8005 279
DN 25 1″ Rp	3.4	Z25/180/08/F02	8005 280
DN 32 1¼″ Rp	5.8	Z25/180/08/F02	8005 281



Test valve DN 8 G ¼"
for TransTherm® aqua L, L-FW, F, FS
Test valve suitable for flame treatment
for hygienic-microbiologic
tests.

Part No. 2049 861



Sludge separator DM with magnet
made of technopolymer (PO) or
brass with insulation (MS)

Type	Connection	Flow rate at 1.2 m/s flow speed	k_v value	Part No.
	inches	m^3/h	m^3/h	
DM PO	Rp 1"	1.3	10.5	2054 376
DM PO	Rp 1¼"	2.1	10.5	2085 523
DM MS	Rp 1½"	5.4	63.2	2085 527
DM MS	Rp 2"	8.2	70.0	2085 528

Additional sludge separators
see "Various system components"



Insulation for sludge separator
DM PO 1"
10 mm insulating caps made of PE-X foam
Thermal conductivity 0.035 W/mK
Fire resistance (DIN 4102): class B2

Part No. 2085 524



Insulation for sludge separator
DM PO 1¼"
10 mm insulating caps made of PE-X foam
Thermal conductivity 0.035 W/mK
Fire resistance (DIN 4102): class B2

Part No. 2086 031

		Part No.
	**Temperature monitor 0 ... 120 °C** for TransTherm® aqua L, L-FW, F, FS	2048 299
	**Safety temperature monitor 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2048 300
	**Safety temperature limiter 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2049 619
	**Immersion sleeve G ½″ stainless steel for thermostat** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 8 mm, inner Ø: 6.5 mm	2048 285
	**Immersion sleeve G ½″ stainless steel for 2 thermostats** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 15 mm, inner Ø: 13.5 mm	2048 288

Services

Services and associated scope of services
see separate catalogue “Hoval Services”

Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.

Performance data

TransTherm® aqua F (6-10 to 6-50)

Domestic water secondary	TransTherm® aqua F		Flow temperature heating water 55 °C (6-...)						60 °C (6-...)					
			(10)	(16)	(20)	(30)	(40)	(50)	(10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
55/5 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.25**	**2.04**	**2.51**	**3.71**	**4.76**	**5.66**
	Q max.	kW	-	-	-	-	-	-	43	70	86	127	163	194
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.74**	**1.2**	**1.48**	**2.18**	**2.8**	**3.33**
55/10 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.11**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	-	-	-	-	-	-	38	70	86	127	163	193
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.73**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
55/15 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.76**	**1.46**	**1.95**	**3.06**	**4.23**	**5.4**
	Q max.	kW	-	-	-	-	-	-	26	50	67	105	145	185
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.56**	**1.08**	**1.44**	**2.26**	**3.12**	**3.98**
55/20 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.47**	**0.9**	**1.17**	**1.9**	**2.63**	**3.36**
	Q max.	kW	-	-	-	-	-	-	16	31	40	65	90	115
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.39**	**0.76**	**0.99**	**1.6**	**2.22**	**2.83**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	37	58	72	105	135	162	44	70	86	127	163	193
	V̇ secondary	**m³/h**	**0.71**	**1.11**	**1.37**	**2**	**2.58**	**3.09**	**0.84**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.73**	**4.81**	**5.69**
	Q max.	kW	38	58	72	105	135	162	44	70	86	128	165	195
	V̇ secondary	**m³/h**	**0.82**	**1.25**	**1.77**	**2.26**	**2.9**	**3.48**	**0.95**	**1.51**	**1.85**	**2.75**	**3.55**	**4.19**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.11**	**1.95**	**2.48**	**3.76**	**4.76**	**5.69**
	Q max.	kW	37	58	72	105	135	162	38	67	85	129	163	195
	V̇ secondary	**m³/h**	**0.91**	**1.43**	**1.77**	**2.58**	**3.32**	**3.99**	**0.94**	**1.65**	**2.09**	**3.18**	**4.01**	**4.8**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.15**	**2.03**	**2.55**	**3.7**	**4.75**	**5.69**	**0.96**	**1.69**	**2.13**	**3.24**	**3.63**	**5.16**
	Q max.	kW	33	58	73	106	136	163	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.05**	**3.91**	**4.69**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**
45/5 °C	T return primary	°C	19	18	18	18	18	17	17	16	16	16	16	15
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.9**	**2.9**	**3.8**	**4.61**	**0.86**	**1.92**	**2.91**	**2.91**	**3.82**	**4.63**
	Q max.	kW	35	80	123	123	162	199	42	95	145	145	192	235
	V̇ secondary	**m³/h**	**0.76**	**1.73**	**2.65**	**2.65**	**3.50**	**4.27**	**0.90**	**2.05**	**3.13**	**3.13**	**4.14**	**5.05**
45/10 °C	T return primary	°C	21	21	20	20	20	20	20	19	19	19	18	18
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.89**	**2.89**	**3.81**	**4.62**	**0.86**	**1.92**	**2.84**	**2.84**	**3.63**	**4.32**
	Q max.	kW	33	74	114	114	151	185	39	89	133	133	172	207
	V̇ secondary	**m³/h**	**0.81**	**1.84**	**2.81**	**2.81**	**3.74**	**4.56**	**0.97**	**2.20**	**3.29**	**3.29**	**4.25**	**5.09**
45/15 °C	T return primary	°C	24	23	23	23	23	23	23	22	21	21	21	21
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.91**	**2.91**	**3.81**	**4.62**	**0.87**	**1.8**	**2.61**	**2.61**	**3.33**	**3.98**
	Q max.	kW	30	69	106	106	139	170	37	78	115	115	148	178
	V̇ secondary	**m³/h**	**0.88**	**1.99**	**3.05**	**3.05**	**4.02**	**4.90**	**1.07**	**2.26**	**3.31**	**3.31**	**4.26**	**5.12**
45/20 °C	T return primary	°C	27	26	26	26	26	26	25	26	24	24	24	24
	V̇ primary	**m³/h**	**0.86**	**1.92**	**2.91**	**2.91**	**3.71**	**4.41**	**0.85**	**1.63**	**2.36**	**2.36**	**3.02**	**3.61**
	Q max.	kW	27	63	96	96	124	148	33	65	96	96	123	148
	V̇ secondary	**m³/h**	**0.96**	**2.18**	**3.33**	**3.33**	**4.28**	**5.13**	**1.16**	**2.27**	**3.32**	**3.32**	**4.28**	**5.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua F (6-10 to 6-50)

Domestic water secondary	TransTherm® aqua F		Flow temperature heating water: 65 °C (6-...) (10)	(16)	(20)	(30)	(40)	(50)	70 °C (6-...) (10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.08**	**1.88**	**2.5**	**3.73**	**4.84**	**5.77**	**1.32**	**2.09**	**2.59**	**3.76**	**4.82**	**5.72**
	Q max.	kW	43	75	100	149	193	230	60	95	118	171	219	260
	V̇ secondary	**m³/h**	**0.67**	**1.17**	**1.55**	**2.33**	**3.01**	**3.59**	**0.94**	**1.48**	**1.84**	**2.67**	**3.42**	**4.06**
60/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**1.94**	**2.48**	**3.77**	**4.95**	**5.92**
	Q max.	kW	32	60	80	126	173	215	50	90	115	175	230	275
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.54**	**1.98**	**3.01**	**3.95**	**4.73**
60/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.55**	**1.05**	**1.38**	**2.13**	**3.08**	**3.96**	**0.97**	**1.8**	**2.37**	**3.73**	**4.84**	**5.72**
	Q max.	kW	22	42	55	85	123	158	44	82	108	170	220	260
	V̇ secondary	**m³/h**	**0.42**	**0.8**	**1.05**	**1.63**	**2.35**	**3.02**	**0.84**	**1.57**	**2.08**	**3.24**	**4.21**	**4.98**
60/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.3**	**0.6**	**0.8**	**1.28**	**1.75**	**2.33**	**0.62**	**1.14**	**2.05**	**2.4**	**3.43**	**4.22**
	Q max.	kW	12	24	32	51	70	93	28	52	68	109	156	192
	V̇ secondary	**m³/h**	**0.26**	**0.52**	**0.69**	**1.1**	**1.51**	**2**	**0.6**	**1.12**	**1.47**	**2.36**	**3.36**	**4.14**
55/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**2.09**	**2.53**	**3.74**	**4.84**	**5.76**
	Q max.	kW	32	60	80	126	173	215	50	95	115	170	220	262
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.63**	**1.97**	**2.92**	**3.78**	**4.5**
55/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.3**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.74**	**4.84**	**5.72**
	Q max.	kW	52	82	101	148	192	225	49	85	110	170	220	260
	V̇ secondary	**m³/h**	**0.99**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.24**	**4.21**	**4.98**
55/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.97**	**1.65**	**2.11**	**3.71**	**4.81**	**5.64**	**1.1**	**1.88**	**2.41**	**3.74**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.94**	**1.62**	**2.1**	**3.19**	**4.21**	**5**
55/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.25**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.56**	**4.84**	**5.72**
	Q max.	kW	50	82	101	148	192	225	49	85	110	162	220	260
	V̇ secondary	**m³/h**	**0.95**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.09**	**4.21**	**4.98**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.1**	**1.88**	**2.41**	**3.71**	**4.81**	**5.64**	**0.97**	**1.65**	**2.11**	**3.25**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**5**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.83**	**1.45**	**1.81**	**2.44**	**3.63**	**4.44**	**0.73**	**1.28**	**1.61**	**2.44**	**3.19**	**3.89**
	Q max.	kW	33	58	73	111	145	177	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**
45/5 °C	T return primary	°C	16	15	14	14	14	13	15	13	13	13	12	12
	V̇ primary	**m³/h**	**0.87**	**1.83**	**2.64**	**2.64**	**3.38**	**4.03**	**0.84**	**1.62**	**2.35**	**2.35**	**3.01**	**3.59**
	Q max.	kW	48	104	152	152	196	236	52	104	152	152	196	236
	V̇ secondary	**m³/h**	**1.04**	**2.24**	**3.27**	**3.27**	**4.23**	**5.07**	**1.13**	**2.24**	**3.28**	**3.28**	**4.23**	**5.07**
45/10 °C	T return primary	°C	19	17	17	17	17	16	17	16	16	16	15	15
	V̇ primary	**m³/h**	**0.87**	**1.69**	**2.45**	**2.45**	**3.13**	**3.73**	**0.77**	**1.49**	**2.17**	**2.17**	**2.78**	**3.32**
	Q max.	kW	45	91	134	134	172	206	46	91	133	133	172	206
	V̇ secondary	**m³/h**	**1.13**	**2.25**	**3.30**	**3.30**	**4.24**	**5.09**	**1.13**	**2.24**	**3.29**	**3.29**	**4.24**	**5.09**
45/15 °C	T return primary	°C	21	20	20	20	20	19	20	19	19	19	19	18
	V̇ primary	**m³/h**	**0.8**	**1.55**	**2.24**	**2.24**	**2.87**	**3.43**	**0.71**	**1.36**	**1.98**	**1.98**	**2.54**	**3.03**
	Q max.	kW	39	78	115	115	148	178	40	78	114	114	148	177
	V̇ secondary	**m³/h**	**1.14**	**2.27**	**3.31**	**3.31**	**4.26**	**5.11**	**1.16**	**2.26**	**3.30**	**3.30**	**4.26**	**5.10**
45/20 °C	T return primary	°C	24	23	23	23	23	23	23	23	22	22	22	22
	V̇ primary	**m³/h**	**0.72**	**1.4**	**2.02**	**2.02**	**2.59**	**3.1**	**0.63**	**1.22**	**1.78**	**1.78**	**2.29**	**2.73**
	Q max.	kW	33	66	96	96	123	148	33	65	96	96	124	148
	V̇ secondary	**m³/h**	**1.16**	**2.29**	**3.32**	**3.32**	**4.28**	**5.13**	**1.15**	**2.27**	**3.32**	**3.32**	**4.29**	**5.13**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua F

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
1	5820	0.17	1.00	0.17	10.01	0.60	35	0.24	14.3	0.86	50	(6-10)	0.13	0.16	(200)	23	15	8
2	11640	0.33	0.680	0.23	13.61	0.82	47	0.24	14.3	0.86	50	(6-10)	0.17	0.22	(200)	31	21	10
3	17460	0.50	0.544	0.27	16.33	0.98	57	0.43	25.8	1.55	90	(6-16)	0.20	0.27	(300)	37	25	12
4	23280	0.67	0.466	0.31	18.66	1.12	65	0.43	25.8	1.55	90	(6-16)	0.23	0.30	(300)	42	28	14
5	29100	0.83	0.415	0.35	20.77	1.25	72	0.43	25.8	1.55	90	(6-16)	0.26	0.34	(500)	47	31	16
6	34920	1.00	0.377	0.38	22.64	1.36	79	0.43	25.8	1.55	90	(6-16)	0.28	0.37	(500)	51	34	17
7	40740	1.17	0.349	0.41	24.45	1.47	85	0.43	25.8	1.55	90	(6-16)	0.31	0.40	(500)	55	37	18
8	46560	1.33	0.349	0.47	27.94	1.68	97	0.55	33.0	1.98	115	(6-20)	0.35	0.45	(500)	63	42	21
9	52380	1.50	0.308	0.46	27.74	1.66	97	0.55	33.0	1.98	115	(6-20)	0.35	0.45	(500)	63	42	21
10	58200	1.67	0.292	0.49	29.23	1.75	102	0.55	33.0	1.98	115	(6-20)	0.37	0.47	(500)	66	44	22
11	64020	1.83	0.279	0.51	30.72	1.84	107	0.55	33.0	1.98	115	(6-20)	0.38	0.50	(500)	70	46	23
12	69840	2.00	0.268	0.54	32.19	1.93	112	0.55	33.0	1.98	115	(6-20)	0.40	0.52	(500)	73	49	24
13	75660	2.17	0.258	0.56	33.57	2.01	117	0.55	33.0	1.98	115	(6-20)	0.42	0.55	(500)	76	51	25
14	81480	2.34	0.249	0.58	34.89	2.09	122	0.84	50.2	3.01	175	(6-30)	0.44	0.57	(500)	79	53	26
15	87300	2.50	0.242	0.61	36.33	2.18	127	0.84	50.2	3.01	175	(6-30)	0.45	0.59	(800)	82	55	27
16	93120	2.67	0.235	0.63	37.63	2.26	131	0.84	50.2	3.01	175	(6-30)	0.47	0.61	(800)	85	57	28
17	98940	2.84	0.228	0.65	38.79	2.33	135	0.84	50.2	3.01	175	(6-30)	0.49	0.63	(800)	88	59	29
18	104 760	3.00	0.223	0.67	40.17	2.41	140	0.84	50.2	3.01	175	(6-30)	0.50	0.65	(800)	91	61	30
19	110 580	3.17	0.217	0.69	41.27	2.48	144	0.84	50.2	3.01	175	(6-30)	0.52	0.67	(800)	94	62	31
20	116 400	3.34	0.212	0.71	42.44	2.55	148	0.84	50.2	3.01	175	(6-30)	0.53	0.69	(800)	96	64	32
21	122 220	3.50	0.208	0.73	43.72	2.62	153	0.84	50.2	3.01	175	(6-30)	0.55	0.71	(800)	99	66	33
22	128 040	3.67	0.204	0.75	44.92	2.70	157	0.84	50.2	3.01	175	(6-30)	0.56	0.73	(800)	102	68	34
23	133 860	3.84	0.200	0.77	46.04	2.76	161	0.84	50.2	3.01	175	(6-30)	0.58	0.75	(800)	104	70	35
24	139 680	4.00	0.196	0.78	47.08	2.82	164	0.84	50.2	3.01	175	(6-30)	0.59	0.77	(800)	107	71	36
25	145 500	4.17	0.193	0.80	48.29	2.90	168	0.84	50.2	3.01	175	(6-30)	0.60	0.78	(800)	110	73	37
26	151 320	4.34	0.190	0.82	49.44	2.97	173	0.84	50.2	3.01	175	(6-30)	0.62	0.80	(800)	112	75	37
27	157 140	4.50	0.187	0.84	50.53	3.03	176	0.84	50.2	3.01	175	(6-30)	0.63	0.82	(800)	115	76	38
28	162 960	4.67	0.184	0.86	51.56	3.09	180	0.84	50.2	3.01	175	(6-30)	0.64	0.84	(800)	117	78	39
29	168 780	4.84	0.181	0.88	52.54	3.15	183	1.10	65.8	3.95	230	(6-40)	0.66	0.85	(800)	119	79	40
30	174 600	5.00	0.179	0.90	53.75	3.22	188	1.10	65.8	3.95	230	(6-40)	0.67	0.87	(1000)	122	81	41
31	180 420	5.17	0.176	0.91	54.61	3.28	191	1.10	65.8	3.95	230	(6-40)	0.68	0.89	(1000)	124	83	41
32	186 240	5.34	0.174	0.93	55.73	3.34	194	1.10	65.8	3.95	230	(6-40)	0.70	0.91	(1000)	126	84	42
33	192 060	5.50	0.172	0.95	56.81	3.41	198	1.10	65.8	3.95	230	(6-40)	0.71	0.92	(1000)	129	86	43
34	197 880	5.67	0.170	0.96	57.85	3.47	202	1.10	65.8	3.95	230	(6-40)	0.72	0.94	(1000)	131	87	44
35	203 700	5.84	0.168	0.98	58.85	3.53	205	1.10	65.8	3.95	230	(6-40)	0.74	0.96	(1000)	133	89	44
36	209 520	6.01	0.166	1.00	59.81	3.59	209	1.10	65.8	3.95	230	(6-40)	0.75	0.97	(1000)	136	90	45
37	215 340	6.17	0.164	1.01	60.73	3.64	212	1.10	65.8	3.95	230	(6-40)	0.76	0.99	(1000)	138	92	46
38	221 160	6.34	0.163	1.03	61.99	3.72	216	1.10	65.8	3.95	230	(6-40)	0.78	1.01	(1000)	141	94	47
39	226 980	6.51	0.161	1.05	62.84	3.77	219	1.10	65.8	3.95	230	(6-40)	0.79	1.02	(1000)	143	95	48
40	232 800	6.67	0.159	1.06	63.65	3.82	222	1.10	65.8	3.95	230	(6-40)	0.80	1.03	(1000)	144	96	48
41	238 620	6.84	0.158	1.08	64.84	3.89	226	1.10	65.8	3.95	230	(6-40)	0.81	1.05	(1000)	147	98	49
42	244 440	7.01	0.156	1.09	65.58	3.93	229	1.10	65.8	3.95	230	(6-40)	0.82	1.07	(1000)	149	99	50
43	250 260	7.17	0.155	1.11	66.71	4.00	233	1.10	65.8	3.95	230	(6-40)	0.83	1.08	(1000)	151	101	50
44	256 080	7.34	0.154	1.13	67.82	4.07	237	1.31	78.8	4.73	275	(6-50)	0.85	1.10	(1500)	154	103	51
45	261 900	7.51	0.152	1.14	68.46	4.11	239	1.31	78.8	4.73	275	(6-50)	0.86	1.11	(1500)	155	104	52
46	267 720	7.67	0.151	1.16	69.52	4.17	243	1.31	78.8	4.73	275	(6-50)	0.87	1.13	(1500)	158	105	53
47	273 540	7.84	0.150	1.18	70.56	4.23	246	1.31	78.8	4.73	275	(6-50)	0.88	1.15	(1500)	160	107	53
48	279 360	8.01	0.149	1.19	71.58	4.29	250	1.31	78.8	4.73	275	(6-50)	0.89	1.16	(1500)	162	108	54
49	285 180	8.17	0.148	1.21	72.58	4.35	253	1.31	78.8	4.73	275	(6-50)	0.91	1.18	(1500)	165	110	55
50	291 000	8.34	0.146	1.22	73.06	4.38	255	1.31	78.8	4.73	275	(6-50)	0.91	1.19	(1500)	166	110	55
51	296 820	8.51	0.145	1.23	74.01	4.44	258	1.31	78.8	4.73	275	(6-50)	0.93	1.20	(1500)	168	112	56
52	302 640	8.67	0.144	1.25	74.94	4.50	261	1.31	78.8	4.73	275	(6-50)	0.94	1.22	(1500)	170	113	57
53	308 460	8.84	0.143	1.26	75.86	4.55	265	1.31	78.8	4.73	275	(6-50)	0.95	1.23	(1500)	172	115	57
54	314 280	9.01	0.142	1.28	76.75	4.60	268	1.31	78.8	4.73	275	(6-50)	0.96	1.25	(1500)	174	116	58

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
55	320 100	9.17	0.141	1.29	77.62	4.66	271	1.31	78.8	4.73	275	(6-50)	0.97	1.26	(1500)	176	117	59
56	325 920	9.34	0.140	1.31	78.47	4.71	274	1.31	78.8	4.73	275	(6-50)	0.98	1.28	(1500)	178	119	59
57	331 740	9.51	0.140	1.33	79.87	4.79	279	1.31	78.8	4.73	275	(6-50)	1.00	1.30	(1500)	181	121	60
58	337 560	9.67	0.139	1.34	80.69	4.84	282	1.69	101.2	6.07	350	(6-60)	1.01	1.31	(1500)	183	122	61
59	343 380	9.84	0.138	1.36	81.49	4.89	284	1.69	101.2	6.07	350	(6-60)	1.02	1.32	(1500)	185	123	62
60	349 200	10.01	0.137	1.37	82.27	4.94	287	1.69	101.2	6.07	350	(6-60)	1.03	1.34	(1500)	187	124	62
61	355 020	10.18	0.136	1.38	83.03	4.98	290	1.69	101.2	6.07	350	(6-60)	1.04	1.35	(1500)	188	126	63
62	360 840	10.34	0.135	1.40	83.77	5.03	292	1.69	101.2	6.07	350	(6-60)	1.05	1.36	(1500)	190	127	63
63	366 660	10.51	0.135	1.42	85.12	5.11	297	1.69	101.2	6.07	350	(6-60)	1.06	1.38	(1500)	193	129	64
64	372 480	10.68	0.134	1.43	85.83	5.15	299	1.69	101.2	6.07	350	(6-60)	1.07	1.40	(1500)	195	130	65
65	378 300	10.84	0.133	1.44	86.52	5.19	302	1.69	101.2	6.07	350	(6-60)	1.08	1.41	(1500)	196	131	65
66	384120	11.01	0.132	1.45	87.19	5.23	304	1.69	101.2	6.07	350	(6-60)	1.09	1.42	(1500)	198	132	66
67	389 940	11.18	0.132	1.48	88.52	5.31	309	1.69	101.2	6.07	350	(6-60)	1.11	1.44	(1500)	201	134	67
68	395 760	11.34	0.131	1.49	89.16	5.35	311	1.69	101.2	6.07	350	(6-60)	1.11	1.45	(1500)	202	135	67
69	401 580	11.51	0.130	1.50	89.78	5.39	313	1.69	101.2	6.07	350	(6-60)	1.12	1.46	(1500)	204	136	68
70	407 400	11.68	0.130	1.52	91.08	5.46	318	1.69	101.2	6.07	350	(6-60)	1.14	1.48	(1500)	207	138	69
71	413 220	11.84	0.129	1.53	91.67	5.50	320	1.69	101.2	6.07	350	(6-60)	1.15	1.49	(1500)	208	139	69
72	419 040	12.01	0.128	1.54	92.24	5.53	322	1.69	101.2	6.07	350	(6-60)	1.15	1.50	(1500)	209	139	70
73	424 860	12.18	0.128	1.56	93.52	5.61	326	1.69	101.2	6.07	350	(6-60)	1.17	1.52	(1500)	212	141	71
74	430 680	12.34	0.127	1.57	94.06	5.64	328	1.69	101.2	6.07	350	(6-60)	1.18	1.53	(1500)	213	142	71
75	436 500	12.51	0.127	1.59	95.33	5.72	333	1.69	101.2	6.07	350	(6-60)	1.19	1.55	(1500)	216	144	72
76	442 320	12.68	0.126	1.60	95.84	5.75	334	1.69	101.2	6.07	350	(6-60)	1.20	1.56	(1500)	217	145	72
77	448 140	12.84	0.126	1.62	97.10	5.83	339	1.69	101.2	6.07	350	(6-60)	1.21	1.58	(1500)	220	147	73
78	453 960	13.01	0.125	1.63	97.58	5.86	340	1.69	101.2	6.07	350	(6-60)	1.22	1.59	(1500)	221	148	74
79	459 780	13.18	0.124	1.63	98.04	5.88	342	1.69	101.2	6.07	350	(6-60)	1.23	1.59	(1500)	222	148	74
80	465 600	13.34	0.124	1.65	99.29	5.96	346	1.69	101.2	6.07	350	(6-60)	1.24	1.61	(2000)	225	150	75
81	471 420	13.51	0.123	1.66	99.72	5.98	348	1.69	101.2	6.07	350	(6-60)	1.25	1.62	(2000)	226	151	75
82	477 240	13.68	0.123	1.68	100.95	6.06	352	1.69	101.2	6.07	350	(6-60)	1.26	1.64	(2000)	229	153	76
83	483 060	13.85	0.122	1.69	101.35	6.08	354	1.69	101.2	6.07	350	(6-60)	1.27	1.65	(2000)	230	153	77
84	488 880	14.01	0.122	1.71	102.57	6.15	358	2.17	130.0	7.80	450	(6-70)	1.28	1.67	(2000)	233	155	78
85	494 700	14.18	0.121	1.72	102.94	6.18	359	2.17	130.0	7.80	450	(6-70)	1.29	1.67	(2000)	233	156	78
86	500 520	14.35	0.121	1.74	104.15	6.25	363	2.17	130.0	7.80	450	(6-70)	1.30	1.69	(2000)	236	157	79
87	506 340	14.51	0.120	1.74	104.49	6.27	365	2.17	130.0	7.80	450	(6-70)	1.31	1.70	(2000)	237	158	79
88	512 160	14.68	0.120	1.76	105.69	6.34	369	2.17	130.0	7.80	450	(6-70)	1.32	1.72	(2000)	240	160	80
89	517 980	14.85	0.120	1.78	106.89	6.41	373	2.17	130.0	7.80	450	(6-70)	1.34	1.74	(2000)	242	162	81
90	523 800	15.01	0.119	1.79	107.19	6.43	374	2.17	130.0	7.80	450	(6-70)	1.34	1.74	(2000)	243	162	81
91	529 620	15.18	0.119	1.81	108.38	6.50	378	2.17	130.0	7.80	450	(6-70)	1.36	1.76	(2000)	246	164	82
92	535 440	15.35	0.118	1.81	108.65	6.52	379	2.17	130.0	7.80	450	(6-70)	1.36	1.77	(2000)	246	164	82
93	541 260	15.51	0.118	1.83	109.83	6.59	383	2.17	130.0	7.80	450	(6-70)	1.37	1.79	(2000)	249	166	83
94	547 080	15.68	0.117	1.83	110.07	6.60	384	2.17	130.0	7.80	450	(6-70)	1.38	1.79	(2000)	250	166	83
95	552 900	15.85	0.117	1.85	111.25	6.67	388	2.17	130.0	7.80	450	(6-70)	1.39	1.81	(2000)	252	168	84
96	558 720	16.01	0.117	1.87	112.42	6.74	392	2.17	130.0	7.80	450	(6-70)	1.41	1.83	(2000)	255	170	85
97	564 540	16.18	0.116	1.88	112.62	6.76	393	2.17	130.0	7.80	450	(6-70)	1.41	1.83	(2000)	255	170	85
98	570 360	16.35	0.116	1.90	113.78	6.83	397	2.17	130.0	7.80	450	(6-70)	1.42	1.85	(2000)	258	172	86
99	576 180	16.51	0.116	1.92	114.94	6.90	401	2.17	130.0	7.80	450	(6-70)	1.44	1.87	(2000)	261	174	87
100	582 000	16.68	0.115	1.92	115.10	6.91	402	2.17	130.0	7.80	450	(6-70)	1.44	1.87	(2000)	261	174	87


Performance data

TransTherm® aqua F

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 65/30 °C (35 K)	Required heating water buffer storage tank volume at 65/30 °C (35 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	V̇s at DHW 60 °C	V̇s at DHW 60 °C	V̇s at DHW 60 °C		V̇s at DHW 60 °C	V̇s at DHW 60 °C	V̇s at DHW 60 °C	Q at HT 65/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 65/30 °C (35 K)	Time: 30 min 65/30 °C (35 K)	Time: 60 min 65/30 °C (35 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
1	5820	0.17	1.00	0.17	10.01	0.60	35	0.15	9.2	0.55	32	(6-10)	0.14	0.19	(200)	23	15	8
2	11640	0.33	0.680	0.23	13.61	0.82	47	0.24	14.3	0.86	60	(6-16)	0.19	0.25	(200)	31	21	10
3	17460	0.50	0.544	0.27	16.33	0.98	57	0.43	25.8	1.55	60	(6-16)	0.23	0.30	(300)	37	25	12
4	23280	0.67	0.466	0.31	18.66	1.12	65	0.38	23.0	1.38	80	(6-20)	0.27	0.35	(300)	42	28	14
5	29100	0.83	0.415	0.35	20.77	1.25	72	0.38	23.0	1.38	80	(6-20)	0.30	0.39	(500)	47	31	16
6	34920	1.00	0.377	0.38	22.64	1.36	79	0.38	23.0	1.38	80	(6-20)	0.32	0.42	(500)	51	34	17
7	40740	1.17	0.349	0.41	24.45	1.47	85	0.60	36.2	2.17	126	(6-30)	0.35	0.45	(500)	55	37	18
8	46560	1.33	0.349	0.47	27.94	1.68	97	0.60	36.2	2.17	126	(6-30)	0.40	0.52	(500)	63	42	21
9	52380	1.50	0.308	0.46	27.74	1.66	97	0.60	36.2	2.17	126	(6-30)	0.40	0.52	(500)	63	42	21
10	58200	1.67	0.292	0.49	29.23	1.75	102	0.60	36.2	2.17	126	(6-30)	0.42	0.54	(500)	66	44	22
11	64020	1.83	0.279	0.51	30.72	1.84	107	0.60	36.2	2.17	126	(6-30)	0.44	0.57	(500)	70	46	23
12	69840	2.00	0.268	0.54	32.19	1.93	112	0.60	36.2	2.17	126	(6-30)	0.46	0.60	(500)	73	49	24
13	75660	2.17	0.258	0.56	33.57	2.01	117	0.60	36.2	2.17	126	(6-30)	0.48	0.62	(500)	76	51	25
14	81480	2.34	0.249	0.58	34.89	2.09	122	0.60	36.2	2.17	126	(6-30)	0.50	0.65	(500)	79	53	26
15	87300	2.50	0.242	0.61	36.33	2.18	127	0.60	36.2	2.17	126	(6-30)	0.52	0.67	(800)	82	55	27
16	93120	2.67	0.235	0.63	37.63	2.26	131	0.83	49.7	2.98	173	(6-40)	0.54	0.70	(800)	85	57	28
17	98940	2.84	0.228	0.65	38.79	2.33	135	0.83	49.7	2.98	173	(6-40)	0.55	0.72	(800)	88	59	29
18	104 760	3.00	0.223	0.67	40.17	2.41	140	0.83	49.7	2.98	173	(6-40)	0.57	0.75	(800)	91	61	30
19	110 580	3.17	0.217	0.69	41.27	2.48	144	0.83	49.7	2.98	173	(6-40)	0.59	0.77	(800)	94	62	31
20	116 400	3.34	0.212	0.71	42.44	2.55	148	0.83	49.7	2.98	173	(6-40)	0.61	0.79	(800)	96	64	32
21	122 220	3.50	0.208	0.73	43.72	2.62	153	0.83	49.7	2.98	173	(6-40)	0.62	0.81	(800)	99	66	33
22	128 040	3.67	0.204	0.75	44.92	2.70	157	0.83	49.7	2.98	173	(6-40)	0.64	0.83	(800)	102	68	34
23	133 860	3.84	0.200	0.77	46.04	2.76	161	0.83	49.7	2.98	173	(6-40)	0.66	0.86	(800)	104	70	35
24	139 680	4.00	0.196	0.78	47.08	2.82	164	0.83	49.7	2.98	173	(6-40)	0.67	0.87	(800)	107	71	36
25	145 500	4.17	0.193	0.80	48.29	2.90	168	0.83	49.7	2.98	173	(6-40)	0.69	0.90	(800)	110	73	37
26	151 320	4.34	0.190	0.82	49.44	2.97	173	0.83	49.7	2.98	173	(6-40)	0.71	0.92	(800)	112	75	37
27	157 140	4.50	0.187	0.84	50.53	3.03	176	0.83	49.7	2.98	173	(6-40)	0.72	0.94	(800)	115	76	38
28	162 960	4.67	0.184	0.86	51.56	3.09	180	1.03	61.7	3.70	215	(6-50)	0.74	0.96	(800)	117	78	39
29	168 780	4.84	0.181	0.88	52.54	3.15	183	1.03	61.7	3.70	215	(6-50)	0.75	0.98	(800)	119	79	40
30	174 600	5.00	0.179	0.90	53.75	3.22	188	1.03	61.7	3.70	215	(6-50)	0.77	1.00	(1000)	122	81	41
31	180 420	5.17	0.176	0.91	54.61	3.28	191	1.03	61.7	3.70	215	(6-50)	0.78	1.01	(1000)	124	83	41
32	186 240	5.34	0.174	0.93	55.73	3.34	194	1.03	61.7	3.70	215	(6-50)	0.80	1.04	(1000)	126	84	42
33	192 060	5.50	0.172	0.95	56.81	3.41	198	1.03	61.7	3.70	215	(6-50)	0.81	1.06	(1000)	129	86	43
34	197 880	5.67	0.170	0.96	57.85	3.47	202	1.03	61.7	3.70	215	(6-50)	0.83	1.07	(1000)	131	87	44
35	203 700	5.84	0.168	0.98	58.85	3.53	205	1.03	61.7	3.70	215	(6-50)	0.84	1.09	(1000)	133	89	44
36	209 520	6.01	0.166	1.00	59.81	3.59	209	1.03	67.7	3.70	215	(6-50)	0.85	1.11	(1000)	136	90	45
37	215 340	6.17	0.164	1.01	60.73	3.64	212	1.03	61.7	3.70	215	(6-50)	0.87	1.13	(1000)	138	92	46
38	221 160	6.34	0.163	1.03	61.99	3.72	216	1.03	61.7	3.70	215	(6-50)	0.89	1.15	(1000)	141	94	47
39	226 980	6.51	0.161	1.05	62.84	3.77	219	1.06	63.7	3.82	220	(6-60)	0.90	1.17	(1000)	143	95	48
40	232 800	6.67	0.159	1.06	63.65	3.82	222	1.06	63.7	3.82	220	(6-60)	0.91	1.18	(1000)	144	96	48
41	238 620	6.84	0.158	1.08	64.84	3.89	226	1.35	81.0	4.86	280	(6-70)	0.93	1.20	(1000)	147	98	49
42	244 440	7.01	0.156	1.09	65.58	3.93	229	1.35	81.0	4.86	280	(6-70)	0.94	1.22	(1000)	149	99	50
43	250 260	7.17	0.155	1.11	66.71	4.00	233	1.35	81.0	4.86	280	(6-70)	0.95	1.24	(1000)	151	101	50
44	256 080	7.34	0.154	1.13	67.82	4.07	237	1.35	81.0	4.86	280	(6-70)	0.97	1.26	(1500)	154	103	51
45	261 900	7.51	0.152	1.14	68.46	4.11	239	1.35	81.0	4.86	280	(6-70)	0.98	1.27	(1500)	155	104	52
46	267 720	7.67	0.151	1.16	69.52	4.17	243	1.35	81.0	4.86	280	(6-70)	0.99	1.29	(1500)	158	105	53
47	273 540	7.84	0.150	1.18	70.56	4.23	246	1.35	81.0	4.86	280	(6-70)	1.01	1.31	(1500)	160	107	53
48	279 360	8.01	0.149	1.19	71.58	4.29	250	1.35	81.0	4.86	280	(6-70)	1.02	1.33	(1500)	162	108	54
49	285 180	8.17	0.148	1.21	72.58	4.35	253	1.35	81.0	4.86	280	(6-70)	1.04	1.35	(1500)	165	110	55
50	291 000	8.34	0.146	1.22	73.06	4.38	255	1.35	81.0	4.86	280	(6-70)	1.04	1.36	(1500)	166	110	55
51	296 820	8.51	0.145	1.23	74.01	4.44	258	1.35	81.0	4.86	280	(6-70)	1.06	1.37	(1500)	168	112	56
52	302 640	8.67	0.144	1.25	74.94	4.50	261	1.35	81.0	4.86	280	(6-70)	1.07	1.39	(1500)	170	113	57
53	308 460	8.84	0.143	1.26	75.86	4.55	265	1.35	81.0	4.86	280	(6-70)	1.08	1.41	(1500)	172	115	57
54	314 280	9.01	0.142	1.28	76.75	4.60	268	1.35	81.0	4.86	280	(6-70)	1.10	1.43	(1500)	174	116	58

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 65/30 °C (35 K)	Required heating water buffer storage tank volume at 65/30 °C (35 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 65/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 65/30 °C (35 K)	Time: 30 min 65/30 °C (35 K)	Time: 60 min 65/30 °C (35 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
55	320 100	9.17	0.141	1.29	77.62	4.66	271	1.35	81.0	4.86	280	(6-70)	1.11	1.44	(1500)	176	117	59
56	325 920	9.34	0.140	1.31	78.47	4.71	274	1.35	81.0	4.86	280	(6-70)	1.12	1.46	(1500)	178	119	59
57	331 740	9.51	0.140	1.33	79.87	4.79	279	1.35	81.0	4.86	280	(6-70)	1.14	1.48	(1500)	181	121	60
58	337 560	9.67	0.139	1.34	80.69	4.84	282	1.83	109.8	6.59	380	(6-80)	1.15	1.50	(1500)	183	122	61
59	343 380	9.84	0.138	1.36	81.49	4.89	284	1.83	109.8	6.59	380	(6-80)	1.16	1.51	(1500)	185	123	62
60	349 200	10.01	0.137	1.37	82.27	4.94	287	1.83	109.8	6.59	380	(6-80)	1.18	1.53	(1500)	187	124	62
61	355 020	10.18	0.136	1.38	83.03	4.98	290	1.83	109.8	6.59	380	(6-80)	1.19	1.54	(1500)	188	126	63
62	360 840	10.34	0.135	1.40	83.77	5.03	292	1.83	109.8	6.59	380	(6-80)	1.20	1.56	(1500)	190	127	63
63	366 660	10.51	0.135	1.42	85.12	5.11	297	1.83	109.8	6.59	380	(6-80)	1.22	1.58	(1500)	193	129	64
64	372 480	10.68	0.134	1.43	85.83	5.15	299	1.83	109.8	6.59	380	(6-80)	1.23	1.59	(1500)	195	130	65
65	378 300	10.84	0.133	1.44	86.52	5.19	302	1.83	109.8	6.59	380	(6-80)	1.24	1.61	(1500)	196	131	65
66	384120	11.01	0.132	1.45	87.19	5.23	304	1.83	109.8	6.59	380	(6-80)	1.25	1.62	(1500)	198	132	66
67	389 940	11.18	0.132	1.48	88.52	5.31	309	1.83	109.8	6.59	380	(6-80)	1.26	1.64	(1500)	201	134	67
68	395 760	11.34	0.131	1.49	89.16	5.35	311	1.83	109.8	6.59	380	(6-80)	1.27	1.66	(1500)	202	135	67
69	401 580	11.51	0.130	1.50	89.78	5.39	313	1.83	109.8	6.59	380	(6-80)	1.28	1.67	(1500)	204	136	68
70	407 400	11.68	0.130	1.52	91.08	5.46	318	1.83	109.8	6.59	380	(6-80)	1.30	1.69	(1500)	207	138	69
71	413 220	11.84	0.129	1.53	91.67	5.50	320	1.83	109.8	6.59	380	(6-80)	1.31	1.70	(1500)	208	139	69
72	419 040	12.01	0.128	1.54	92.24	5.53	322	1.83	109.8	6.59	380	(6-80)	1.32	1.71	(1500)	209	139	70
73	424 860	12.18	0.128	1.56	93.52	5.61	326	1.83	109.8	6.59	380	(6-80)	1.34	1.74	(1500)	212	141	71
74	430 680	12.34	0.127	1.57	94.06	5.64	328	1.83	109.8	6.59	380	(6-80)	1.34	1.75	(1500)	213	142	71
75	436 500	12.51	0.127	1.59	95.33	5.72	333	1.83	109.8	6.59	380	(6-80)	1.36	1.77	(1500)	216	144	72
76	442 320	12.68	0.126	1.60	95.84	5.75	334	1.83	109.8	6.59	380	(6-80)	1.37	1.78	(1500)	217	145	72
77	448 140	12.84	0.126	1.62	97.10	5.83	339	1.83	109.8	6.59	380	(6-80)	1.39	1.80	(1500)	220	147	73
78	453 960	13.01	0.125	1.63	97.58	5.86	340	1.83	109.8	6.59	380	(6-80)	1.39	1.81	(1500)	221	148	74
79	459 780	13.18	0.124	1.63	98.04	5.88	342	1.83	109.8	6.59	380	(6-80)	1.40	1.82	(1500)	222	148	74
80	465 600	13.34	0.124	1.65	99.29	5.96	346	1.83	109.8	6.59	380	(6-80)	1.42	1.84	(2000)	225	150	75
81	471 420	13.51	0.123	1.66	99.72	5.98	348	1.83	109.8	6.59	380	(6-80)	1.42	1.85	(2000)	226	151	75
82	477 240	13.68	0.123	1.68	100.95	6.06	352	1.83	109.8	6.59	380	(6-80)	1.44	1.88	(2000)	229	153	76
83	483 060	13.85	0.122	1.69	101.35	6.08	354	1.83	109.8	6.59	380	(6-80)	1.45	1.88	(2000)	230	153	77
84	488 880	14.01	0.122	1.71	102.57	6.15	358	1.83	109.8	6.59	380	(6-80)	1.47	1.91	(2000)	233	155	78
85	494 700	14.18	0.121	1.72	102.94	6.18	359	1.83	109.8	6.59	380	(6-80)	1.47	1.91	(2000)	233	156	78
86	500 520	14.35	0.121	1.74	104.15	6.25	363	1.83	109.8	6.59	380	(6-80)	1.49	1.93	(2000)	236	157	79
87	506 340	14.51	0.120	1.74	104.49	6.27	365	1.83	109.8	6.59	380	(6-80)	1.49	1.94	(2000)	237	158	79
88	512 160	14.68	0.120	1.76	105.69	6.34	369	1.83	109.8	6.59	380	(6-80)	1.51	1.96	(2000)	240	160	80
89	517 980	14.85	0.120	1.78	106.89	6.41	373	1.83	109.8	6.59	380	(6-80)	1.53	1.99	(2000)	242	162	81
90	523 800	15.01	0.119	1.79	107.19	6.43	374	1.83	109.8	6.59	380	(6-80)	1.53	1.99	(2000)	243	162	81
91	529 620	15.18	0.119	1.81	108.38	6.50	378	1.83	109.8	6.59	380	(6-80)	1.55	2.01	(2000)	246	164	82
92	535 440	15.35	0.118	1.81	108.65	6.52	379	1.83	109.8	6.59	380	(6-80)	1.55	2.02	(2000)	246	164	82
93	541 260	15.51	0.118	1.83	109.83	6.59	383	1.83	109.8	6.59	380	(6-80)	1.57	2.04	(2000)	249	166	83
94	547 080	15.68	0.117	1.83	110.07	6.60	384	1.83	109.8	6.59	380	(6-80)	1.57	2.04	(2000)	250	166	83
95	552 900	15.85	0.117	1.85	111.25	6.67	388	2.51	150.3	9.02	520	(6-90)	1.59	2.07	(2000)	252	168	84
96	558 720	16.01	0.117	1.87	112.42	6.74	392	2.51	150.3	9.02	520	(6-90)	1.61	2.09	(2000)	255	170	85
97	564 540	16.18	0.116	1.88	112.62	6.76	393	2.51	150.3	9.02	520	(6-90)	1.61	2.09	(2000)	255	170	85
98	570 360	16.35	0.116	1.90	113.78	6.83	397	2.51	150.3	9.02	520	(6-90)	1.63	2.11	(2000)	258	172	86
99	576 180	16.51	0.116	1.92	114.94	6.90	401	2.51	150.3	9.02	520	(6-90)	1.64	2.13	(2000)	261	174	87
100	582 000	16.68	0.115	1.92	115.10	6.91	402	2.51	150.3	9.02	520	(6-90)	1.64	2.14	(2000)	261	174	87


Pressure drop (ΔP / Q max) – domestic water side (secondary)




Circulating pumps characteristic curves

for circulation set ¾″


Δp-v (variable)



Constant speed




for circulation set 1″ and 1¼″





Fresh water module TransTherm® aqua F (6-10 to 6-20)

(Dimensions in mm)

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.







1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(6-10) (6-16) (6-20)
6	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
7 *	Hot water	DN 25, Rp 1″ (IT)
8	Cold water	DN 25, Gp 1″ (IT)
9	Flow heating water	DN 25, Rp 1″ (IT)
10	Return heating water	DN 20, Gp 1″ (IT)

[1] Optional, connection and installation on site


Gp = straight internal thread


TransTherm® aqua F	Weight in kg
(6-10)	52
(6-16)	54
(6-20)	56


Fresh water module TransTherm® aqua F (6-10 to 6-20)

(Dimensions in mm)


*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.







Version incl. circulation set



	A	B	C
(6-10)	112	163	1056
(6-16)	112	163	1045
(6-20)	133	246	1143

1 Safety valve Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Primary three-way valve
5 Primary circulating pump

Gp = straight internal thread


		(6-10) (6-16) (6-20)
6	Circulation [1]	DN 25, Rp 1″ (20, Rp ¾″) (IT)
7 *	Hot water	DN 25, Rp 1″ (IT)
8	Cold water	DN 25, Gp 1″ (IT)
9	Flow heating water	DN 25, Rp 1″ (IT)
10	Return heating water	DN 20, Gp 1″ (IT)


[1] Optional, connection and installation on site


Fresh water module TransTherm® aqua F (6-30 to 6-50)

(Dimensions in mm)

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.







1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger

		(6-30) (6-40) (6-50)
6	Circulation [1]	DN 32, Rp 1¼″ (25 Rp 1″) (20 Rp ¾″) (IT)
7 *	Hot water	DN 32, Rp 1¼″ (IT)
8	Cold water	DN 32, Rp 1¼″ (IT)
9	Flow heating water	DN 32, Rp 1¼″ (IT)
10	Return heating water	DN 32, Rp 1¼″ (IT)


[1] Optional, connection and installation on site

TransTherm® aqua F	Weight in kg
(6-30)	62
(6-40)	64
(6-50)	66


Fresh water module TransTherm® aqua F (6-30 to 6-50)


(Dimensions in mm)

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.




	A
(6-30), (6-50)	1074
(6-40)	1077





Version incl. circulation set




1 Safety valve
Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Primary three-way valve
5 Primary circulating pump

		(6-30) (6-40) (6-50)
6	Circulation [1]	DN 32, Rp 1¼″ (25 Rp 1″) (20 Rp ¾″) (IT)
7 *	Hot water	DN 32, Rp 1¼″ (IT)
8	Cold water	DN 32, Rp 1¼″ (IT)
9	Flow heating water	DN 32, Rp 1¼″ (IT)
10	Return heating water	DN 32, Rp 1¼″ (IT)

[1] Optional, connection and installation on site

Water heating
TransTherm® aqua F

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.



TTE-FW	Basic module district heating/fresh water
TW	Flow temperature monitor (if required)
VFP	Flow sensor primary
VFW	Flow sensor DHW
RLF	Return sensor primary
RLF2	Return sensor domestic cold water
SF	Calorifier sensor
SF1	Calorifier sensor 1
RLFZ	Circulation sensor
SLP1	Calorifier charging pump primary
FVT	Flow rate sensor
YFW	Three-way valve with actuator
ZKP	Recirculation pump
Y11	Return switching with actuator

Option

BM	TopTronic® E control module
SF2	Calorifier sensor 2

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval TransTherm® aqua

Calorifier continuous flow system
TransTherm® aqua F (6-60)-(6-90)



Table of contents

- Description 5
- Part numbers 6
- Technical data 10
- Dimensions 19
- Example 23

Calorifier continuous flow system

Consisting of:
- fresh water module TransTherm® aqua F
- buffer storage tank (option)

Fresh water module TransTherm® aqua F

- Fully installed station with plate heat exchanger for the provision of domestic hot water using the continuous flow principle
- Mounted on stand frame.
  Stand frame consisting of:
  - frame with corrosion protection coating RAL 9005
  - height-adjustable and vibration-damped feet
- The primary side (heating side) contains the three-way valve, high-efficiency pump, ventilation, filling/drain valve and balancing valve. These components ensure a constant flow temperature at the plate heat exchanger. Pipes made from steel
- The secondary side (DHW side) contains the safety valve (10 bar), non-return valve and a filling/drain valve. A flow sensor ensures the correct hot water temperature. Pipes made from stainless steel
- Stainless steel plate heat exchanger 1.4404, copper-soldered
- Flow rate sensor
- T-piece with dummy plug for on-site connection of the circulation group. Connect the pump to the controller on site.
- TopTronic® E control with integrated thermal disinfection of the DHW storage tank (anti-legionella circuit)


Thermal insulation consisting of:
- thermal insulation of the heat exchanger with 30-mm EPP mouldings
- thermal insulation of the pipes with EPP mouldings. Insulation thickness of 50 % according to EnEV
- deep black, similar to RAL 9005
- suitable for damp rooms
- CFC-free
- normal flammability according to DIN 4102-1 and EN 13501-1 (fuel class: B2)
- no bleaching and disintegration of the insulation under the influence of UV light

Delivery
- The buffer storage tank required is not included in the scope of delivery

On site
- Installation of a circulation unit;
  the necessary connection is provided.
- Electrical connection of the controller

TopTronic® E controller

TopTronic® E basic module district heating/ fresh water
- Control unit for controlling district heating transfer stations in non-communicative networks and the corresponding consumers with integrated control functions for
  - primary valve control
  - cascade management
  - 1 heating/cooling circuit with mixer
  - 1 heating/cooling circuit without mixer
  - 1 hot water charging circuit
  - various additional functions



Range
Fresh water module

TransTherm® aqua F type	Output kW
(6-60)	350
(6-70)	450
(6-80)	580
(6-90)	700

- Various functions for hot water:
  - selection of different basic programs (week programs, economy mode, holiday until, etc.)
  - various operating modes (e.g. accumulator priority or parallel mode)
  - buffer storage circuit on the primary or secondary side
  - adjustable loading criteria (e.g.: adjustable loading times, undershooting the minimum nominal value, etc.)
  - adjustable switch-off criteria (e.g. achieving the setpoint valve, achieving the lower sensor setpoint value, etc.)
  - adjustable loading block (if the loading flow temperature is too low, the setpoint temperature is not reached, differential temperature-dependent solar circuit control)
- Definable switching times for recirculation pump control
- Outdoor sensor
- Immersion sensor (calorifier sensor)
- Contact sensor (flow temperature sensor)
- Complete plug set for DH module
- speed-controlled pumps

No further module expansions or controller modules can be installed in the control panel!

Option

TopTronic® E control module
- Simple, intuitive operating concept
- Display of the most important operating states
- Configurable start screen
- Operating mode selection
- Configurable day and week programs
- Operation of all connected Hoval CAN bus modules
- Commissioning wizard
- Service and maintenance function
- Fault message management
- Analysis function
- Weather display (with HovalConnect option)
- Adaptation of the heating strategy based on the weather forecast (with HovalConnect option)

Notice
The TopTronic® E control module for operating the basic module district heating/fresh water must be ordered separately!


Further information about the TopTronic® E
see “Controls”

Delivery
- All armatures required for operation, such as strainers, flow balancing and shut-off valves, backflow preventer, air-bleeding and drain valve are fitted.

Caution
As a result of thermal disinfection of the domestic hot water for legionella protection, increased water temperatures (at least 65 ... 70 °C) occur. Depending on the water quality, this may result in increased calcification at the installed armatures and heat exchangers and also brings the risk of scalding at the tapping points. Corresponding protective measures must be implemented on site.

Hot water connection for application according to the SVGW (Swiss association for electricity, gas, district heating and water)
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.

Fresh water module



TransTherm® aqua F


Fully assembled station with plate heat exchanger for the provision of domestic hot water using the continuous flow principle and built-in Hoval TopTronic® E control
The required buffer storage tank is not supplied.

TransTherm® aqua F	Output kW	Part No.
(6-60)	350	8006 393
(6-70)	450	8006 394
(6-80)	580	8006 395
(6-90)	700	8006 396

Authorisation number

TransTherm® aqua F (6-60)-(6-90)
SVGW test number 2407-7331

Accessories

	Part No.
	
TopTronic® E control module black with 4.3″ colour touchscreen For operation of all controller modules connected to the bus system (basic, solar, buffer modules etc.) Connection to the Hoval bus system via RJ45 plug connection or via plug terminals (max. 0.75 mm²), flat design with flexible installation option Installation: - in control panel of the heat generator - in the Hoval wall casing - in the control panel front, black high-gloss cover, customer-specific configurable start screen, Display of current weather or weather forecast (only possible in combination with HovalConnect) Consisting of: - TopTronic® E control module black - Clamping device set control module - RJ45-RAST 5 CAN cable, L = 500	6043 844
	
Return changeover valve set Consisting of: - temperature sensor - changeover valve - drive (8 sec.) DN 20-40 - drive (30 sec.) DN 50-80 - seals - screw connections	

Nominal diameter	Output kW	k_{vs} m³/h	Part No.
DN 20	50-90	6.3	7010 832
DN 25	115-175	10	7010 836
DN 32	230-275	16	7011 009
DN 40	350	25	7011 025
DN 50	450	40	7016 331
DN 65	580	63	7016 332
DN 80	700	100	7016 333

Notice
When using a circulation set (also on-site recirculation pump), it is imperative to install a return switching valve set.



Circulation set
for TransTherm® aqua L, L-FW, F
Piping of parts in contact with domestic water in stainless steel and gunmetal
Consisting of:
- temperature sensor PT1000
- recirculation pump Wilo Yonos PARA
- recirculation pump Wilo Para MAXO
- regulating valve
- non-return valve

Connection	Flow rate m³/h	Recirculation pump	Part No.
DN 20 ¾″ Rp	1.9	Z15/7.0 RKC	8005 279
DN 25 1″ Rp	3.4	Z25/180/08/F02	8005 280
DN 32 1¼″ Rp	5.8	Z25/180/08/F02	8005 281

	Part No.
 **Test valve DN 8 G ¼″** for TransTherm® aqua L, L-FW, F, FS Test valve suitable for flame treatment for hygienic-microbiologic tests.	2049 861
  **Sludge separator DM with magnet** made of technopolymer (PO) or brass with insulation (MS)	

Type	Connection inches	Flow rate at 1.2 m/s flow speed m^3/h	k_v value m^3/h	
DM PO	Rp 1″	1.3	10.5	2054 376
DM PO	Rp 1¼″	2.1	10.5	2085 523
DM MS	Rp 1½″	5.4	63.2	2085 527
DM MS	Rp 2″	8.2	70.0	2085 528

Additional sludge separators
see “Various system components”

 **Insulation for sludge separator DM PO 1″** 10 mm insulating caps made of PE-X foam Thermal conductivity 0.035 W/mK Fire resistance (DIN 4102): class B2	2085 524
 **Insulation for sludge separator DM PO 1¼″** 10 mm insulating caps made of PE-X foam Thermal conductivity 0.035 W/mK Fire resistance (DIN 4102): class B2	2086 031

		Part No.
	**Temperature monitor 0 ... 120 °C** for TransTherm® aqua L, L-FW, F, FS	2048 299
	**Safety temperature monitor 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2048 300
	**Safety temperature limiter 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2049 619
	**Immersion sleeve G ½″ stainless steel for thermostat** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 8 mm, inner Ø: 6.5 mm	2048 285
	**Immersion sleeve G ½″ stainless steel for 2 thermostats** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 15 mm, inner Ø: 13.5 mm	2048 288

Services

Services and associated scope of services
see separate catalogue “Hoval Services”

Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.

Performance data

TransTherm® aqua F (6-60 to 6-90)

Domestic water secondary	TransTherm® aqua F		Flow temperature heating water 52 °C (60)	52 °C (70)	52 °C (80)	52 °C (90)	55 °C (60)	55 °C (70)	55 °C (80)	55 °C (90)	60 °C (60)	60 °C (70)	60 °C (80)	60 °C (90)
60/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
55/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	28	28	28	27
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**7.27**	**10.06**	**12.62**	**15.81**
	Q max.	kW	-	-	-	-	-	-	-	-	270	370	470	600
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**4.68**	**6.42**	**8.15**	**10.4**
55/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	29	29	29
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**7.30**	**9.04**	**11.82**	**14.63**
	Q max.	kW	-	-	-	-	-	-	-	-	255	320	420	530
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**4.91**	**6.17**	**8.09**	**10.21**
55/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**5.20**	**7.23**	**9.25**	**13.01**
	Q max.	kW	-	-	-	-	-	-	-	-	180	250	320	450
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**3.90**	**5.42**	**6.94**	**9.75**
55/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**3.18**	**4.34**	**5.78**	**7.51**
	Q max.	kW	-	-	-	-	-	-	-	-	110	150	200	260
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**2.73**	**3.72**	**4.95**	**6.44**
50/5 °C	T return primary	°C	-	-	-	-	25	25	25	24	22	22	21	21
	V̇ primary	**m³/h**	-	-	-	-	**7.32**	**8.93**	**11.59**	**14.69**	**7.17**	**9.14**	**11.65**	**13.93**
	Q max.	kW	-	-	-	-	250	310	405	520	315	405	520	630
	V̇ secondary	**m³/h**	-	-	-	-	**4.82**	**5.97**	**7.80**	**10.02**	**6.07**	**7.80**	**10.02**	**12.14**
50/10 °C	T return primary	°C	-	-	-	-	27	27	27	26	24	24	24	23
	V̇ primary	**m³/h**	-	-	-	-	**7.17**	**8.95**	**11.64**	**14.45**	**6.78**	**8.62**	**11.52**	**13.16**
	Q max.	kW	-	-	-	-	230	290	380	480	280	360	485	560
	V̇ secondary	**m³/h**	-	-	-	-	**4.99**	**6.29**	**8.24**	**10.4**	**6.07**	**7.80**	**10.51**	**12.14**
50/15 °C	T return primary	°C	-	-	-	-	29	29	29	28	26	26	26	26
	V̇ primary	**m³/h**	-	-	-	-	**7.25**	**9.24**	**11.63**	**14.5**	**6.31**	**8.10**	**10.97**	**12.35**
	Q max.	kW	-	-	-	-	215	275	350	445	245	315	430	490
	V̇ secondary	**m³/h**	-	-	-	-	**5.33**	**6.81**	**8.67**	**11.02**	**6.07**	**7.80**	**10.65**	**12.14**
50/20 °C	T return primary	°C	-	-	-	-	30	30	30	30	30	29	29	29
	V̇ primary	**m³/h**	-	-	-	-	**5.03**	**6.59**	**9.02**	**11.96**	**6.00**	**7.6**	**10.35**	**11.6**
	Q max.	kW	-	-	-	-	145	190	260	345	210	270	370	420
	V̇ secondary	**m³/h**	-	-	-	-	**4.20**	**5.49**	**7.51**	**9.97**	**6.07**	**7.80**	**10.69**	**12.14**
45/5 °C	T return primary	°C	21	21	21	20	20	19	19	19	18	18	18	17
	V̇ primary	**m³/h**	**7.20**	**8.95**	**11.53**	**14.54**	**6.90**	**8.77**	**11.62**	**13.4**	**5.77**	**7.36**	**10.00**	**11.26**
	Q max.	kW	255	320	415	530	280	360	480	560	280	360	490	560
	V̇ secondary	**m³/h**	**5.53**	**6.94**	**9.00**	**11.50**	**6.07**	**7.80**	**10.4**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
45/10 °C	T return primary	°C	23	23	23	23	22	22	22	21	20	20	20	19
	V̇ primary	**m³/h**	**7.12**	**9.21**	**11.51**	**14.45**	**6.44**	**8.23**	**11.13**	**12.57**	**5.27**	**6.77**	**9.24**	**10.28**
	Q max.	kW	235	305	385	490	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**5.82**	**7.56**	**9.54**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
45/15 °C	T return primary	°C	25	25	25	25	25	24	24	24	23	22	22	22
	V̇ primary	**m³/h**	**6.10**	**8.03**	**10.67**	**13.49**	**6.01**	**7.63**	**10.38**	**11.63**	**4.88**	**6.23**	**8.51**	**9.53**
	Q max.	kW	190	250	335	420	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**5.49**	**7.23**	**9.68**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/20 °C	T return primary	°C	25	25	25	25	27	27	27	27	25	25	25	25
	V̇ primary	**m³/h**	**2.73**	**3.53**	**4.66**	**6.42**	**5.46**	**6.97**	**9.57**	**10.65**	**4.37**	**5.59**	**7.68**	**8.57**
	Q max.	kW	85	110	145	200	175	225	310	350	175	225	310	350
	V̇ secondary	**m³/h**	**2.95**	**3.82**	**5.03**	**6.94**	**6.07**	**7.80**	**10.75**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua F (6-60 to 6-90)

Domestic water secondary	TransTherm® aqua F		Flow temperature heating water 65 °C (60)	65 °C (70)	65 °C (80)	65 °C (90)	70 °C (60)	70 °C (70)	70 °C (80)	70 °C (90)
60/5 °C	T return primary	°C	30	30	30	29	26	26	25	25
	V̇ primary	**m³/h**	**7.15**	**9.17**	**11.72**	**14.69**	**7.42**	**9.40**	**11.66**	**14.64**
	Q max.	kW	290	370	480	610	375	480	600	760
	V̇ secondary	**m³/h**	**4.57**	**5.83**	**7.57**	**9.62**	**5.91**	**7.57**	**9.46**	**11.98**
60/10 °C	T return primary	°C	30	30	30	30	28	28	28	27
	V̇ primary	**m³/h**	**5.45**	**6.94**	**9.41**	**12.88**	**7.23**	**9.29**	**11.92**	**14.15**
	Q max.	kW	220	280	380	520	350	450	580	700
	V̇ secondary	**m³/h**	**3.82**	**4.86**	**6.59**	**9.02**	**6.07**	**7.80**	**10.06**	**12.14**
60/15 °C	T return primary	°C	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**3.72**	**4.83**	**6.44**	**8.67**	**6.72**	**8.78**	**11.73**	**13.49**
	Q max.	kW	150	195	260	350	310	405	540	630
	V̇ secondary	**m³/h**	**2.89**	**3.76**	**5.01**	**6.74**	**5.97**	**7.80**	**10.4**	**12.14**
60/20 °C	T return primary	°C	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**2.11**	**2.85**	**3.72**	**4.95**	**4.34**	**5.64**	**7.37**	**9.97**
	Q max.	kW	85	115	150	200	200	260	340	460
	V̇ secondary	**m³/h**	**1.84**	**2.49**	**3.25**	**4.34**	**4.34**	**5.64**	**7.37**	**9.97**
55/5 °C	T return primary	°C	24	24	23	23	22	21	21	21
	V̇ primary	**m³/h**	**7.42**	**9.24**	**11.64**	**14.38**	**6.30**	**8.03**	**10.99**	**12.26**
	Q max.	kW	350	440	560	700	350	450	620	700
	V̇ secondary	**m³/h**	**6.07**	**7.63**	**9.71**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**
55/10 °C	T return primary	°C	26	26	26	25	24	24	24	23
	V̇ primary	**m³/h**	**7.06**	**8.96**	**11.66**	**13.66**	**5.96**	**7.6**	**10.25**	**11.6**
	Q max.	kW	315	405	530	630	315	405	550	630
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.21**	**12.14**	**6.07**	**7.80**	**10.6**	**12.14**
55/15 °C	T return primary	°C	29	28	28	27	27	26	26	26
	V̇ primary	**m³/h**	**6.67**	**8.48**	**11.48**	**12.91**	**5.62**	**7.16**	**9.70**	**10.96**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
55/20 °C	T return primary	°C	30	30	30	30	29	29	29	28
	V̇ primary	**m³/h**	**5.95**	**7.80**	**10.4**	**12.14**	**5.13**	**6.64**	**9.01**	**10.16**
	Q max.	kW	240	315	420	490	245	315	430	490
	V̇ secondary	**m³/h**	**5.95**	**7.80**	**10.4**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
50/5 °C	T return primary	°C	20	20	19	19	18	18	17	17
	V̇ primary	**m³/h**	**6.06**	**7.72**	**10.43**	**11.77**	**5.30**	**6.74**	**9.05**	**10.27**
	Q max.	kW	315	405	550	630	315	405	550	630
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.6**	**12.14**	**6.07**	**7.80**	**10.6**	**12.14**
50/10 °C	T return primary	°C	22	22	22	21	21	20	20	19
	V̇ primary	**m³/h**	**5.69**	**7.28**	**9.81**	**11.08**	**4.90**	**6.24**	**8.46**	**9.57**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
50/15 °C	T return primary	°C	25	25	24	24	23	23	22	22
	V̇ primary	**m³/h**	**5.30**	**6.74**	**9.14**	**10.29**	**4.52**	**5.76**	**7.82**	**8.83**
	Q max.	kW	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
50/20 °C	T return primary	°C	27	26	27	26	26	26	25	25
	V̇ primary	**m³/h**	**4.84**	**6.00**	**8.38**	**9.43**	**4.12**	**5.26**	**7.16**	**8.07**
	Q max.	kW	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/5 °C	T return primary	°C	16	16	16	15	15	14	14	13
	V̇ primary	**m³/h**	**4.99**	**6.34**	**8.58**	**9.69**	**4.39**	**5.59**	**7.59**	**8.58**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
45/10 °C	T return primary	°C	19	18	18	18	17	17	17	16
	V̇ primary	**m³/h**	**4.57**	**5.85**	**7.92**	**8.94**	**4.02**	**5.13**	**6.98**	**7.90**
	Q max.	kW	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
45/15 °C	T return primary	°C	21	21	21	20	20	20	20	19
	V̇ primary	**m³/h**	**4.15**	**5.30**	**7.24**	**8.15**	**3.64**	**4.66**	**6.37**	**7.18**
	Q max.	kW	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/20 °C	T return primary	°C	24	24	24	24	23	23	23	23
	V̇ primary	**m³/h**	**3.71**	**4.75**	**6.51**	**7.31**	**3.24**	**4.15**	**5.71**	**6.42**
	Q max.	kW	175	225	310	350	175	225	310	350
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.75**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua F

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
1	5820	0.17	1.00	0.17	10.01	0.60	35	0.24	14.3	0.86	50	(6-10)	0.13	0.16	(200)	23	15	8
2	11640	0.33	0.680	0.23	13.61	0.82	47	0.24	14.3	0.86	50	(6-10)	0.17	0.22	(200)	31	21	10
3	17460	0.50	0.544	0.27	16.33	0.98	57	0.43	25.8	1.55	90	(6-16)	0.20	0.27	(300)	37	25	12
4	23280	0.67	0.466	0.31	18.66	1.12	65	0.43	25.8	1.55	90	(6-16)	0.23	0.30	(300)	42	28	14
5	29100	0.83	0.415	0.35	20.77	1.25	72	0.43	25.8	1.55	90	(6-16)	0.26	0.34	(500)	47	31	16
6	34920	1.00	0.377	0.38	22.64	1.36	79	0.43	25.8	1.55	90	(6-16)	0.28	0.37	(500)	51	34	17
7	40740	1.17	0.349	0.41	24.45	1.47	85	0.43	25.8	1.55	90	(6-16)	0.31	0.40	(500)	55	37	18
8	46560	1.33	0.349	0.47	27.94	1.68	97	0.55	33.0	1.98	115	(6-20)	0.35	0.45	(500)	63	42	21
9	52380	1.50	0.308	0.46	27.74	1.66	97	0.55	33.0	1.98	115	(6-20)	0.35	0.45	(500)	63	42	21
10	58200	1.67	0.292	0.49	29.23	1.75	102	0.55	33.0	1.98	115	(6-20)	0.37	0.47	(500)	66	44	22
11	64020	1.83	0.279	0.51	30.72	1.84	107	0.55	33.0	1.98	115	(6-20)	0.38	0.50	(500)	70	46	23
12	69840	2.00	0.268	0.54	32.19	1.93	112	0.55	33.0	1.98	115	(6-20)	0.40	0.52	(500)	73	49	24
13	75660	2.17	0.258	0.56	33.57	2.01	117	0.55	33.0	1.98	115	(6-20)	0.42	0.55	(500)	76	51	25
14	81480	2.34	0.249	0.58	34.89	2.09	122	0.84	50.2	3.01	175	(6-30)	0.44	0.57	(500)	79	53	26
15	87300	2.50	0.242	0.61	36.33	2.18	127	0.84	50.2	3.01	175	(6-30)	0.45	0.59	(800)	82	55	27
16	93120	2.67	0.235	0.63	37.63	2.26	131	0.84	50.2	3.01	175	(6-30)	0.47	0.61	(800)	85	57	28
17	98940	2.84	0.228	0.65	38.79	2.33	135	0.84	50.2	3.01	175	(6-30)	0.49	0.63	(800)	88	59	29
18	104 760	3.00	0.223	0.67	40.17	2.41	140	0.84	50.2	3.01	175	(6-30)	0.50	0.65	(800)	91	61	30
19	110 580	3.17	0.217	0.69	41.27	2.48	144	0.84	50.2	3.01	175	(6-30)	0.52	0.67	(800)	94	62	31
20	116 400	3.34	0.212	0.71	42.44	2.55	148	0.84	50.2	3.01	175	(6-30)	0.53	0.69	(800)	96	64	32
21	122 220	3.50	0.208	0.73	43.72	2.62	153	0.84	50.2	3.01	175	(6-30)	0.55	0.71	(800)	99	66	33
22	128 040	3.67	0.204	0.75	44.92	2.70	157	0.84	50.2	3.01	175	(6-30)	0.56	0.73	(800)	102	68	34
23	133 860	3.84	0.200	0.77	46.04	2.76	161	0.84	50.2	3.01	175	(6-30)	0.58	0.75	(800)	104	70	35
24	139 680	4.00	0.196	0.78	47.08	2.82	164	0.84	50.2	3.01	175	(6-30)	0.59	0.77	(800)	107	71	36
25	145 500	4.17	0.193	0.80	48.29	2.90	168	0.84	50.2	3.01	175	(6-30)	0.60	0.78	(800)	110	73	37
26	151 320	4.34	0.190	0.82	49.44	2.97	173	0.84	50.2	3.01	175	(6-30)	0.62	0.80	(800)	112	75	37
27	157 140	4.50	0.187	0.84	50.53	3.03	176	0.84	50.2	3.01	175	(6-30)	0.63	0.82	(800)	115	76	38
28	162 960	4.67	0.184	0.86	51.56	3.09	180	0.84	50.2	3.01	175	(6-30)	0.64	0.84	(800)	117	78	39
29	168 780	4.84	0.181	0.88	52.54	3.15	183	1.10	65.8	3.95	230	(6-40)	0.66	0.85	(800)	119	79	40
30	174 600	5.00	0.179	0.90	53.75	3.22	188	1.10	65.8	3.95	230	(6-40)	0.67	0.87	(1000)	122	81	41
31	180 420	5.17	0.176	0.91	54.61	3.28	191	1.10	65.8	3.95	230	(6-40)	0.68	0.89	(1000)	124	83	41
32	186 240	5.34	0.174	0.93	55.73	3.34	194	1.10	65.8	3.95	230	(6-40)	0.70	0.91	(1000)	126	84	42
33	192 060	5.50	0.172	0.95	56.81	3.41	198	1.10	65.8	3.95	230	(6-40)	0.71	0.92	(1000)	129	86	43
34	197 880	5.67	0.170	0.96	57.85	3.47	202	1.10	65.8	3.95	230	(6-40)	0.72	0.94	(1000)	131	87	44
35	203 700	5.84	0.168	0.98	58.85	3.53	205	1.10	65.8	3.95	230	(6-40)	0.74	0.96	(1000)	133	89	44
36	209 520	6.01	0.166	1.00	59.81	3.59	209	1.10	65.8	3.95	230	(6-40)	0.75	0.97	(1000)	136	90	45
37	215 340	6.17	0.164	1.01	60.73	3.64	212	1.10	65.8	3.95	230	(6-40)	0.76	0.99	(1000)	138	92	46
38	221 160	6.34	0.163	1.03	61.99	3.72	216	1.10	65.8	3.95	230	(6-40)	0.78	1.01	(1000)	141	94	47
39	226 980	6.51	0.161	1.05	62.84	3.77	219	1.10	65.8	3.95	230	(6-40)	0.79	1.02	(1000)	143	95	48
40	232 800	6.67	0.159	1.06	63.65	3.82	222	1.10	65.8	3.95	230	(6-40)	0.80	1.03	(1000)	144	96	48
41	238 620	6.84	0.158	1.08	64.84	3.89	226	1.10	65.8	3.95	230	(6-40)	0.81	1.05	(1000)	147	98	49
42	244 440	7.01	0.156	1.09	65.58	3.93	229	1.10	65.8	3.95	230	(6-40)	0.82	1.07	(1000)	149	99	50
43	250 260	7.17	0.155	1.11	66.71	4.00	233	1.10	65.8	3.95	230	(6-40)	0.83	1.08	(1000)	151	101	50
44	256 080	7.34	0.154	1.13	67.82	4.07	237	1.31	78.8	4.73	275	(6-50)	0.85	1.10	(1500)	154	103	51
45	261 900	7.51	0.152	1.14	68.46	4.11	239	1.31	78.8	4.73	275	(6-50)	0.86	1.11	(1500)	155	104	52
46	267 720	7.67	0.151	1.16	69.52	4.17	243	1.31	78.8	4.73	275	(6-50)	0.87	1.13	(1500)	158	105	53
47	273 540	7.84	0.150	1.18	70.56	4.23	246	1.31	78.8	4.73	275	(6-50)	0.88	1.15	(1500)	160	107	53
48	279 360	8.01	0.149	1.19	71.58	4.29	250	1.31	78.8	4.73	275	(6-50)	0.89	1.16	(1500)	162	108	54
49	285 180	8.17	0.148	1.21	72.58	4.35	253	1.31	78.8	4.73	275	(6-50)	0.91	1.18	(1500)	165	110	55
50	291 000	8.34	0.146	1.22	73.06	4.38	255	1.31	78.8	4.73	275	(6-50)	0.91	1.19	(1500)	166	110	55
51	296 820	8.51	0.145	1.23	74.01	4.44	258	1.31	78.8	4.73	275	(6-50)	0.93	1.20	(1500)	168	112	56
52	302 640	8.67	0.144	1.25	74.94	4.50	261	1.31	78.8	4.73	275	(6-50)	0.94	1.22	(1500)	170	113	57
53	308 460	8.84	0.143	1.26	75.86	4.55	265	1.31	78.8	4.73	275	(6-50)	0.95	1.23	(1500)	172	115	57
54	314 280	9.01	0.142	1.28	76.75	4.60	268	1.31	78.8	4.73	275	(6-50)	0.96	1.25	(1500)	174	116	58

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
55	320 100	9.17	0.141	1.29	77.62	4.66	271	1.31	78.8	4.73	275	(6-50)	0.97	1.26	(1500)	176	117	59
56	325 920	9.34	0.140	1.31	78.47	4.71	274	1.31	78.8	4.73	275	(6-50)	0.98	1.28	(1500)	178	119	59
57	331 740	9.51	0.140	1.33	79.87	4.79	279	1.31	78.8	4.73	275	(6-50)	1.00	1.30	(1500)	181	121	60
58	337 560	9.67	0.139	1.34	80.69	4.84	282	1.69	101.2	6.07	350	(6-60)	1.01	1.31	(1500)	183	122	61
59	343 380	9.84	0.138	1.36	81.49	4.89	284	1.69	101.2	6.07	350	(6-60)	1.02	1.32	(1500)	185	123	62
60	349 200	10.01	0.137	1.37	82.27	4.94	287	1.69	101.2	6.07	350	(6-60)	1.03	1.34	(1500)	187	124	62
61	355 020	10.18	0.136	1.38	83.03	4.98	290	1.69	101.2	6.07	350	(6-60)	1.04	1.35	(1500)	188	126	63
62	360 840	10.34	0.135	1.40	83.77	5.03	292	1.69	101.2	6.07	350	(6-60)	1.05	1.36	(1500)	190	127	63
63	366 660	10.51	0.135	1.42	85.12	5.11	297	1.69	101.2	6.07	350	(6-60)	1.06	1.38	(1500)	193	129	64
64	372 480	10.68	0.134	1.43	85.83	5.15	299	1.69	101.2	6.07	350	(6-60)	1.07	1.40	(1500)	195	130	65
65	378 300	10.84	0.133	1.44	86.52	5.19	302	1.69	101.2	6.07	350	(6-60)	1.08	1.41	(1500)	196	131	65
66	384 120	11.01	0.132	1.45	87.19	5.23	304	1.69	101.2	6.07	350	(6-60)	1.09	1.42	(1500)	198	132	66
67	389 940	11.18	0.132	1.48	88.52	5.31	309	1.69	101.2	6.07	350	(6-60)	1.11	1.44	(1500)	201	134	67
68	395 760	11.34	0.131	1.49	89.16	5.35	311	1.69	101.2	6.07	350	(6-60)	1.11	1.45	(1500)	202	135	67
69	401 580	11.51	0.130	1.50	89.78	5.39	313	1.69	101.2	6.07	350	(6-60)	1.12	1.46	(1500)	204	136	68
70	407 400	11.68	0.130	1.52	91.08	5.46	318	1.69	101.2	6.07	350	(6-60)	1.14	1.48	(1500)	207	138	69
71	413 220	11.84	0.129	1.53	91.67	5.50	320	1.69	101.2	6.07	350	(6-60)	1.15	1.49	(1500)	208	139	69
72	419 040	12.01	0.128	1.54	92.24	5.53	322	1.69	101.2	6.07	350	(6-60)	1.15	1.50	(1500)	209	139	70
73	424 860	12.18	0.128	1.56	93.52	5.61	326	1.69	101.2	6.07	350	(6-60)	1.17	1.52	(1500)	212	141	71
74	430 680	12.34	0.127	1.57	94.06	5.64	328	1.69	101.2	6.07	350	(6-60)	1.18	1.53	(1500)	213	142	71
75	436 500	12.51	0.127	1.59	95.33	5.72	333	1.69	101.2	6.07	350	(6-60)	1.19	1.55	(1500)	216	144	72
76	442 320	12.68	0.126	1.60	95.84	5.75	334	1.69	101.2	6.07	350	(6-60)	1.20	1.56	(1500)	217	145	72
77	448 140	12.84	0.126	1.62	97.10	5.83	339	1.69	101.2	6.07	350	(6-60)	1.21	1.58	(1500)	220	147	73
78	453 960	13.01	0.125	1.63	97.58	5.86	340	1.69	101.2	6.07	350	(6-60)	1.22	1.59	(1500)	221	148	74
79	459 780	13.18	0.124	1.63	98.04	5.88	342	1.69	101.2	6.07	350	(6-60)	1.23	1.59	(1500)	222	148	74
80	465 600	13.34	0.124	1.65	99.29	5.96	346	1.69	101.2	6.07	350	(6-60)	1.24	1.61	(2000)	225	150	75
81	471 420	13.51	0.123	1.66	99.72	5.98	348	1.69	101.2	6.07	350	(6-60)	1.25	1.62	(2000)	226	151	75
82	477 240	13.68	0.123	1.68	100.95	6.06	352	1.69	101.2	6.07	350	(6-60)	1.26	1.64	(2000)	229	153	76
83	483 060	13.85	0.122	1.69	101.35	6.08	354	1.69	101.2	6.07	350	(6-60)	1.27	1.65	(2000)	230	153	77
84	488 880	14.01	0.122	1.71	102.57	6.15	358	2.17	130.0	7.80	450	(6-70)	1.28	1.67	(2000)	233	155	78
85	494 700	14.18	0.121	1.72	102.94	6.18	359	2.17	130.0	7.80	450	(6-70)	1.29	1.67	(2000)	233	156	78
86	500 520	14.35	0.121	1.74	104.15	6.25	363	2.17	130.0	7.80	450	(6-70)	1.30	1.69	(2000)	236	157	79
87	506 340	14.51	0.120	1.74	104.49	6.27	365	2.17	130.0	7.80	450	(6-70)	1.31	1.70	(2000)	237	158	79
88	512 160	14.68	0.120	1.76	105.69	6.34	369	2.17	130.0	7.80	450	(6-70)	1.32	1.72	(2000)	240	160	80
89	517 980	14.85	0.120	1.78	106.89	6.41	373	2.17	130.0	7.80	450	(6-70)	1.34	1.74	(2000)	242	162	81
90	523 800	15.01	0.119	1.79	107.19	6.43	374	2.17	130.0	7.80	450	(6-70)	1.34	1.74	(2000)	243	162	81
91	529 620	15.18	0.119	1.81	108.38	6.50	378	2.17	130.0	7.80	450	(6-70)	1.36	1.76	(2000)	246	164	82
92	535 440	15.35	0.118	1.81	108.65	6.52	379	2.17	130.0	7.80	450	(6-70)	1.36	1.77	(2000)	246	164	82
93	541 260	15.51	0.118	1.83	109.83	6.59	383	2.17	130.0	7.80	450	(6-70)	1.37	1.79	(2000)	249	166	83
94	547 080	15.68	0.117	1.83	110.07	6.60	384	2.17	130.0	7.80	450	(6-70)	1.38	1.79	(2000)	250	166	83
95	552 900	15.85	0.117	1.85	111.25	6.67	388	2.17	130.0	7.80	450	(6-70)	1.39	1.81	(2000)	252	168	84
96	558 720	16.01	0.117	1.87	112.42	6.74	392	2.17	130.0	7.80	450	(6-70)	1.41	1.83	(2000)	255	170	85
97	564 540	16.18	0.116	1.88	112.62	6.76	393	2.17	130.0	7.80	450	(6-70)	1.41	1.83	(2000)	255	170	85
98	570 360	16.35	0.116	1.90	113.78	6.83	397	2.17	130.0	7.80	450	(6-70)	1.42	1.85	(2000)	258	172	86
99	576 180	16.51	0.116	1.92	114.94	6.90	401	2.17	130.0	7.80	450	(6-70)	1.44	1.87	(2000)	261	174	87
100	582 000	16.68	0.115	1.92	115.10	6.91	402	2.17	130.0	7.80	450	(6-70)	1.44	1.87	(2000)	261	174	87

Performance data

TransTherm® aqua F


Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 65/30 °C (35 K)	Required heating water buffer storage tank volume at 65/30 °C (35 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 65/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 65/30 °C (35 K)	Time: 30 min 65/30 °C (35 K)	Time: 60 min 65/30 °C (35 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
1	5820	0.17	1.00	0.17	10.01	0.60	35	0.15	9.2	0.55	32	(6-10)	0.14	0.19	(200)	23	15	8
2	11640	0.33	0.680	0.23	13.61	0.82	47	0.24	14.3	0.86	60	(6-16)	0.19	0.25	(200)	31	21	10
3	17460	0.50	0.544	0.27	16.33	0.98	57	0.43	25.8	1.55	60	(6-16)	0.23	0.30	(300)	37	25	12
4	23280	0.67	0.466	0.31	18.66	1.12	65	0.38	23.0	1.38	80	(6-20)	0.27	0.35	(300)	42	28	14
5	29100	0.83	0.415	0.35	20.77	1.25	72	0.38	23.0	1.38	80	(6-20)	0.30	0.39	(500)	47	31	16
6	34920	1.00	0.377	0.38	22.64	1.36	79	0.38	23.0	1.38	80	(6-20)	0.32	0.42	(500)	51	34	17
7	40740	1.17	0.349	0.41	24.45	1.47	85	0.60	36.2	2.17	126	(6-30)	0.35	0.45	(500)	55	37	18
8	46560	1.33	0.349	0.47	27.94	1.68	97	0.60	36.2	2.17	126	(6-30)	0.40	0.52	(500)	63	42	21
9	52380	1.50	0.308	0.46	27.74	1.66	97	0.60	36.2	2.17	126	(6-30)	0.40	0.52	(500)	63	42	21
10	58200	1.67	0.292	0.49	29.23	1.75	102	0.60	36.2	2.17	126	(6-30)	0.42	0.54	(500)	66	44	22
11	64020	1.83	0.279	0.51	30.72	1.84	107	0.60	36.2	2.17	126	(6-30)	0.44	0.57	(500)	70	46	23
12	69840	2.00	0.268	0.54	32.19	1.93	112	0.60	36.2	2.17	126	(6-30)	0.46	0.60	(500)	73	49	24
13	75660	2.17	0.258	0.56	33.57	2.01	117	0.60	36.2	2.17	126	(6-30)	0.48	0.62	(500)	76	51	25
14	81480	2.34	0.249	0.58	34.89	2.09	122	0.60	36.2	2.17	126	(6-30)	0.50	0.65	(500)	79	53	26
15	87300	2.50	0.242	0.61	36.33	2.18	127	0.60	36.2	2.17	126	(6-30)	0.52	0.67	(800)	82	55	27
16	93120	2.67	0.235	0.63	37.63	2.26	131	0.83	49.7	2.98	173	(6-40)	0.54	0.70	(800)	85	57	28
17	98940	2.84	0.228	0.65	38.79	2.33	135	0.83	49.7	2.98	173	(6-40)	0.55	0.72	(800)	88	59	29
18	104 760	3.00	0.223	0.67	40.17	2.41	140	0.83	49.7	2.98	173	(6-40)	0.57	0.75	(800)	91	61	30
19	110 580	3.17	0.217	0.69	41.27	2.48	144	0.83	49.7	2.98	173	(6-40)	0.59	0.77	(800)	94	62	31
20	116 400	3.34	0.212	0.71	42.44	2.55	148	0.83	49.7	2.98	173	(6-40)	0.61	0.79	(800)	96	64	32
21	122 220	3.50	0.208	0.73	43.72	2.62	153	0.83	49.7	2.98	173	(6-40)	0.62	0.81	(800)	99	66	33
22	128 040	3.67	0.204	0.75	44.92	2.70	157	0.83	49.7	2.98	173	(6-40)	0.64	0.83	(800)	102	68	34
23	133 860	3.84	0.200	0.77	46.04	2.76	161	0.83	49.7	2.98	173	(6-40)	0.66	0.86	(800)	104	70	35
24	139 680	4.00	0.196	0.78	47.08	2.82	164	0.83	49.7	2.98	173	(6-40)	0.67	0.87	(800)	107	71	36
25	145 500	4.17	0.193	0.80	48.29	2.90	168	0.83	49.7	2.98	173	(6-40)	0.69	0.90	(800)	110	73	37
26	151 320	4.34	0.190	0.82	49.44	2.97	173	0.83	49.7	2.98	173	(6-40)	0.71	0.92	(800)	112	75	37
27	157 140	4.50	0.187	0.84	50.53	3.03	176	0.83	49.7	2.98	173	(6-40)	0.72	0.94	(800)	115	76	38
28	162 960	4.67	0.184	0.86	51.56	3.09	180	1.03	61.7	3.70	215	(6-50)	0.74	0.96	(800)	117	78	39
29	168 780	4.84	0.181	0.88	52.54	3.15	183	1.03	61.7	3.70	215	(6-50)	0.75	0.98	(800)	119	79	40
30	174 600	5.00	0.179	0.90	53.75	3.22	188	1.03	61.7	3.70	215	(6-50)	0.77	1.00	(1000)	122	81	41
31	180 420	5.17	0.176	0.91	54.61	3.28	191	1.03	61.7	3.70	215	(6-50)	0.78	1.01	(1000)	124	83	41
32	186 240	5.34	0.174	0.93	55.73	3.34	194	1.03	61.7	3.70	215	(6-50)	0.80	1.04	(1000)	126	84	42
33	192 060	5.50	0.172	0.95	56.81	3.41	198	1.03	61.7	3.70	215	(6-50)	0.81	1.06	(1000)	129	86	43
34	197 880	5.67	0.170	0.96	57.85	3.47	202	1.03	61.7	3.70	215	(6-50)	0.83	1.07	(1000)	131	87	44
35	203 700	5.84	0.168	0.98	58.85	3.53	205	1.03	61.7	3.70	215	(6-50)	0.84	1.09	(1000)	133	89	44
36	209 520	6.01	0.166	1.00	59.81	3.59	209	1.03	67.7	3.70	215	(6-50)	0.85	1.11	(1000)	136	90	45
37	215 340	6.17	0.164	1.01	60.73	3.64	212	1.03	61.7	3.70	215	(6-50)	0.87	1.13	(1000)	138	92	46
38	221 160	6.34	0.163	1.03	61.99	3.72	216	1.03	61.7	3.70	215	(6-50)	0.89	1.15	(1000)	141	94	47
39	226 980	6.51	0.161	1.05	62.84	3.77	219	1.06	63.7	3.82	220	(6-60)	0.90	1.17	(1000)	143	95	48
40	232 800	6.67	0.159	1.06	63.65	3.82	222	1.06	63.7	3.82	220	(6-60)	0.91	1.18	(1000)	144	96	48
41	238 620	6.84	0.158	1.08	64.84	3.89	226	1.35	81.0	4.86	280	(6-70)	0.93	1.20	(1000)	147	98	49
42	244 440	7.01	0.156	1.09	65.58	3.93	229	1.35	81.0	4.86	280	(6-70)	0.94	1.22	(1000)	149	99	50
43	250 260	7.17	0.155	1.11	66.71	4.00	233	1.35	81.0	4.86	280	(6-70)	0.95	1.24	(1000)	151	101	50
44	256 080	7.34	0.154	1.13	67.82	4.07	237	1.35	81.0	4.86	280	(6-70)	0.97	1.26	(1500)	154	103	51
45	261 900	7.51	0.152	1.14	68.46	4.11	239	1.35	81.0	4.86	280	(6-70)	0.98	1.27	(1500)	155	104	52
46	267 720	7.67	0.151	1.16	69.52	4.17	243	1.35	81.0	4.86	280	(6-70)	0.99	1.29	(1500)	158	105	53
47	273 540	7.84	0.150	1.18	70.56	4.23	246	1.35	81.0	4.86	280	(6-70)	1.01	1.31	(1500)	160	107	53
48	279 360	8.01	0.149	1.19	71.58	4.29	250	1.35	81.0	4.86	280	(6-70)	1.02	1.33	(1500)	162	108	54
49	285 180	8.17	0.148	1.21	72.58	4.35	253	1.35	81.0	4.86	280	(6-70)	1.04	1.35	(1500)	165	110	55
50	291 000	8.34	0.146	1.22	73.06	4.38	255	1.35	81.0	4.86	280	(6-70)	1.04	1.36	(1500)	166	110	55
51	296 820	8.51	0.145	1.23	74.01	4.44	258	1.35	81.0	4.86	280	(6-70)	1.06	1.37	(1500)	168	112	56
52	302 640	8.67	0.144	1.25	74.94	4.50	261	1.35	81.0	4.86	280	(6-70)	1.07	1.39	(1500)	170	113	57
53	308 460	8.84	0.143	1.26	75.86	4.55	265	1.35	81.0	4.86	280	(6-70)	1.08	1.41	(1500)	172	115	57
54	314 280	9.01	0.142	1.28	76.75	4.60	268	1.35	81.0	4.86	280	(6-70)	1.10	1.43	(1500)	174	116	58

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	Peak flow rate TransTherm® aqua F (DHW)	DHW calorifier output TransTherm® aqua F	TransTherm® aqua F	Required heating water volume at 65/30 °C (35 K)	Required heating water buffer storage tank volume at 65/30 °C (35 K)	Buffer storage tank 1 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 65/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 65/30 °C (35 K)	Time: 30 min 65/30 °C (35 K)	Time: 60 min 65/30 °C (35 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
55	320 100	9.17	0.141	1.29	77.62	4.66	271	1.35	81.0	4.86	280	(6-70)	1.11	1.44	(1500)	176	117	59
56	325 920	9.34	0.140	1.31	78.47	4.71	274	1.35	81.0	4.86	280	(6-70)	1.12	1.46	(1500)	178	119	59
57	331 740	9.51	0.140	1.33	79.87	4.79	279	1.35	81.0	4.86	280	(6-70)	1.14	1.48	(1500)	181	121	60
58	337 560	9.67	0.139	1.34	80.69	4.84	282	1.83	109.8	6.59	380	(6-80)	1.15	1.50	(1500)	183	122	61
59	343 380	9.84	0.138	1.36	81.49	4.89	284	1.83	109.8	6.59	380	(6-80)	1.16	1.51	(1500)	185	123	62
60	349 200	10.01	0.137	1.37	82.27	4.94	287	1.83	109.8	6.59	380	(6-80)	1.18	1.53	(1500)	187	124	62
61	355 020	10.18	0.136	1.38	83.03	4.98	290	1.83	109.8	6.59	380	(6-80)	1.19	1.54	(1500)	188	126	63
62	360 840	10.34	0.135	1.40	83.77	5.03	292	1.83	109.8	6.59	380	(6-80)	1.20	1.56	(1500)	190	127	63
63	366 660	10.51	0.135	1.42	85.12	5.11	297	1.83	109.8	6.59	380	(6-80)	1.22	1.58	(1500)	193	129	64
64	372 480	10.68	0.134	1.43	85.83	5.15	299	1.83	109.8	6.59	380	(6-80)	1.23	1.59	(1500)	195	130	65
65	378 300	10.84	0.133	1.44	86.52	5.19	302	1.83	109.8	6.59	380	(6-80)	1.24	1.61	(1500)	196	131	65
66	384120	11.01	0.132	1.45	87.19	5.23	304	1.83	109.8	6.59	380	(6-80)	1.25	1.62	(1500)	198	132	66
67	389 940	11.18	0.132	1.48	88.52	5.31	309	1.83	109.8	6.59	380	(6-80)	1.26	1.64	(1500)	201	134	67
68	395 760	11.34	0.131	1.49	89.16	5.35	311	1.83	109.8	6.59	380	(6-80)	1.27	1.66	(1500)	202	135	67
69	401 580	11.51	0.130	1.50	89.78	5.39	313	1.83	109.8	6.59	380	(6-80)	1.28	1.67	(1500)	204	136	68
70	407 400	11.68	0.130	1.52	91.08	5.46	318	1.83	109.8	6.59	380	(6-80)	1.30	1.69	(1500)	207	138	69
71	413 220	11.84	0.129	1.53	91.67	5.50	320	1.83	109.8	6.59	380	(6-80)	1.31	1.70	(1500)	208	139	69
72	419 040	12.01	0.128	1.54	92.24	5.53	322	1.83	109.8	6.59	380	(6-80)	1.32	1.71	(1500)	209	139	70
73	424 860	12.18	0.128	1.56	93.52	5.61	326	1.83	109.8	6.59	380	(6-80)	1.34	1.74	(1500)	212	141	71
74	430 680	12.34	0.127	1.57	94.06	5.64	328	1.83	109.8	6.59	380	(6-80)	1.34	1.75	(1500)	213	142	71
75	436 500	12.51	0.127	1.59	95.33	5.72	333	1.83	109.8	6.59	380	(6-80)	1.36	1.77	(1500)	216	144	72
76	442 320	12.68	0.126	1.60	95.84	5.75	334	1.83	109.8	6.59	380	(6-80)	1.37	1.78	(1500)	217	145	72
77	448 140	12.84	0.126	1.62	97.10	5.83	339	1.83	109.8	6.59	380	(6-80)	1.39	1.80	(1500)	220	147	73
78	453 960	13.01	0.125	1.63	97.58	5.86	340	1.83	109.8	6.59	380	(6-80)	1.39	1.81	(1500)	221	148	74
79	459 780	13.18	0.124	1.63	98.04	5.88	342	1.83	109.8	6.59	380	(6-80)	1.40	1.82	(1500)	222	148	74
80	465 600	13.34	0.124	1.65	99.29	5.96	346	1.83	109.8	6.59	380	(6-80)	1.42	1.84	(2000)	225	150	75
81	471 420	13.51	0.123	1.66	99.72	5.98	348	1.83	109.8	6.59	380	(6-80)	1.42	1.85	(2000)	226	151	75
82	477 240	13.68	0.123	1.68	100.95	6.06	352	1.83	109.8	6.59	380	(6-80)	1.44	1.88	(2000)	229	153	76
83	483 060	13.85	0.122	1.69	101.35	6.08	354	1.83	109.8	6.59	380	(6-80)	1.45	1.88	(2000)	230	153	77
84	488 880	14.01	0.122	1.71	102.57	6.15	358	1.83	109.8	6.59	380	(6-80)	1.47	1.91	(2000)	233	155	78
85	494 700	14.18	0.121	1.72	102.94	6.18	359	1.83	109.8	6.59	380	(6-80)	1.47	1.91	(2000)	233	156	78
86	500 520	14.35	0.121	1.74	104.15	6.25	363	1.83	109.8	6.59	380	(6-80)	1.49	1.93	(2000)	236	157	79
87	506 340	14.51	0.120	1.74	104.49	6.27	365	1.83	109.8	6.59	380	(6-80)	1.49	1.94	(2000)	237	158	79
88	512 160	14.68	0.120	1.76	105.69	6.34	369	1.83	109.8	6.59	380	(6-80)	1.51	1.96	(2000)	240	160	80
89	517 980	14.85	0.120	1.78	106.89	6.41	373	1.83	109.8	6.59	380	(6-80)	1.53	1.99	(2000)	242	162	81
90	523 800	15.01	0.119	1.79	107.19	6.43	374	1.83	109.8	6.59	380	(6-80)	1.53	1.99	(2000)	243	162	81
91	529 620	15.18	0.119	1.81	108.38	6.50	378	1.83	109.8	6.59	380	(6-80)	1.55	2.01	(2000)	246	164	82
92	535 440	15.35	0.118	1.81	108.65	6.52	379	1.83	109.8	6.59	380	(6-80)	1.55	2.02	(2000)	246	164	82
93	541 260	15.51	0.118	1.83	109.83	6.59	383	1.83	109.8	6.59	380	(6-80)	1.57	2.04	(2000)	249	166	83
94	547 080	15.68	0.117	1.83	110.07	6.60	384	1.83	109.8	6.59	380	(6-80)	1.57	2.04	(2000)	250	166	83
95	552 900	15.85	0.117	1.85	111.25	6.67	388	2.51	150.3	9.02	520	(6-90)	1.59	2.07	(2000)	252	168	84
96	558 720	16.01	0.117	1.87	112.42	6.74	392	2.51	150.3	9.02	520	(6-90)	1.61	2.09	(2000)	255	170	85
97	564 540	16.18	0.116	1.88	112.62	6.76	393	2.51	150.3	9.02	520	(6-90)	1.61	2.09	(2000)	255	170	85
98	570 360	16.35	0.116	1.90	113.78	6.83	397	2.51	150.3	9.02	520	(6-90)	1.63	2.11	(2000)	258	172	86
99	576 180	16.51	0.116	1.92	114.94	6.90	401	2.51	150.3	9.02	520	(6-90)	1.64	2.13	(2000)	261	174	87
100	582 000	16.68	0.115	1.92	115.10	6.91	402	2.51	150.3	9.02	520	(6-90)	1.64	2.14	(2000)	261	174	87

Performance data


TransTherm® aqua F (6-60)

Performance data		Q	VS	VS	VS	Buffer storage tank
primary	secondary	kW	l/s	l/min	m³/h	min. content in l [1]
70 °C/30 °C	10 °C/60 °C	350	1.67	100.33	6.02	1405
65 °C/30 °C	10 °C/60 °C	220	1.05	63.07	3.78	883
65 °C/30 °C	10 °C/55 °C	315	1.67	100.33	6.02	1405
65 °C/30 °C	10 °C/50 °C	280	1.67	100.33	6.02	1405
60 °C/30 °C	10 °C/55 °C	255	1.35	81.22	4.87	1137
60 °C/30 °C	10 °C/50 °C	280	1.67	100.33	6.02	1405
55 °C/30 °C	10 °C/50 °C	230	1.37	82.42	4.95	1154
55 °C/30 °C	10 °C/45 °C	245	1.67	100.33	6.02	1405




TransTherm® aqua F (6-70)

Performance data		Q	VS	VS	VS	Buffer storage tank
primary	secondary	kW	l/s	l/min	m³/h	min. content in l [1]
70 °C/30 °C	10 °C/60 °C	450	2.15	129.00	7.74	1806
65 °C/30 °C	10 °C/60 °C	280	1.34	80.27	4.82	1124
65 °C/30 °C	10 °C/55 °C	405	2.15	129.00	7.74	1806
65 °C/30 °C	10 °C/50 °C	360	2.15	129.00	7.74	1806
60 °C/30 °C	10 °C/55 °C	320	1.70	101.93	6.12	1427
60 °C/30 °C	10 °C/50 °C	360	2.15	129.00	7.74	1806
55 °C/30 °C	10 °C/50 °C	290	1.73	103.92	6.24	1455
55 °C/30 °C	10 °C/45 °C	315	2.15	129.00	7.74	1806




TransTherm® aqua F (6-80)

Performance data		Q	VS	VS	VS	Buffer storage tank
primary	secondary	kW	l/s	l/min	m³/h	min. content in l [1]
70 °C/30 °C	10 °C/60 °C	580	2.77	166.27	9.98	2328
65 °C/30 °C	10 °C/60 °C	380	1.82	108.93	6.54	1525
65 °C/30 °C	10 °C/55 °C	530	2.81	168.81	10.13	2363
65 °C/30 °C	10 °C/50 °C	490	2.93	175.58	10.54	2458
60 °C/30 °C	10 °C/55 °C	420	2.23	133.78	8.03	1873
60 °C/30 °C	10 °C/50 °C	485	2.90	173.79	10.43	2433
55 °C/30 °C	10 °C/50 °C	380	2.27	136.17	8.17	1906
55 °C/30 °C	10 °C/45 °C	430	2.93	176.10	10.57	2465



TransTherm® aqua F (6-90)

Performance data		Q	VS	VS	VS	Buffer storage tank
primary	secondary	kW	l/s	l/min	m³/h	min. content in l [1]
70 °C/30 °C	10 °C/60 °C	700	3.34	200.67	12.04	2809
65 °C/30 °C	10 °C/60 °C	520	2.48	149.07	8.94	2087
65 °C/30 °C	10 °C/55 °C	630	3.34	200.67	12.04	2809
65 °C/30 °C	10 °C/50 °C	560	3.34	200.67	12.04	2809
60 °C/30 °C	10 °C/55 °C	530	2.81	168.81	10.13	2363
60 °C/30 °C	10 °C/50 °C	560	3.34	200.67	12.04	2809
55 °C/30 °C	10 °C/50 °C	480	2.87	172.00	10.32	2408
55 °C/30 °C	10 °C/45 °C	490	3.34	200.67	12.04	2809



[1] The calculation for the content of the buffer storage tank depends on the temperature spread.
Here, 0.7 has been set for the temperature spread and 2 for short non-draw-off times. See calculation of the required buffer volume

Performance data

Calculation of the required buffer volume

In order to provide the required energy for domestic water heating, a fresh water station is generally connected to a buffer storage tank. The volume of the buffer storage tank is determined by the domestic hot water requirement of the installation, the storage temperature in the buffer storage tank and the user behaviour.

VP = V x t x (Tp/Tww) x Sn

VP	Required minimum volume of the buffer storage tank
V	Calculated peak flow of the fresh water module
t	Time for which the peak flow is required. The value can be gear towards, for example the duration of the tub filling, user information or the standard value from DIN 4708 (10 min.)
(Tp/Tww)	For the temperature spread between the buffer storage tank and domestic water
	0.5 for a high temperature spread (e.g. 90/45 °C)
	0.7 for a medium temperature spread (e.g. 70/45 °C)
	1 for a low temperature spread (e.g. 55/45 °C)
Sn	Safety factor for observing user behaviour
	1 normal non-draw-off times
	2 short non-draw-off times
	3-4 very short non-draw-off times


Example calculation

VP	V	t	(Tp/Tww)	Sn
(l)	(l/min)	(min)		
1576	78.8	10.0	1.0	2.0

Result

Input


Pressure drop (ΔP / Q max) – domestic water side (secondary)




Circulating pump characteristic curves

for circulation set ¾″


Δp-v (variable)



Constant speed




for circulation set 1″ and 1¼″





Fresh water module TransTherm® aqua F (6-60)

(Dimensions in mm)

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.








** With circulation 680

TransTherm® aqua F	Weight in kg
(6-60)	123

1	Safety valve Hot water 10 bar	
2	Filling/drain valve	
3	Heat exchanger	
4	Three-way valve	
5	Circulating pump	
6	Circulation [1]	DN 32, Rp 1¼″ (DN 25, Rp 1″) (IT)
7	Cold water	DN 32, Rp 1¼″ (IT)
8 *	Hot water	DN 32, Rp 1¼″ (IT)
9	Flow heating water	DN 40, Rp 1½″ (IT)
10	Return heating water	DN 40, Rp 1½″ (IT)

[1] Optional, connection and installation on site


Version incl. circulation set





Fresh water module TransTherm® aqua F (6-70)

(Dimensions in mm)

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.








** With circulation 680

TransTherm® aqua F	Weight in kg
(6-70)	172

1 Safety valve Hot water 10 bar
2 Filling/drain valve
3 Heat exchanger
4 Three-way valve
5 Circulating pump
6 Circulation [1] DN 32, Rp 1 ¼″ (DN 25, Rp 1″) (IT)
7 Cold water DN 32, Rp 1 ¼″ (IT)
8 * Hot water DN 32, Rp 1 ¼″ (IT)
9 Flow heating water DN 50, Rp 2″ (IT)
10 Return heating water DN 50, Rp 2″ (IT)

[1] Optional, connection and installation on site


Version incl. circulation set





Fresh water module TransTherm® aqua F (6-80)

(Dimensions in mm)


*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.







Version incl. circulation set



** With circulation 680

TransTherm® aqua F	Weight in kg
(6-80)	202


1	Safety valve Hot water 10 bar	
2	Filling/drain valve	
3	Heat exchanger	
4	Three-way valve	
5	Circulating pump	
6	Circulation [1]	DN 32, Rp 1¼″ (DN 25, Rp 1″) (IT)
7	Cold water	DN 40, Rp 1½″ (IT)
8 *	Hot water	DN 40, Rp 1½″ (IT)
9	Flow heating water	DN 65 AE (weld-on end)
10	Return heating water	DN 65 AE (weld-on end)


[1] Optional, connection and installation on site


Fresh water module TransTherm® aqua F (6-90)

(Dimensions in mm)


*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.







Version incl. circulation set



** With circulation 700


TransTherm® aqua F	Weight in kg
(6-90)	214

1	Safety valve Hot water 10 bar	
2	Filling/drain valve	
3	Heat exchanger	
4	Three-way valve	
5	Circulating pump	
6	Circulation [1)]	DN 32, Rp 1¼″ (DN 25, Rp 1″) (IT)
7	Cold water	DN 50, Rp 2″ (IT)
8 *	Hot water	DN 50, Rp 2″ (IT)
9	Flow heating water	DN 65 AE (weld-on end)
10	Return heating water	DN 65 AE (weld-on end)

[1)] Optional, connection and installation on site

Water heating
TransTherm® aqua F

*** For application according to the SVGW**
The installation of ball valves is not permitted in Switzerland according to SVGW regulation W3.



TTE-FW	Basic module district heating/fresh water
TW	Flow temperature monitor (if required)
VFP	Flow sensor primary
VFW	Flow sensor DHW
RLF	Return sensor primary
RLF2	Return sensor domestic cold water
SF	Calorifier sensor
SF1	Calorifier sensor 1
RLFZ	Circulation sensor
SLP1	Calorifier charging pump primary
FVT	Flow rate sensor
YFW	Three-way valve with actuator
ZKP	Recirculation pump
Y11	Return switching with actuator
Option	
BM	TopTronic® E control module
SF2	Calorifier sensor 2

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval TransTherm® aqua

Calorifier continuous flow system TransTherm® aqua FS (7-10)-(7-90)




Table of contents

- Description 5
- Part numbers 7
- Technical data 10
- Dimensions 18
- Example 20

Calorifier continuous flow system

Consisting of:
- fresh water module TransTherm® aqua FS
- buffer storage tank (option)

Fresh water module TransTherm® aqua FS

Consisting of:
Charging circuit flow:
- ball valve with thermometer handle
- three-way valve
- drive Siemens SAT 61 (0-10 V)
- Stratos pump
- sleeve for cable sensor M10 x 1
- sleeve for AGFW sensor

Charging circuit high temperature return:
- flow rate limiter Hydrocontrol VTR
- test port OVENTROP set 2
- three-way valve
- drive Siemens SAT 61 (0-10 V)
- sleeve for cable sensor M10 x 1
- sleeve for AGFW sensor

Charging circuit low temperature return:
- flow rate limiter Hydrocontrol VTR
- test port OVENTROP set 2
- ball valve WESA 1533
- sleeve for cable sensor M10 x 1
- sleeve for AGFW sensor

Heat exchanger supplementary heater:
- plate heat exchanger DANFOSS

Heat exchanger preheater:
- plate heat exchanger DANFOSS


Domestic hot water DHW:
- ball valve OVENTROP Optibal TW
- bimetallic thermometer OVENTROP TW
- sampling valve OVENTROP Aquastrom P (optional)
- ball valve OVENTROP
- sleeve for AGFW sensor

Domestic hot water circulation DHWC:
- flow rate limiter Aquastrom
- sampling valve OVENTROP Aquastrom P
- measurement nozzle OVENTROP
- circulating pump
- non-return valve TS73S
- sleeve for AGFW sensor

Domestic water DW:
- flow rate limiter Aquastrom C
- non-return valve ROSSWEINER
- adapter
- flow rate sensor HUBA
- ball valve OVENTROP
- sleeve for AGFW sensor
- diaphragm safety valve

Control panel control system:
- control panel casing SCHNEIDER
- control TTE-FW
- fuses
- sockets
- terminals

Stand frame:
- frame with corrosion protection coating RAL 9005
- height-adjustable and vibration-damped feet



Range
Fresh water module

TransTherm® aqua FS type	Output kW
(7-10)	50
(7-16)	90
(7-20)	130
(7-30)	175
(7-40)	220
(7-50)	275
(7-60)	358
(7-70)	453
(7-80)	569
(7-90)	717

Delivery time on request

Thermal insulation:
- thermal insulation of the heat exchanger with 30 mm EPP mouldings
- thermal insulation of the pipes with EPP mouldings. insulation thickness of 50 % according to EnEV
- deep black, similar to RAL 9005
- suitable for damp rooms
- CFC-free
- normal flammability according to DIN 4102-1 and EN 13501-1 (fuel class: B2)
- no bleaching or disintegration of the insulation under the influence of UV

Delivery
- The buffer storage tank required is not included in the scope of delivery

On site
- Electrical connection of the controller

Suitable buffer storage tanks
see separate chapter

TopTronic® E controller

TopTronic® E basic module
District heating/fresh water
- Control unit for controlling district heating transfer stations in non-communicative networks and the corresponding consumers with integrated control functions for
  - primary valve control
  - cascade management
  - 1 heating circuit with mixer
  - 1 heating circuit without mixer
  - 1 hot water charging circuit
  - various additional functions
- Various functions for domestic hot water:
  - selection of different basic programs (week programs, eco mode, holiday, etc.)
  - various operating modes (e.g. accumulator priority or parallel mode)
  - buffer storage circuit on the primary or secondary side
  - adjustable loading criteria (e.g. adjustable loading times, undershooting the minimum nominal value, etc.)
  - adjustable switch-off criteria (e.g. achieving the set value, achieving the lower sensor set value, etc.)
  - adjustable loading block (if the loading flow temperature is too low, the setpoint temperature is not reached, differential temperature-dependent solar circuit control)

- Definable switching times for circulating pump control
- Outdoor sensor
- Immersion sensor (calorifier sensor)
- Contact sensor (flow temperature sensor)
- Complete plug set for district heating module
- Speed-controlled pumps

No further module expansions or controller modules can be installed in the control panel!

Option

TopTronic® E control module
- Simple, intuitive operating concept
- Display of the most important operating states
- Configurable start screen
- Operating mode selection
- Configurable day and week programmes
- Operation of all connected Hoval CAN bus modules
- Commissioning wizard
- Service and maintenance function
- Fault message management
- Analysis function
- Weather display (with HovalConnect option)
- Adaptation of the heating strategy based on the weather forecast (with HovalConnect option)


Notice
The TopTronic® E control module for operating the basic module district heating/fresh water must be ordered separately!

For further information about the TopTronic® E,
see “Controls”

Delivery
- Incl. thermometer, non-return valves, cut-off ball valves on the domestic water side
- All fittings required for operation, such as strainers, flow balancing and shut-off valves, non-return valves, air vent and drain valve are fitted

Caution
As a result of thermal disinfection of the domestic hot water for legionella protection, increased water temperatures (at least 65 ... 70 °C) occur. Depending on the water quality, this may result in increased calcification at the installed fittings and heat exchangers and also brings the risk of scalding at the tapping points. Corresponding protective measures must be implemented on site.

Calorifier fresh water module



Delivery time on request

TransTherm® aqua FS

Fully assembled station with 2 plate heat exchangers for the provision of domestic hot water using the continuous flow principle and built-in Hoval TopTronic® E control.
The buffer storage tanks required for this are not included in the scope of delivery.

TransTherm® aqua FS	Output kW	Part No.
(7-10)	50	8008 017
(7-16)	90	8008 018
(7-20)	130	8008 019
(7-30)	175	8008 020
(7-40)	220	8008 021
(7-50)	275	8008 022
(7-60)	358	8008 023
(7-70)	453	8008 024
(7-80)	569	8008 025
(7-90)	717	8008 026


Version with copper-free heat exchanger

Delivery time on request

TransTherm® aqua FS

with copper-free heat exchanger

TransTherm® aqua FS	Output kW	Part No.
(7-10)	50	8008 027
(7-16)	90	8008 028
(7-20)	130	8008 029
(7-30)	175	8008 030
(7-40)	220	8008 031

	Part No.
 **TopTronic® E control module black with 4.3″ colour touchscreen** For operation of all controller modules connected to the bus system (basic, solar, buffer modules etc.) Connection to the Hoval bus system via RJ45 plug connection or via plug terminals (max. 0.75 mm²), flat design with flexible installation option Installation: - in control panel of the heat generator - in the Hoval wall casing - in the control panel front, black high-gloss cover, customer-specific configurable start screen, Display of current weather or weather forecast (only possible in combination with HovalConnect) Consisting of: - TopTronic® E control module black - Clamping device set control module - RJ45-RAST 5 CAN cable, L = 500	6043 844
 **Test valve DN 8 G ¼″** for TransTherm® aqua L, L-FW, F, FS Test valve suitable for flame treatment for hygienic-microbiologic tests.	2049 861
  **Sludge separator DM with magnet** made of technopolymer (PO) or brass with insulation (MS)	
DM PO, Rp 1″, 1.3, 10.5	2054 376
DM PO, Rp 1¼″, 2.1, 10.5	2085 523
DM MS, Rp 1½″, 5.4, 63.2	2085 527
DM MS, Rp 2″, 8.2, 70.0	2085 528
Additional sludge separators see “Various system components”	
 **Insulation for sludge separator DM PO 1″** 10 mm insulating caps made of PE-X foam Thermal conductivity 0.035 W/mK Fire resistance (DIN 4102): class B2	2085 524
 **Insulation for sludge separator DM PO 1¼″** 10 mm insulating caps made of PE-X foam Thermal conductivity 0.035 W/mK Fire resistance (DIN 4102): class B2	2086 031

Type	Connection inches	Flow rate at 1.2 m/s flow speed m^3/h	k_v value m^3/h

		Part No.
	**Temperature monitor 0 ... 120 °C** for TransTherm® aqua L, L-FW, F, FS	2048 299
	**Safety temperature monitor 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2048 300
	**Safety temperature limiter 70 ... 130 °C** for TransTherm® aqua L, L-FW, F, FS	2049 619
	**Immersion sleeve G ½″ stainless steel for thermostat** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 8 mm, inner Ø: 6.5 mm	2048 285
	**Immersion sleeve G ½″ stainless steel for 2 thermostats** for TransTherm® aqua L, L-FW, F, FS Installation length = 100 mm Outer Ø: 15 mm, inner Ø: 13.5 mm	2048 288

Services

Services and associated scope of services
see separate catalogue “Hoval Services”

Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.

Performance data

TransTherm® aqua FS (7-10 to 7-50)

Domestic water secondary	TransTherm® aqua FS		Flow temperature heating water 55 °C (6-...)						60 °C (6-...)					
			(10)	(16)	(20)	(30)	(40)	(50)	(10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
55/5 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.25**	**2.04**	**2.51**	**3.71**	**4.76**	**5.66**
	Q max.	kW	-	-	-	-	-	-	43	70	86	127	163	194
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.74**	**1.2**	**1.48**	**2.18**	**2.8**	**3.33**
55/10 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**1.11**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	-	-	-	-	-	-	38	70	86	127	163	193
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.73**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
55/15 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.76**	**1.46**	**1.95**	**3.06**	**4.23**	**5.4**
	Q max.	kW	-	-	-	-	-	-	26	50	67	105	145	185
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.56**	**1.08**	**1.44**	**2.26**	**3.12**	**3.98**
55/20 °C	T return primary	°C	-	-	-	-	-	-	30	30	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	**0.47**	**0.9**	**1.17**	**1.9**	**2.63**	**3.36**
	Q max.	kW	-	-	-	-	-	-	16	31	40	65	90	115
	V̇ secondary	**m³/h**	-	-	-	-	-	-	**0.39**	**0.76**	**0.99**	**1.6**	**2.22**	**2.83**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.71**	**4.76**	**5.63**
	Q max.	kW	37	58	72	105	135	162	44	70	86	127	163	193
	V̇ secondary	**m³/h**	**0.71**	**1.11**	**1.37**	**2**	**2.58**	**3.09**	**0.84**	**1.34**	**1.64**	**2.43**	**3.12**	**3.69**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.28**	**2.04**	**2.51**	**3.73**	**4.81**	**5.69**
	Q max.	kW	38	58	72	105	135	162	44	70	86	128	165	195
	V̇ secondary	**m³/h**	**0.82**	**1.25**	**1.77**	**2.26**	**2.9**	**3.48**	**0.95**	**1.51**	**1.85**	**2.75**	**3.55**	**4.19**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.29**	**2.03**	**2.51**	**3.67**	**4.72**	**5.66**	**1.11**	**1.95**	**2.48**	**3.76**	**4.76**	**5.69**
	Q max.	kW	37	58	72	105	135	162	38	67	85	129	163	195
	V̇ secondary	**m³/h**	**0.91**	**1.43**	**1.77**	**2.58**	**3.32**	**3.99**	**0.94**	**1.65**	**2.09**	**3.18**	**4.01**	**4.8**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.15**	**2.03**	**2.55**	**3.7**	**4.75**	**5.69**	**0.96**	**1.69**	**2.13**	**3.24**	**3.63**	**5.16**
	Q max.	kW	33	58	73	106	136	163	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.05**	**3.91**	**4.69**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**
45/5 °C	T return primary	°C	19	18	18	18	18	17	177	16	16	16	16	15
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.9**	**2.9**	**3.8**	**4.61**	**0.86**	**1.92**	**2.91**	**2.91**	**3.82**	**4.63**
	Q max.	kW	35	80	123	123	162	199	42	95	145	145	192	235
	V̇ secondary	**m³/h**	**0.76**	**1.73**	**2.65**	**2.65**	**3.50**	**4.27**	**0.90**	**2.05**	**3.13**	**3.13**	**4.14**	**5.05**
45/10 °C	T return primary	°C	21	21	20	20	20	20	20	19	19	19	18	18
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.89**	**2.89**	**3.81**	**4.62**	**0.86**	**1.92**	**2.84**	**2.84**	**3.63**	**4.32**
	Q max.	kW	33	74	114	114	151	185	39	89	133	133	172	207
	V̇ secondary	**m³/h**	**0.81**	**1.84**	**2.81**	**2.81**	**3.74**	**4.56**	**0.97**	**2.20**	**3.29**	**3.29**	**4.25**	**5.09**
45/15 °C	T return primary	°C	24	23	23	23	23	23	23	22	21	21	21	21
	V̇ primary	**m³/h**	**0.86**	**1.91**	**2.91**	**2.91**	**3.81**	**4.62**	**0.87**	**1.8**	**2.61**	**2.61**	**3.33**	**3.98**
	Q max.	kW	30	69	106	106	139	170	37	78	115	115	148	178
	V̇ secondary	**m³/h**	**0.88**	**1.99**	**3.05**	**3.05**	**4.02**	**4.90**	**1.07**	**2.26**	**3.31**	**3.31**	**4.26**	**5.12**
45/20 °C	T return primary	°C	27	26	26	26	26	26	25	25	24	24	24	24
	V̇ primary	**m³/h**	**0.86**	**1.92**	**2.91**	**2.91**	**3.71**	**4.41**	**0.85**	**1.63**	**2.36**	**2.36**	**3.02**	**3.61**
	Q max.	kW	27	63	96	96	124	148	33	65	96	96	123	148
	V̇ secondary	**m³/h**	**0.96**	**2.18**	**3.33**	**3.33**	**4.28**	**5.13**	**1.16**	**2.27**	**3.32**	**3.32**	**4.28**	**5.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua FS (7-10 to 7-50)

Domestic water secondary	TransTherm® aqua FS		Flow temperature heating water 65 °C (6-...) (10)	(16)	(20)	(30)	(40)	(50)	70 °C (6-...) (10)	(16)	(20)	(30)	(40)	(50)
60/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.08**	**1.88**	**2.5**	**3.73**	**4.84**	**5.77**	**1.32**	**2.09**	**2.86**	**3.76**	**4.49**	**5.72**
	Q max.	kW	43	75	100	149	193	230	60	95	133	171	209	260
	V̇ secondary	**m³/h**	**0.67**	**1.17**	**1.55**	**2.33**	**3.01**	**3.59**	**0.94**	**1.48**	**2.29**	**2.67**	**3.59**	**4.06**
60/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**1.94**	**2.80**	**3.77**	**4.73**	**5.92**
	Q max.	kW	32	60	80	126	173	215	50	90	130	175	220	275
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.54**	**2.24**	**3.01**	**3.78**	**4.73**
60/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.55**	**1.05**	**1.38**	**2.13**	**3.08**	**3.96**	**0.97**	**1.8**	**2.37**	**3.73**	**4.84**	**5.72**
	Q max.	kW	22	42	55	85	123	158	44	82	108	170	220	260
	V̇ secondary	**m³/h**	**0.42**	**0.8**	**1.05**	**1.63**	**2.35**	**3.02**	**0.84**	**1.57**	**2.08**	**3.24**	**4.21**	**4.98**
60/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.3**	**0.6**	**0.8**	**1.28**	**1.75**	**2.33**	**0.62**	**1.14**	**2.05**	**2.4**	**3.43**	**4.22**
	Q max.	kW	12	24	32	51	70	93	28	52	68	109	156	192
	V̇ secondary	**m³/h**	**0.26**	**0.52**	**0.69**	**1.1**	**1.51**	**2**	**0.6**	**1.12**	**1.47**	**2.36**	**3.36**	**4.14**
55/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.8**	**1.5**	**2.01**	**3.16**	**4.34**	**5.39**	**1.08**	**2.09**	**2.53**	**3.74**	**4.84**	**5.76**
	Q max.	kW	32	60	80	126	173	215	50	95	115	170	220	262
	V̇ secondary	**m³/h**	**0.55**	**1.03**	**1.38**	**2.17**	**2.98**	**3.7**	**0.86**	**1.63**	**1.97**	**2.92**	**3.78**	**4.5**
55/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.3**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.74**	**4.84**	**5.72**
	Q max.	kW	52	82	101	148	192	225	49	85	110	170	220	260
	V̇ secondary	**m³/h**	**0.99**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.24**	**4.21**	**4.98**
55/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.97**	**1.65**	**2.11**	**3.71**	**4.81**	**5.64**	**1.1**	**1.88**	**2.41**	**3.74**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.94**	**1.62**	**2.1**	**3.19**	**4.21**	**5**
55/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/5 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.25**	**2.06**	**2.53**	**3.71**	**4.81**	**5.64**	**1.08**	**1.87**	**2.42**	**3.56**	**4.84**	**5.72**
	Q max.	kW	50	82	101	148	192	225	49	85	110	162	220	260
	V̇ secondary	**m³/h**	**0.95**	**1.57**	**1.93**	**2.83**	**3.67**	**4.3**	**0.94**	**1.62**	**2.1**	**3.09**	**4.21**	**4.98**
50/10 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**1.1**	**1.88**	**2.41**	**3.71**	**4.81**	**5.64**	**0.97**	**1.65**	**2.11**	**3.25**	**4.22**	**5.1**
	Q max.	kW	44	75	96	148	192	225	44	75	96	148	192	232
	V̇ secondary	**m³/h**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**4.84**	**0.95**	**1.61**	**2.07**	**3.19**	**4.13**	**5**
50/15 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.95**	**1.68**	**2.13**	**3.23**	**4.24**	**5.14**	**0.84**	**1.47**	**1.87**	**2.84**	**3.72**	**4.51**
	Q max.	kW	38	67	85	129	169	205	38	67	85	129	169	205
	V̇ secondary	**m³/h**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**	**0.94**	**1.65**	**2.09**	**3.18**	**4.16**	**5.05**
50/20 °C	T return primary	°C	30	30	30	30	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**0.83**	**1.45**	**1.81**	**2.44**	**3.63**	**4.44**	**0.73**	**1.28**	**1.61**	**2.44**	**3.19**	**3.89**
	Q max.	kW	33	58	73	111	145	177	33	58	73	111	145	177
	V̇ secondary	**m³/h**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**	**0.95**	**1.67**	**2.1**	**3.19**	**4.17**	**5.09**
45/5 °C	T return primary	°C	16	15	14	14	14	14	15	13	13	13	12	12
	V̇ primary	**m³/h**	**0.87**	**1.83**	**2.64**	**2.64**	**3.38**	**4.03**	**0.84**	**1.62**	**2.35**	**2.35**	**3.01**	**3.59**
	Q max.	kW	48	104	152	152	196	236	52	104	152	152	196	236
	V̇ secondary	**m³/h**	**1.04**	**2.24**	**3.27**	**3.27**	**4.23**	**5.07**	**1.13**	**2.24**	**3.28**	**3.28**	**4.23**	**5.07**
45/10 °C	T return primary	°C	19	17	17	17	17	16	17	16	16	16	15	15
	V̇ primary	**m³/h**	**0.87**	**1.69**	**2.45**	**2.45**	**3.13**	**3.73**	**0.77**	**1.49**	**2.17**	**2.17**	**2.78**	**3.32**
	Q max.	kW	45	91	134	134	172	206	46	91	133	133	172	206
	V̇ secondary	**m³/h**	**1.13**	**2.25**	**3.30**	**3.30**	**4.24**	**5.09**	**1.13**	**2.24**	**3.29**	**3.29**	**4.24**	**5.09**
45/15 °C	T return primary	°C	21	20	20	20	20	19	20	19	19	19	19	19
	V̇ primary	**m³/h**	**0.8**	**1.55**	**2.24**	**2.24**	**2.87**	**3.43**	**0.71**	**1.36**	**1.98**	**1.98**	**2.54**	**3.03**
	Q max.	kW	39	78	115	115	148	178	40	78	114	114	148	177
	V̇ secondary	**m³/h**	**1.14**	**2.27**	**3.31**	**3.31**	**4.26**	**5.11**	**1.16**	**2.26**	**3.30**	**3.30**	**4.26**	**5.10**
45/20 °C	T return primary	°C	24	23	23	23	23	23	23	23	22	22	22	22
	V̇ primary	**m³/h**	**0.72**	**1.4**	**2.02**	**2.02**	**2.59**	**3.1**	**0.63**	**1.22**	**1.78**	**1.78**	**2.29**	**2.73**
	Q max.	kW	33	66	96	96	123	148	33	65	96	96	124	148
	V̇ secondary	**m³/h**	**1.16**	**2.29**	**3.32**	**3.32**	**4.28**	**5.13**	**1.15**	**2.27**	**3.32**	**3.32**	**4.29**	**5.13**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua FS (7-60 to 7-90)

Domestic water secondary	TransTherm® aqua FS		Flow temperature heating water 52 °C (60)	52 °C (70)	52 °C (80)	52 °C (90)	55 °C (60)	55 °C (70)	55 °C (80)	55 °C (90)	60 °C (60)	60 °C (70)	60 °C (80)	60 °C (90)
60/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
60/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
	Q max.	kW	-	-	-	-	-	-	-	-	-	-	-	-
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	-	-	-	-
55/5 °C	T return primary	°C	-	-	-	-	-	-	-	-	28	28	28	27
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**7.27**	**10.06**	**12.62**	**15.81**
	Q max.	kW	-	-	-	-	-	-	-	-	270	370	470	600
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**4.68**	**6.42**	**8.15**	**10.4**
55/10 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	29	29	29
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**7.30**	**9.04**	**11.82**	**14.63**
	Q max.	kW	-	-	-	-	-	-	-	-	255	320	420	530
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**4.91**	**6.17**	**8.09**	**10.21**
55/15 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**5.20**	**7.23**	**9.25**	**13.01**
	Q max.	kW	-	-	-	-	-	-	-	-	180	250	320	450
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**3.90**	**5.42**	**6.94**	**9.75**
55/20 °C	T return primary	°C	-	-	-	-	-	-	-	-	30	30	30	30
	V̇ primary	**m³/h**	-	-	-	-	-	-	-	-	**3.18**	**4.34**	**5.78**	**7.51**
	Q max.	kW	-	-	-	-	-	-	-	-	110	150	200	260
	V̇ secondary	**m³/h**	-	-	-	-	-	-	-	-	**2.73**	**3.72**	**4.95**	**6.44**
50/5 °C	T return primary	°C	-	-	-	-	25	25	25	24	22	22	21	21
	V̇ primary	**m³/h**	-	-	-	-	**7.32**	**8.93**	**11.59**	**14.69**	**7.17**	**9.14**	**11.65**	**13.93**
	Q max.	kW	-	-	-	-	250	310	405	520	315	405	520	630
	V̇ secondary	**m³/h**	-	-	-	-	**4.82**	**5.97**	**7.80**	**10.02**	**6.07**	**7.80**	**10.02**	**12.14**
50/10 °C	T return primary	°C	-	-	-	-	27	27	27	26	24	24	24	23
	V̇ primary	**m³/h**	-	-	-	-	**7.17**	**8.95**	**11.64**	**14.45**	**6.78**	**8.62**	**11.52**	**13.16**
	Q max.	kW	-	-	-	-	230	290	380	480	280	360	485	560
	V̇ secondary	**m³/h**	-	-	-	-	**4.99**	**6.29**	**8.24**	**10.4**	**6.07**	**7.80**	**10.51**	**12.14**
50/15 °C	T return primary	°C	-	-	-	-	29	29	29	28	26	26	26	26
	V̇ primary	**m³/h**	-	-	-	-	**7.25**	**9.24**	**11.63**	**14.5**	**6.31**	**8.10**	**10.97**	**12.35**
	Q max.	kW	-	-	-	-	215	275	350	445	245	315	430	490
	V̇ secondary	**m³/h**	-	-	-	-	**5.33**	**6.81**	**8.67**	**11.02**	**6.07**	**7.80**	**10.65**	**12.14**
50/20 °C	T return primary	°C	-	-	-	-	30	30	30	30	30	29	29	29
	V̇ primary	**m³/h**	-	-	-	-	**5.03**	**6.59**	**9.02**	**11.96**	**6.00**	**7.6**	**10.35**	**11.6**
	Q max.	kW	-	-	-	-	145	190	260	345	210	270	370	420
	V̇ secondary	**m³/h**	-	-	-	-	**4.20**	**5.49**	**7.51**	**9.97**	**6.07**	**7.80**	**10.69**	**12.14**
45/5 °C	T return primary	°C	21	21	21	20	20	19	19	19	18	18	18	17
	V̇ primary	**m³/h**	**7.20**	**8.95**	**11.53**	**14.54**	**6.90**	**8.77**	**11.62**	**13.4**	**5.77**	**7.36**	**10.00**	**11.26**
	Q max.	kW	255	320	415	530	280	360	480	560	280	360	490	560
	V̇ secondary	**m³/h**	**5.53**	**6.94**	**9.00**	**11.50**	**6.07**	**7.80**	**10.4**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
45/10 °C	T return primary	°C	23	23	23	23	22	22	22	21	20	20	20	19
	V̇ primary	**m³/h**	**7.12**	**9.21**	**11.51**	**14.45**	**6.44**	**8.23**	**11.13**	**12.57**	**5.36**	**6.86**	**9.27**	**7.24**
	Q max.	kW	235	305	385	490	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**5.82**	**7.56**	**9.54**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
45/15 °C	T return primary	°C	25	25	25	25	25	24	24	24	23	22	22	22
	V̇ primary	**m³/h**	**6.10**	**8.03**	**10.67**	**13.49**	**6.01**	**7.63**	**10.38**	**11.63**	**4.88**	**6.23**	**8.51**	**9.53**
	Q max.	kW	190	250	335	420	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**5.49**	**7.23**	**9.68**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/20 °C	T return primary	°C	25	25	25	25	27	27	27	27	25	25	25	25
	V̇ primary	**m³/h**	**2.73**	**3.53**	**4.66**	**6.42**	**5.46**	**6.97**	**9.57**	**10.65**	**4.37**	**5.59**	**7.68**	**8.57**
	Q max.	kW	85	110	145	200	175	225	310	350	175	225	310	350
	V̇ secondary	**m³/h**	**2.95**	**3.82**	**5.03**	**6.94**	**6.07**	**7.80**	**10.75**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.

Performance data

TransTherm® aqua FS (7-60 to 7-90)

Domestic water secondary	TransTherm® aqua FS		Flow temperature heating water 65 °C (60)	65 °C (70)	65 °C (80)	65 °C (90)	70 °C (60)	70 °C (70)	70 °C (80)	70 °C (90)
60/5 °C	T return primary	°C	30	30	30	29	26	26	25	25
	V̇ primary	**m³/h**	**7.15**	**9.17**	**11.72**	**14.69**	**7.42**	**9.40**	**11.80**	**14.64**
	Q max.	kW	290	370	480	610	375	480	549	760
	V̇ secondary	**m³/h**	**4.57**	**5.83**	**7.57**	**9.62**	**5.91**	**7.57**	**9.44**	**11.98**
60/10 °C	T return primary	°C	30	30	30	30	28	28	28	27
	V̇ primary	**m³/h**	**5.45**	**6.94**	**9.41**	**12.88**	**7.23**	**9.29**	**12.23**	**15.42**
	Q max.	kW	220	280	380	520	358	453	569	717
	V̇ secondary	**m³/h**	**3.82**	**4.86**	**6.59**	**9.02**	**6.16**	**7.80**	**9.79**	**12.14**
60/15 °C	T return primary	°C	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**3.72**	**4.83**	**6.44**	**8.67**	**6.72**	**8.78**	**11.73**	**13.49**
	Q max.	kW	150	195	260	350	310	405	540	630
	V̇ secondary	**m³/h**	**2.89**	**3.76**	**5.01**	**6.74**	**5.97**	**7.80**	**10.4**	**12.14**
60/20 °C	T return primary	°C	30	30	30	30	30	30	30	30
	V̇ primary	**m³/h**	**2.11**	**2.85**	**3.72**	**4.95**	**4.34**	**5.64**	**7.37**	**9.97**
	Q max.	kW	85	115	150	200	200	260	340	460
	V̇ secondary	**m³/h**	**1.84**	**2.49**	**3.25**	**4.34**	**4.34**	**5.64**	**7.37**	**9.97**
55/5 °C	T return primary	°C	24	24	23	23	22	21	21	21
	V̇ primary	**m³/h**	**7.42**	**9.24**	**11.64**	**14.38**	**6.30**	**8.03**	**10.99**	**12.26**
	Q max.	kW	350	440	560	700	350	450	620	700
	V̇ secondary	**m³/h**	**6.07**	**7.63**	**9.71**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**
55/10 °C	T return primary	°C	26	26	26	25	24	24	24	23
	V̇ primary	**m³/h**	**7.06**	**8.96**	**11.66**	**13.66**	**5.96**	**7.6**	**10.25**	**11.6**
	Q max.	kW	315	405	530	630	315	405	550	630
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.21**	**12.14**	**6.07**	**7.80**	**10.6**	**12.14**
55/15 °C	T return primary	°C	29	28	28	27	27	26	26	26
	V̇ primary	**m³/h**	**6.67**	**8.48**	**11.48**	**12.91**	**5.62**	**7.16**	**9.70**	**10.96**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
55/20 °C	T return primary	°C	30	30	30	30	29	29	29	28
	V̇ primary	**m³/h**	**5.95**	**7.80**	**10.4**	**12.14**	**5.13**	**6.64**	**9.01**	**10.16**
	Q max.	kW	240	315	420	490	245	315	430	490
	V̇ secondary	**m³/h**	**5.95**	**7.80**	**10.4**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
50/5 °C	T return primary	°C	20	20	19	19	18	18	17	17
	V̇ primary	**m³/h**	**6.06**	**7.72**	**10.43**	**11.77**	**5.30**	**6.74**	**9.05**	**10.27**
	Q max.	kW	315	405	550	630	315	405	550	630
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.6**	**12.14**	**6.07**	**7.80**	**10.6**	**12.14**
50/10 °C	T return primary	°C	22	22	22	21	21	20	20	19
	V̇ primary	**m³/h**	**5.69**	**7.28**	**9.81**	**11.08**	**4.90**	**6.24**	**8.46**	**9.57**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
50/15 °C	T return primary	°C	25	25	24	24	23	23	22	22
	V̇ primary	**m³/h**	**5.30**	**6.74**	**9.14**	**10.29**	**4.52**	**5.76**	**7.82**	**8.83**
	Q max.	kW	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
50/20 °C	T return primary	°C	27	26	27	26	26	26	25	25
	V̇ primary	**m³/h**	**4.84**	**6.00**	**8.38**	**9.43**	**4.12**	**5.26**	**7.16**	**8.07**
	Q max.	kW	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/5 °C	T return primary	°C	16	16	16	15	15	14	14	13
	V̇ primary	**m³/h**	**4.99**	**6.34**	**8.58**	**9.69**	**4.39**	**5.59**	**7.59**	**8.58**
	Q max.	kW	280	360	490	560	280	360	490	560
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.62**	**12.14**	**6.07**	**7.80**	**10.62**	**12.14**
45/10 °C	T return primary	°C	19	18	18	18	17	17	17	16
	V̇ primary	**m³/h**	**4.57**	**5.85**	**7.92**	**8.94**	**4.02**	**5.13**	**6.98**	**7.90**
	Q max.	kW	245	315	430	490	245	315	430	490
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.65**	**12.14**	**6.07**	**7.80**	**10.65**	**12.14**
45/15 °C	T return primary	°C	21	21	21	20	20	20	20	19
	V̇ primary	**m³/h**	**4.15**	**5.30**	**7.24**	**8.15**	**3.64**	**4.66**	**6.37**	**7.18**
	Q max.	kW	210	270	370	420	210	270	370	420
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.69**	**12.14**	**6.07**	**7.80**	**10.69**	**12.14**
45/20 °C	T return primary	°C	24	24	24	24	23	23	23	23
	V̇ primary	**m³/h**	**3.71**	**4.75**	**6.51**	**7.31**	**3.24**	**4.15**	**5.71**	**6.42**
	Q max.	kW	175	225	310	350	175	225	310	350
	V̇ secondary	**m³/h**	**6.07**	**7.80**	**10.75**	**12.14**	**6.07**	**7.80**	**10.75**	**12.14**

T return primary	°C	Return temperature primary
V̇ primary	**m³/h**	Flow rate primary
Q max.	kW	Output
V̇ secondary	**m³/h**	Flow rate secondary

The specified technical data relate to the full load of the module in each case.


Performance data

TransTherm® aqua FS


Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	DHW calorifier output TransTherm® aqua FS	TransTherm® aqua FS	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 2 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	V̇s at DHW 60 °C	V̇s at DHW 60 °C	V̇s at DHW 60 °C		V̇s at DHW 60 °C	V̇s at DHW 60 °C	V̇s at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
1	5820	0.17	1.00	0.17	10.01	0.60	35	0.24	14.3	0.86	50	(7-10)	0.13	0.16	(200)	23	15	8
2	11640	0.33	0.680	0.23	13.61	0.82	47	0.24	14.3	0.86	50	(7-10)	0.17	0.22	(200)	31	21	10
3	17460	0.50	0.544	0.27	16.33	0.98	57	0.43	25.8	1.55	90	(7-16)	0.20	0.27	(200)	37	25	12
4	23280	0.67	0.466	0.31	18.66	1.12	65	0.43	25.8	1.55	90	(7-16)	0.23	0.30	(200)	42	28	14
5	29100	0.83	0.415	0.35	20.77	1.25	72	0.43	25.8	1.55	90	(7-16)	0.26	0.34	(200)	47	31	16
6	34920	1.00	0.377	0.38	22.64	1.36	79	0.43	25.8	1.55	90	(7-16)	0.28	0.37	(200)	51	34	17
7	40740	1.17	0.349	0.41	24.45	1.47	85	0.43	25.8	1.55	90	(7-16)	0.31	0.40	(300)	55	37	18
8	46560	1.33	0.349	0.47	27.94	1.68	97	0.62	37.3	2.24	130	(7-20)	0.35	0.45	(300)	63	42	21
9	52380	1.50	0.308	0.46	27.74	1.66	97	0.62	37.3	2.24	130	(7-20)	0.35	0.45	(300)	63	42	21
10	58200	1.67	0.292	0.49	29.23	1.75	102	0.62	37.3	2.24	130	(7-20)	0.37	0.47	(300)	66	44	22
11	64020	1.83	0.279	0.51	30.72	1.84	107	0.62	37.3	2.24	130	(7-20)	0.38	0.50	(300)	70	46	23
12	69840	2.00	0.268	0.54	32.19	1.93	112	0.62	37.3	2.24	130	(7-20)	0.40	0.52	(500)	73	49	24
13	75660	2.17	0.258	0.56	33.57	2.01	117	0.62	37.3	2.24	130	(7-20)	0.42	0.55	(500)	76	51	25
14	81480	2.34	0.249	0.58	34.89	2.09	122	0.62	37.3	2.24	130	(7-20)	0.44	0.57	(500)	79	53	26
15	87300	2.50	0.242	0.61	36.33	2.18	127	0.62	37.3	2.24	130	(7-20)	0.45	0.59	(500)	82	55	27
16	93120	2.67	0.235	0.63	37.63	2.26	131	0.62	37.3	2.24	130	(7-20)	0.47	0.61	(500)	85	57	28
17	98940	2.84	0.228	0.65	38.79	2.33	135	0.84	50.2	3.01	175	(7-30)	0.49	0.63	(500)	88	59	29
18	104760	3.00	0.223	0.67	40.17	2.41	140	0.84	50.2	3.01	175	(7-30)	0.50	0.65	(500)	91	61	30
19	110580	3.17	0.217	0.69	41.27	2.48	144	0.84	50.2	3.01	175	(7-30)	0.52	0.67	(500)	94	62	31
20	116400	3.34	0.212	0.71	42.44	2.55	148	0.84	50.2	3.01	175	(7-30)	0.53	0.69	(500)	96	64	32
21	122220	3.50	0.208	0.73	43.72	2.62	153	0.84	50.2	3.01	175	(7-30)	0.55	0.71	(500)	99	66	33
22	128040	3.67	0.204	0.75	44.92	2.70	157	0.84	50.2	3.01	175	(7-30)	0.56	0.73	(500)	102	68	34
23	133860	3.84	0.200	0.77	46.04	2.76	161	0.84	50.2	3.01	175	(7-30)	0.58	0.75	(500)	104	70	35
24	139680	4.00	0.196	0.78	47.08	2.82	164	0.84	50.2	3.01	175	(7-30)	0.59	0.77	(500)	107	71	36
25	145500	4.17	0.193	0.80	48.29	2.90	168	0.84	50.2	3.01	175	(7-30)	0.60	0.78	(500)	110	73	37
26	151320	4.34	0.190	0.82	49.44	2.97	173	0.84	50.2	3.01	175	(7-30)	0.62	0.80	(500)	112	75	37
27	157140	4.50	0.187	0.84	50.53	3.03	176	0.84	50.2	3.01	175	(7-30)	0.63	0.82	(500)	115	76	38
28	162960	4.67	0.184	0.86	51.56	3.09	180	0.84	50.2	3.01	175	(7-30)	0.64	0.84	(500)	117	78	39
29	168780	4.84	0.181	0.88	52.54	3.15	183	1.05	63.1	3.78	220	(7-40)	0.66	0.85	(800)	119	79	40
30	174600	5.00	0.179	0.90	53.75	3.22	188	1.05	63.1	3.78	220	(7-40)	0.67	0.87	(800)	122	81	41
31	180420	5.17	0.176	0.91	54.61	3.28	191	1.05	63.1	3.78	220	(7-40)	0.68	0.89	(800)	124	83	41
32	186240	5.34	0.174	0.93	55.73	3.34	194	1.05	63.1	3.78	220	(7-40)	0.70	0.91	(800)	126	84	42
33	192060	5.50	0.172	0.95	56.81	3.41	198	1.05	63.1	3.78	220	(7-40)	0.71	0.92	(800)	129	86	43
34	197880	5.67	0.170	0.96	57.85	3.47	202	1.05	63.1	3.78	220	(7-40)	0.72	0.94	(800)	131	87	44
35	203700	5.84	0.168	0.98	58.85	3.53	205	1.05	63.1	3.78	220	(7-40)	0.74	0.96	(800)	133	89	44
36	209520	6.01	0.166	1.00	59.81	3.59	209	1.05	63.1	3.78	220	(7-40)	0.75	0.97	(800)	136	90	45
37	215340	6.17	0.164	1.01	60.73	3.64	212	1.05	63.1	3.78	220	(7-40)	0.76	0.99	(800)	138	92	46
38	221160	6.34	0.163	1.03	61.99	3.72	216	1.05	63.1	3.78	220	(7-40)	0.78	1.01	(800)	141	94	47
39	226980	6.51	0.161	1.05	62.84	3.77	219	1.05	63.1	3.78	220	(7-40)	0.79	1.02	(800)	143	95	48
40	232800	6.67	0.159	1.06	63.65	3.82	222	1.05	63.1	3.78	220	(7-40)	0.80	1.03	(800)	144	96	48
41	238620	6.84	0.158	1.08	64.84	3.89	226	1.31	78.8	4.73	275	(7-50)	0.81	1.05	(1000)	147	98	49
42	244440	7.01	0.156	1.09	65.58	3.93	229	1.31	78.8	4.73	275	(7-50)	0.82	1.07	(1000)	149	99	50
43	250260	7.17	0.155	1.11	66.71	4.00	233	1.31	78.8	4.73	275	(7-50)	0.83	1.08	(1000)	151	101	50
44	256080	7.34	0.154	1.13	67.82	4.07	237	1.31	78.8	4.73	275	(7-50)	0.85	1.10	(1000)	154	103	51
45	261900	7.51	0.152	1.14	68.46	4.11	239	1.31	78.8	4.73	275	(7-50)	0.86	1.11	(1000)	155	104	52
46	267720	7.67	0.151	1.16	69.52	4.17	243	1.31	78.8	4.73	275	(7-50)	0.87	1.13	(1000)	158	105	53
47	273540	7.84	0.150	1.18	70.56	4.23	246	1.31	78.8	4.73	275	(7-50)	0.88	1.15	(1000)	160	107	53
48	279360	8.01	0.149	1.19	71.58	4.29	250	1.31	78.8	4.73	275	(7-50)	0.89	1.16	(1000)	162	108	54
49	285180	8.17	0.148	1.21	72.58	4.35	253	1.31	78.8	4.73	275	(7-50)	0.91	1.18	(1000)	165	110	55
50	291000	8.34	0.146	1.22	73.06	4.38	255	1.31	78.8	4.73	275	(7-50)	0.91	1.19	(1000)	166	110	55
51	296820	8.51	0.145	1.23	74.01	4.44	258	1.31	78.8	4.73	275	(7-50)	0.93	1.20	(1000)	168	112	56
52	302640	8.67	0.144	1.25	74.94	4.50	261	1.31	78.8	4.73	275	(7-50)	0.94	1.22	(1000)	170	113	57
53	308460	8.84	0.143	1.26	75.86	4.55	265	1.31	78.8	4.73	275	(7-50)	0.95	1.23	(1000)	172	115	57
54	314280	9.01	0.142	1.28	76.75	4.60	268	1.31	78.8	4.73	275	(7-50)	0.96	1.25	(1000)	174	116	58
55	320100	9.17	0.141	1.29	77.62	4.66	271	1.31	78.8	4.73	275	(7-50)	0.97	1.26	(1000)	176	117	59

Residential units standard apartment according to DIN 4708	Peak heat demand standard apartment according to DIN 4708 with preparation 10 min	Sum flow rate domestic hot water calculation flow rate according to DIN 4708	Simultaneity factor according to DIN 4708	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak flow rate (DHW)	Peak output (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	Peak flow rate TransTherm® aqua FS (DHW)	DHW calorifier output TransTherm® aqua FS	TransTherm® aqua FS	Required heating water volume at 70/30 °C (40 K)	Required heating water buffer storage tank volume at 70/30 °C (40 K)	Buffer storage tank 2 EnerVal	Required recharging capacity	Required recharging capacity	Required recharging capacity
N	Preparation	∑ VR at DHW 60 °C	g	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C		$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	$\dot{V}s$ at DHW 60 °C	Q at HT 70/30 °C DHW 10/60 °C	Type			Type	Time: 20 min 70/30 °C (40 K)	Time: 30 min 70/30 °C (40 K)	Time: 60 min 70/30 °C (40 K)
	[Wh]	[l/s]		[l/s]	[l/min]	[m³/h]	[kW]	[l/s]	[l/min]	[m³/h]	[kW]		[m³]	[m³]		[kW]	[kW]	[kW]
56	325920	9.34	0.140	1.31	78.47	4.71	274	1.31	78.8	4.73	275	(7-50)	0.98	1.28	(1000)	178	119	59
57	331740	9.51	0.140	1.33	79.87	4.79	279	1.31	78.8	4.73	275	(7-50)	1.00	1.30	(1000)	181	121	60
58	337560	9.67	0.139	1.34	80.69	4.84	282	1.71	102.6	6.16	358	(7-60)	1.01	1.31	(1000)	183	122	61
59	343380	9.84	0.138	1.36	81.49	4.89	284	1.71	102.6	6.16	358	(7-60)	1.02	1.32	(1000)	185	123	62
60	349200	10.01	0.137	1.37	82.27	4.94	287	1.71	102.6	6.16	358	(7-60)	1.03	1.34	(1000)	187	124	62
61	355020	10.18	0.136	1.38	83.03	4.98	290	1.71	102.6	6.16	358	(7-60)	1.04	1.35	(1000)	188	126	63
62	360840	10.34	0.135	1.40	83.77	5.03	292	1.71	102.6	6.16	358	(7-60)	1.05	1.36	(1000)	190	127	63
63	366660	10.51	0.135	1.42	85.12	5.11	297	1.71	102.6	6.16	358	(7-60)	1.06	1.38	(1000)	193	129	64
64	372480	10.68	0.134	1.43	85.83	5.15	299	1.71	102.6	6.16	358	(7-60)	1.07	1.40	(1000)	195	130	65
65	378300	10.84	0.133	1.44	86.52	5.19	302	1.71	102.6	6.16	358	(7-60)	1.08	1.41	(1000)	196	131	65
66	384120	11.01	0.132	1.45	87.19	5.23	304	1.71	102.6	6.16	358	(7-60)	1.09	1.42	(1000)	198	132	66
67	389940	11.18	0.132	1.48	88.52	5.31	309	1.71	102.6	6.16	358	(7-60)	1.11	1.44	(1000)	201	134	67
68	395760	11.34	0.131	1.49	89.16	5.35	311	1.71	102.6	6.16	358	(7-60)	1.11	1.45	(1000)	202	135	67
69	401580	11.51	0.130	1.50	89.78	5.39	313	1.71	102.6	6.16	358	(7-60)	1.12	1.46	(1000)	204	136	68
70	407400	11.68	0.130	1.52	91.08	5.46	318	1.71	102.6	6.16	358	(7-60)	1.14	1.48	(1000)	207	138	69
71	413220	11.84	0.129	1.53	91.67	5.50	320	1.71	102.6	6.16	358	(7-60)	1.15	1.49	(1000)	208	139	69
72	419040	12.01	0.128	1.54	92.24	5.53	322	1.71	102.6	6.16	358	(7-60)	1.15	1.50	(1500)	209	139	70
73	424860	12.18	0.128	1.56	93.52	5.61	326	1.71	102.6	6.16	358	(7-60)	1.17	1.52	(1500)	212	141	71
74	430680	12.34	0.127	1.57	94.06	5.64	328	1.71	102.6	6.16	358	(7-60)	1.18	1.53	(1500)	213	142	71
75	436500	12.51	0.127	1.59	95.33	5.72	333	1.71	102.6	6.16	358	(7-60)	1.19	1.55	(1500)	216	144	72
76	442320	12.68	0.126	1.60	95.84	5.75	334	1.71	102.6	6.16	358	(7-60)	1.20	1.56	(1500)	217	145	72
77	448140	12.84	0.126	1.62	97.10	5.83	339	1.71	102.6	6.16	358	(7-60)	1.21	1.58	(1500)	220	147	73
78	453960	13.01	0.125	1.63	97.58	5.86	340	1.71	102.6	6.16	358	(7-60)	1.22	1.59	(1500)	221	148	74
79	459780	13.18	0.124	1.63	98.04	5.88	342	1.71	102.6	6.16	358	(7-60)	1.23	1.59	(1500)	222	148	74
80	465600	13.34	0.124	1.65	99.29	5.96	346	1.71	102.6	6.16	358	(7-60)	1.24	1.61	(1500)	225	150	75
81	471420	13.51	0.123	1.66	99.72	5.98	348	1.71	102.6	6.16	358	(7-60)	1.25	1.62	(1500)	226	151	75
82	477240	13.68	0.123	1.68	100.95	6.06	352	1.71	102.6	6.16	358	(7-60)	1.26	1.64	(1500)	229	153	76
83	483060	13.85	0.122	1.69	101.35	6.08	354	1.71	102.6	6.16	358	(7-60)	1.27	1.65	(1500)	230	153	77
84	488880	14.01	0.122	1.71	102.57	6.15	358	1.71	102.6	6.16	358	(7-60)	1.28	1.67	(1500)	233	155	78
85	494700	14.18	0.121	1.72	102.94	6.18	359	1.71	102.6	6.16	358	(7-60)	1.29	1.67	(1500)	233	156	78
86	500520	14.35	0.121	1.74	104.15	6.25	363	2.16	129.9	7.79	453	(7-70)	1.30	1.69	(1500)	236	157	79
87	506340	14.51	0.120	1.74	104.49	6.27	365	2.16	129.9	7.79	453	(7-70)	1.31	1.70	(1500)	237	158	79
88	512160	14.68	0.120	1.76	105.69	6.34	369	2.16	129.9	7.79	453	(7-70)	1.32	1.72	(1500)	240	160	80
89	517980	14.85	0.120	1.78	106.89	6.41	373	2.16	129.9	7.79	453	(7-70)	1.34	1.74	(1500)	242	162	81
90	523800	15.01	0.119	1.79	107.19	6.43	374	2.16	129.9	7.79	453	(7-70)	1.34	1.74	(1500)	243	162	81
91	529620	15.18	0.119	1.81	108.38	6.50	378	2.16	129.9	7.79	453	(7-70)	1.36	1.76	(1500)	246	164	82
92	535440	15.35	0.118	1.81	108.65	6.52	379	2.16	129.9	7.79	453	(7-70)	1.36	1.77	(1500)	246	164	82
93	541260	15.51	0.118	1.83	109.83	6.59	383	2.16	129.9	7.79	453	(7-70)	1.37	1.79	(1500)	249	166	83
94	547080	15.68	0.117	1.83	110.07	6.60	384	2.16	129.9	7.79	453	(7-70)	1.38	1.79	(1500)	250	166	83
95	552900	15.85	0.117	1.85	111.25	6.67	388	2.16	129.9	7.79	453	(7-70)	1.39	1.81	(2000)	252	168	84
96	558720	16.01	0.117	1.87	112.42	6.74	392	2.16	129.9	7.79	453	(7-70)	1.41	1.83	(2000)	255	170	85
97	564540	16.18	0.116	1.88	112.62	6.76	393	2.16	129.9	7.79	453	(7-70)	1.41	1.83	(2000)	255	170	85
98	570360	16.35	0.116	1.90	113.78	6.83	397	2.16	129.9	7.79	453	(7-70)	1.42	1.85	(2000)	258	172	86
99	576180	16.51	0.116	1.92	114.94	6.90	401	2.16	129.9	7.79	453	(7-70)	1.44	1.87	(2000)	261	174	87
100	582000	16.68	0.115	1.92	115.10	6.91	402	2.16	129.9	7.79	453	(7-70)	1.44	1.87	(2000)	261	174	87


Residual overpressure / V domestic hot water circulation > draw-off standby




Residual overpressure / domestic hot water circulation > with draw-off Vs



Residual overpressure / V domestic hot water circulation > draw-off standby




Residual overpressure / domestic hot water circulation > with draw-off Vs




All values with open line balancing valve
Dotted lines = values above nominal performance range


ΔP / V max / cold water > domestic hot water



Residual overpressure / charging circuit flow HT




Residual overpressure / charging circuit flow LT



All values with open line balancing valve
Dotted lines = values above nominal performance range

Fresh water module TransTherm® aqua FS (7-10 to 7-50)

(Dimensions in mm)




		(7-10)	(7-16)	(7-20) (7-30)	(7-40)	(7-50)
1	Charging circuit FL	DN 20, Rp ¾″	DN 25, Rp 1″	DN 32, Rp 1¼″	DN 32, Rp 1¼″	DN 40, Rp 1½″
2	Charging circuit HT RT	DN 20, Rp ¾″	DN 25, Rp 1″	DN 32, Rp 1¼″	DN 32, Rp 1¼″	DN 40, Rp 1½″
3	Charging circuit LT RT	DN 20, Rp ¾″	DN 25, Rp 1″	DN 32, Rp 1¼″	DN 32, Rp 1¼″	DN 40, Rp 1½″
4	Domestic hot water	DN 20, Rp ¾″	DN 20, Rp ¾″	DN 25, Rp 1″	DN 32, Rp 1¼″	DN 32, Rp 1¼″
5	Domestic hot water circulation	DN 20, Rp ¾″	DN 20, Rp ¾″	DN 20, Rp ¾″	DN 25, Rp 1″	DN 25, Rp 1″
6	Cold water	DN 20, Rp ¾″	DN 20, Rp ¾″	DN 25, Rp 1″	DN 32, Rp 1¼″	DN 32, Rp 1¼″

Rp = Internal thread

Fresh water module TransTherm® aqua FS (7-60 to 7-90)


(Dimensions in mm)



		(7-60) (7-70)		(7-80) (7-90)	
1	Charging circuit FL	DN 50, Rp 2″	(IT)	DN 65, Rp 2½″	(IT)
2	Charging circuit HT RT	DN 50, Rp 2″	(IT)	DN 65, Rp 2½″	(IT)
3	Charging circuit LT RT	DN 50, Rp 2″	(IT)	DN 65, Rp 2½″	(IT)
4	Domestic hot water	DN 40, Rp 1½″	(IT)	DN 50, Rp 2″	(IT)
5	Domestic hot water circulation	DN 32, Rp 1¼″	(IT)	DN 40, Rp 1½″	(IT)
6	Cold water	DN 40, Rp 1½″	(IT)	DN 50, Rp 2″	(IT)

Water heating

TransTherm® aqua FS



TTE-FW	Basic module district heating/fresh water
TW	Temperature monitor (if required)
VFW	Flow sensor DHW
RLF4	Return sensor DHW
RLF5	Return sensor DHW
RLF2	Return sensor domestic cold water
RLFZ	Return sensor domestic hot water circulation
SF1	Calorifier sensor
SF1.1	Calorifier sensor (heat generator)
SF2.1	Calorifier sensor (heat generator)
RLFZ	Circulation sensor
FVT	Flow rate sensor
VFP	Flow sensor primary
RLF3	Return sensor HT primary
RLF	Return sensor LT primary
SLP1	Calorifier charging pump
YFW	Three-way valve with drive (mixing valve)
YK1	Three-way valve with drive (distributor valve)
ZKP	Circulating pump

Option

BM	TopTronic® E control module

Notice
A safety valve (6 bar) must be installed in the cold water line.
The fresh water module is already protected with a safety valve (10 bar).

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval TransTherm® aqua

Fresh water module
TransTherm® aqua FT/FTC



Hoval | Responsibility for energy and environment

Table of contents

- Description 5
- Part numbers 6
- Technical data 8
- Dimensions 10

Fresh water module TransTherm® aqua FT/FTC

Fresh water module for hygienic water heating in the continuous flow principle for single- and two-family homes with:

- high-output, soldered stainless steel plate heat exchanger
  (heat exchanger solder – FT: copper, FTC: stainless steel)
- integrated heating water charging pump
- flow switch for heating water charging pump
- cut-off armatures (optional)
- thermostatic hot water temperature control
- stainless steel piping for quick assembly
- wall attachment
- ready-to-connect
- casing made of sheet steel painted in red or white (optional)
- base plate

The quick-acting hot water temperature sensor accelerates the closing function of the regulating valve and protects the heat exchanger against overheating and scaling.

Output	65 kW (27 l/min) 57 kW (23 l/min)




Circulation module

for TransTherm® aqua FT (65), FTC (57)

- Pre-assembled, for installation on-site, incl. cable and plug
- Recirculation pump with integrated timer and circulation temperature control, as well as with pre-mounted safety valve (option)

Minimum requirements on water quality for fresh water modules see engineering hot water

Fresh water module



TransTherm® aqua FT/FTC

Fresh water module for hygienic water heating with thermostatic control of the hot water temperature by means of quick-acting water temperature controller

Fresh water module TransTherm® aqua	Output kW	Part No.
FT (65)	65	6040 453
FTC (57)	57	6048 769

Accessories

Ball valve set DVGW
for TransTherm® aqua FT/FTC — 6040 456



Casing
for TransTherm® aqua FT/FTC
White colour — 6044 175



Casing
for TransTherm® aqua FT/FTC
Red colour — 6045 319



Circulation heat exchanger lance R 1″
is screwed into the buffer storage tank and integrated into the circulation line.
Material: Copper, tinned inside
Transmission power approx. 1 kW at 60 °C
Hot water temperature in the buffer storage tank without mixing through the storage tank temperature.
Circulation connections R ½″
Installation length 660 mm — 2038 434

Notice
Circulating pump, safety valve, shut-off valves and non-return flap/valve are missing and must be installed on site.



Circulation module
for TransTherm® aqua FT/FTC
preassembled, for subsequent installation on the fresh water module
comprising:
Circulation pump with timer switch
Integrated control of the temperature
Non-return flap, ball valve Rp ¾″
cable and plug,
safety valve 10 bar — 6040 455

Services



Services and associated scope of services
see separate catalogue “Hoval Services”


Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.

Part No.


TransTherm® aqua FT/FTC

Type			FT (65)	FTC (57)
• Output		kW	65	57
• Connection dimension	Heating flow/return	Inches	G ¾" (ext. thread)	
	Cold/hot water	Inches	G ¾" (ext. thread)	
• Dimensions (W x H x D)	Without casing	mm	440 x 655 x 140	
	With casing	mm	450 x 715 x 150	
	With circulation	mm	440/450 x 940 x 140/150	
• Weight (incl. packaging)		kg	20	23
• Controller protection class			IP54	IP54
• Supply voltage		V	230	
• Plate heat exchanger stainless steel			copper-soldered	soldered stainless steel
Heat exchanger domestic water side				
• Min. static cold water pressure		bar	0.5	
• Max. operating pressure		bar	10	
• Max. operating temperature		°C	70	
Design temperatures domestic water side				
• Cold water		°C	10	
• Hot water		°C	45	
• Continuous output		l/min	27	23
Heat exchanger heating side				
• Max. operating pressure		bar	10	
• Max. permissible operating temperature		°C	100	
Design temperatures heating side				
• Heating flow		°C	55	
• Heating return		°C	20	
• Flow resistance (at V = 1.5 m³/h)		kPa	34	

TransTherm® aqua FT (65)
Hot water temperature 45 °C: Tapping capacity – Output – Pressure drops




TransTherm® aqua FTC (57)
Hot water temperature 45 °C: Tapping capacity – Output – Pressure drops




Construction TransTherm® aqua FT/FTC

Buffer storage tank | **Fresh water module with circulation module (accessories)**



Buffer storage tank | **Fresh water module with heat exchanger lance**



1 Stainless steel plate heat exchanger
2 Hot water sensor, quick-acting
3 Thermostatic control
4 Heating water charging pump
5 Circulation incl. safety valve (optional)
6 Circulation (optional)
7 Flow switch
8 Non-return valve (optional)
9 Cut-off ball valve – flat-sealing (optional)
10 Heat exchanger lance

* Safety valve also necessary with recirculation pump on site

Installation of strainer on site

Functional description Hoval TransTherm® aqua FT/FTC

The Hoval fresh water module TransTherm® aqua FT/FTC, with all piping pre-installed and ready-to-connect, consists of a soldered stainless-steel plate heat exchanger (heat exchanger solder – FT: copper, FTC: stainless steel), an integrated heating water charging pump, a thermostatic controller with tapping detection and hot water temperature control.

When a hot water tapping point is opened, the heating water charging pump is switched on via the flow detection device and the heating water transported from the buffer storage tank to the heat exchanger.


In the large-dimension plate heat exchanger, the hot water is heated in the counterflow principle, directly before removal and in a continuous flow process, from the cold water temperature to the desired DHW temperature.

The quick-acting water temperature controller ensures maintenance of the desired hot water temperature, providing a constant tapping temperature and optimum maintenance of stratification in the buffer storage tank.


An optional recirculation pump with thermostat ensures that the circulating water maintains the desired temperature.


TransTherm® aqua FT/FTC
(Dimensions in mm)

Casing



Base plate





Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval EnerVal (100-2000)

Buffer storage tank
EnerVal (100-2000)






Table of contents

- Description 5
- Part numbers 6
- Technical data 8
- Dimensions 9

Buffer storage tank EnerVal (100-300)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Thermal insulation made of polyurethane hard foam, foamed on the storage
- Removable foil jacket in red
- (100): 2 connection sleeves Rp 1 ½″, 2 connection nozzles R 1″
  (200): 5 connection sleeves Rp 1 ½″
  (300): 8 connection sleeves Rp 1 ½″
- 1 sleeve Rp ½″ with thermometer and immersion sleeve mounted
- (200,300): 2 sensor channels

Delivery
- Buffer storage tank with foil jacket completely installed and packed

Buffer storage tank EnerVal (500)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Thermal insulation made of polyurethane hard foam, foamed on the calorifier
- Removable foil jacket in red
- 8 connection sleeves Rp 1 ½″
- 1 sleeve Rp 1½″ for screw-in electrical heating inset
- 1 sleeve Rp ½″ with thermometer and immersion sleeve mounted
- 2 sensor channels

Delivery
- Buffer storage tank with foil jacket completely installed and packed

Buffer storage tank EnerVal (800-2000)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Thermal insulation made of polyester fleece with foil jacket, colour red (removable)
- 10 connection sleeves G 2″ (IT)
- 2 sleeves G 1½″ (IT) for screw-in electric heating element
- 3 sleeves G ½″ (IT) for sensor/thermometer
- Terminal strips for contact sensors
- 1 sleeve G 1″ (IT) for circulation lance only with EnerVal (800,1000)
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed
- 13 insulated cover caps made of EPP hard foam, 2-piece (can be broken out)

Delivery
- Buffer storage tank with thermal insulation completely installed and packed
- Insulated cover caps already installed (can be removed and broken out)




Range

EnerVal type		Content l	Operating pressure bar
(100)	A	117	3
(200)	B	222	3
(300)	B	283	3
(500)	B	473	3
(800)		785	3
(1000)		918	3
(1500)		1425	3
(2000)		2019	3

A⁺ → F

Buffer storage tank



EnerVal (100-2000)

Steel container raw on the inside,
EnerVal (100-500) completely installed,
EnerVal (800-2000) thermal insulation completely installed

EnerVal type	Content l	Part No.
(100)	117	7016 826
(200)	222	7013 681
(300)	283	7015 975
(500)	473	7015 976
(800)	785	7019 129
(1000)	918	7019 130
(1500)	1425	7019 131
(2000)	2019	7019 132

Energy efficiency class
see “Description”

Electric heating elements
see chapter “Electric heating elements”

Accessories



Protective tube immersion 6061 045
sleeve set 200 ½″, 4 x
For installation of maximum 4 sensors
Nickel-plated brass
Installation length = 187 mm
Outer Ø: 18 mm, inner Ø: 16 mm
including 3 segment springs 90°,
1 Omega clamping spring



Protective tube immersion sleeve SB280 ½″ 2018 837
Nickel-plated brass
Installation length = 280 mm
Outer Ø: 9 mm, inner Ø: 7 mm



Thermometer kit 6052 107
for EnerVal (800-6000)
Thermometer 0 ... 120 °C with
chromium plated edge and Hoval logo
Stem length: 80 mm, stem Ø: 9 (13) mm,
External Ø: 80 mm
incl. immersion sleeve ½″ nickel-plated
brass, installation length: 200 mm,
external Ø: 16 mm, internal Ø: 15 mm
and clamping spring



Inject lance 6051 645
for EnerVal (200-500)
For horizontal installation in the
buffer storage tank.
For the decrease of the turbulence of
the attached water.
Screw-in depth: 450 mm
Connection: Rp 1½″

Services



Services and associated scope of services
see separate catalogue “Hoval Services”


Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.

Part No.


EnerVal (100-2000)

Type		(100)	(200)	(300)	(500)	(800)	(1000)	(1500)	(2000)
• Volume	litres	117	222	283	473	785	918	1425	2019
• Max. operating/test pressure	bar	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
• Min. operating temperature	°C	5	5	5	5	20	20	20	20
• Max. operating temperature	°C	95	95	95	95	95	95	95	95
• Thermal insulation PU rigid foam, foam-lined	mm	50	50	75	75	-	-	-	-
• Thermal insulation polyester fleece	mm	-	-	-	-	150	150	150	150
• Thermal insulation λ	W/mK	0.027	0.027	0.027	0.027	0.04	0.04	0.04	0.04
• Fire protection class		B2	B2	B2	B2	B2	B2	B2	B2
• Heat loss at 65 °C	W	35	53	51	72	119	130	153	185
• Transport weight	kg	41	59	79	111	150	160	265	385
• U value	W/m^2K	0.359	0.359	0.279	0.296	0.315	0.308	0.299	0.302
• Dimensions		see table of dimensions							

Outflow velocity flow lance DN 40
EnerVal (200-500)




Velocity in the connection nozzles and inflow velocity with flow deflection
EnerVal (800-2000)




1 = flow rate
2 = velocity in the connection nozzles
3 = inflow velocity with flow deflection in the EnerVal


Example of inlet velocity distribution by flow diversions EnerVal (800-2000)



EnerVal (100)
(Dimensions in mm)



EnerVal (200-500)



			Type (100)	Type (200-500)
1	Heating connection	return discharge	R 1″ (ET)	G 1½″ (IT)
2	Heating connection	flow discharge	R 1″ (ET)	G 1½″ (IT)
3	Heat generator connection	flow/return	G 1½″ (IT)	G 1½″ (IT)
4	Heat generator connection	flow/return 3 x, only with EnerVal (300,500)		G 1½″ (IT)
7	Sleeve with mounted immersion sleeve and thermometer			
8	Sensor channel inner Ø 11 mm			
9	Removable cap (60 mm) for positioning the sensor in the sensor channel			
12	Connection for screw-in electric heating element			G 1½″ (IT)
	(Positioning depends on the system, see hydraulic schematics of the heat generator)			
12a	Additional connection for screw-in electric heating element, only for EnerVal (500)			G 1½″ (IT)


1 + 2 For EnerVal (100), suitable for direct installation of an armature group LG/HA 25-2 and 32-2


EnerVal type	D	d	H	a	b	c	e	f	g	Tilting dimension
(100)	600	480	910	152	337	567	125	-	230	985
(200)	600	480	1440	152	300	720	-	1140	860	1560
(300)	650	480	1780	152	300	890	-	1479	1285	1895
(500)	750	597	1921	127	220	946	1400	1670	1360	2025


Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

EnerVal (800-2000)

(Dimensions in mm)







1	Heating connection	return discharge (inflow restrictor)	Rp 2″	(IT)
2	Heating connection	flow discharge (single-layer elbow pipe)	Rp 2″	(IT)
3	Heat generator connection	flow top (inflow restrictor)	Rp 2″	(IT)
4	Heat generator connection	return top (inflow restrictor)	Rp 2″	(IT)
5	Heat generator connection	flow bottom (inflow restrictor)	Rp 2″	(IT)
6	Heat generator connection	return bottom (inflow restrictor)	Rp 2″	(IT)
7	Sleeve for immersion sleeve, thermostat or thermometer		Rp ½″	(IT)
8	Sensor terminal strip		2 x	
9	Removable cap (100 mm) for positioning the sensor			
10	Possible air vent		Rp 1″	(IT)
11	Separating plate			
11a	Holes in the separating plate		12 x	
12	Connection for electric heating element		Rp 1½″	(IT)
14	Connection for circulation lance, **attention:** only for type (800,1000)		Rp 1″	(IT)

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

EnerVal type	D	d	H	a	b	c	e	f	g	i	k	m	n	p	q	r	s	Tilting dimension
(800)	1090	790	1907	183	315	410	496	840	1011	1269	1402	1537	1672	251	800	50	500	1945
(1000)	1090	790	2197	183	369	468	569	970	1171	1472	1596	1759	1942	370	800	100	500	2230
(1500)	1300	1000	2135	220	368	451	549	941	1137	1431	-	1699	1839	339	800	100	500	2179
(2000)	1500	1200	2145	220	382	430	529	928	1127	1425	-	1672	1839	350	800	80	500	2210

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval EnerVal G

Buffer storage tank
EnerVal G (800-6000)




Table of contents

- Description 5
- Part numbers 6
- Technical data 7
- Dimensions 9

Buffer storage tank EnerVal G (800,1000)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Thermal insulation made of polyester fibre with foil jacket, colour red (removable)
- 8 connection flanges DN 65 (PN 6)
- 2 connection flanges DN 80 (PN 6)
- 2 flanges outside Ø 180 mm for flange-mounted electric heating element
- 3 sleeves G ½″ (IT) for sensor/thermometer
- Terminal strips for contact sensors
- 1 sleeve G 1″ (IT) for circulation lance
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed
- 12 insulated flange hoods
- 1 insulated cover cap made of EPP hard foam, 2-piece (can be broken out)

Delivery
- Buffer storage tank mounted and packed with thermal insulation (can be removed for installation)
- Insulated flange hoods and cover cap already mounted (removable)



Range

EnerVal G type	Content l	Operating pressure bar
(800)	783	6
(1000)	925	6
(1500)	1395	6
(2500)	2360	6
(4000)	3907	6
(6000)	5815	6

Buffer storage tank EnerVal G (1500,2500)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Thermal insulation made of polyester fibre with foil jacket, colour red (removable)
- 8 connection flanges DN 80 (PN 6)
- 2 connection flanges DN 100 (PN 6)
- 2 flanges outside Ø 257 mm for flange-mounted electric heating element
- 3 sleeves G ½″ (IT) for sensor/thermometer
- Terminal strips for contact sensors
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed
- 12 insulated flange hoods


Delivery
- Buffer storage tank (1500) mounted and packed with thermal insulation (can be removed for installation)
- Buffer storage tank (2500) separate thermal insulation
- Insulated flange hoods already mounted (removable)

Buffer storage tank EnerVal G (4000,6000)

- Steel buffer storage tank for the hydraulic integration of energy generators
- Without thermal insulation (on-site)
- 8 connection flanges DN 100 (PN 6)
- 2 connection flanges DN 125 (PN 6)
- 2 flanges outside Ø 257 mm for flange-mounted electric heating element
- 3 sleeves G ½″ (IT) for sensor/thermometer
- Terminal strips for contact sensors
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed

Delivery
- Buffer storage tank raw packed
- Thermal insulation to be provided on site

Buffer storage tank



EnerVal G (800-6000)

Steel tank raw on the inside
EnerVal G (800-1500) fully insulated;
EnerVal G (2500), separate thermal insulation;
EnerVal G (4000,6000) packaged raw,
thermal insulation to be provided on site

EnerVal G type	Content l	Part No.
(800)	783	7019 133
(1000)	925	7019 134
(1500)	1395	7019 135
(2500)	2360	7019 136
(4000)	3907	6059 869
(6000)	5815	6059 870

Electric heating elements
see chapter “Electric heating elements”

Accessories



Protective tube immersion
sleeve set 200 ½″, 4 x
For installation of maximum 4 sensors
Nickel-plated brass
Installation length = 187 mm
Outer Ø: 18 mm, inner Ø: 16 mm
including 3 segment springs 90°,
1 Omega clamping spring

6061 045



Protective tube immersion sleeve SB280 ½″
Nickel-plated brass
Installation length = 280 mm
Outer Ø: 9 mm, inner Ø: 7 mm

2018 837



Thermometer kit
for EnerVal (800-6000)
Thermometer 0 ... 120 °C with
chromium plated edge and Hoval logo
Stem length: 80 mm, stem Ø: 9 (13) mm,
External Ø: 80 mm
incl. immersion sleeve ½″ nickel-plated
brass, installation length: 200 mm,
external Ø: 16 mm, internal Ø: 15 mm
and clamping spring

6052 107

Services


Services and associated scope of services
see separate catalogue “Hoval Services”

Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.


EnerVal G (800-6000)

Type		(800)	(1000)	(1500)	(2500)	(4000)	(6000)
• Volume	l	783	925	1395	2360	3907	5815
• Max. operating/test pressure	bar	6/8	6/8	6/8	6/8	6/8	6/8
• Min. operating temperature	°C	20	20	20	20	20	20
• Max. operating temperature	°C	95	95	95	95	95	95
• Thermal insulation made from polyester fleece	mm	150	150	150	150	-	-
• Thermal insulation λ	W/mK	0.04	0.04	0.04	0.04	-	-
• Fire protection class		B2	B2	B2	B2	-	-
• Heat loss at 65 °C	W	114	129	152	203	-	-
• Transport weight	kg	215	235	345	775	1275	1695
• U value	W/m^2K	0.302	0.305	0.295	0.295	-	-
• Dimensions		see dimensional drawing					


Velocity in the connection nozzles and inflow velocity with flow deflection in the EnerVal G (800-2500)



EnerVal G (4000,6000)





Example of inlet velocity distribution by flow diversions EnerVal G (800,1000)



EnerVal G (800-2500)

(Dimensions in mm)






Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm


			Type (800,1000)	pitch circle Ø	Type (1500,2500)	pitch circle Ø
1	Heating connection	return discharge (inflow restrictor)	DN 80, 4 x M16*, PN 6,	150 mm	DN 100, 4 x M16*, PN 6,	170 mm
2	Heating connection	flow discharge (single-layer elbow pipe)	DN 80, 4 x M16*, PN 6,	150 mm	DN 100, 4 x M16*, PN 6,	170 mm
3	Heat generator connection	flow top (inflow restrictor)	DN 65, 4 x M12*, PN 6,	130 mm	DN 80, 4 x M16*, PN 6,	150 mm
4	Heat generator connection	return top (inflow restrictor)	DN 65, 4 x M12*, PN 6,	130 mm	DN 80, 4 x M16*, PN 6,	150 mm
5	Heat generator connection	flow bottom (inflow restrictor)	DN 65, 4 x M12*, PN 6,	130 mm	DN 80, 4 x M16*, PN 6,	150 mm
6	Heat generator connection	return bottom (inflow restrictor)	DN 65, 4 x M12*, PN 6,	130 mm	DN 80, 4 x M16*, PN 6,	150 mm
7	Sleeve for immersion sleeve, thermostat or thermometer		Rp ½″ (IT)		Rp ½″ (IT)	
8	2 sensor terminal strips					
9	Removable cap (100 mm) for positioning the sensor					
10	Possible air vent		Rp 1″ (IT)		Rp 1″ (IT)	
11	Separating plate					
11a	Holes in the separating plate		12 x		12 x	
13	Hand-hole flange (flange-mounted electric heating element) (800,1000) outside Ø 180 mm, pitch circle Ø 150 mm, 8 x M10 (1500,2500) outside Ø 257 mm, pitch circle Ø 225 mm, 10 x M10					
14	Connection for circulation lance, **attention:** only for type (800,1000)		Rp 1″ (IT)		-	
*	The screw holes have threads					
**	Dimension for transport into building 823 mm (due to flanges position 3,4,6)					

EnerVal G type	D	d	H	a	b	c	e	f	g	i	k	m	n	p	q	r	s	Tilting measure
(800)	1090	790**	1907	183	326	435	496	810	1041	1269	1402	1526	1672	262	800	28	500	1945
(1000)	1090	790**	2197	183	369	468	569	955	1186	1472	1596	1759	1942	370	800	100	500	2230
(1500)	1300	1000	2135	180	358	489	529	894	1144	1360	-	1679	1819	319	800	100	500	2154
(2500)	1500	1200	2500	250	435	560	645	1100	1352	1670	-	2003	2211	400	800	100	800	2567

EnerVal G (4000,6000)

(Dimensions in mm)





Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

			Type (4000,6000)	pitch circle Ø
1	Heating connection	return discharge (inflow restrictor)	DN 125, 8 x M16*, PN 6,	200 mm
2	Heating connection	flow discharge (single-layer elbow pipe)	DN 125, 8 x M16*, PN 6,	200 mm
3	Heat generator connection	flow top (inflow restrictor)	DN 100, 4 x M16*, PN 6,	170 mm
4	Heat generator connection	return top (inflow restrictor)	DN 100, 4 x M16*, PN 6,	170 mm
5	Heat generator connection	flow bottom (inflow restrictor)	DN 100, 4 x M16*, PN 6,	170 mm
6	Heat generator connection	return bottom (inflow restrictor)	DN 100, 4 x M16*, PN 6,	170 mm
7	Sleeve for immersion sleeve, thermostat or thermometer		Rp ½″ (IT)	
8	3 sensor terminal strips			
10	Possible air vent		Rp 1″ (IT)	
11	Separating plate			
11a	Holes in the separating plate		24 x	
13	Hand-hole flange (flange-mounted electric heating element) Outside Ø 257 mm, pitch circle Ø 225 mm, 10 x M10			
15	Transport strap			

* The screw holes have threads

EnerVal G type	D	H	a	b	c	e	f	g	i	k	m	n	p	Tilting measure
(4000)	1500	2696	305	549	585	710	1202	1461	1829	2118	2330	430	1820	2773
(6000)	1500	3802	302	625	805	985	1704	2064	2603	3142	3442	550	2700	3858

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval EnerVal G cool

Buffer storage tank – cold storage tank

~~EnerVal G cool (800-6000)~~



Table of contents

- Description 5
- Part numbers 6
- Technical data 7
- Dimensions 9

Buffer storage tank – cold storage tank EnerVal G cool (800,1000)

- Steel buffer storage tank for the hydraulic integration of energy generators, coating with water-based paint
- Cold insulation made of synthetic rubber (19 mm), glued on diffusion-proof, with outer plastic jacket (red)
- 8 connection flanges DN 65 (PN 6)
- 2 connection flanges DN 80 (PN 6)
- 1 sleeve G 1½″ (IT) for electric heating element
- 5 sleeves G ½″ (IT) for sensor/thermometer
- 1 sleeve G 1″ (IT) for circulation lance
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed

Delivery
- Cold storage tank mounted with cold insulation (glued on diffusion-proof)

Buffer storage tank – cold storage tank EnerVal G cool (1500,2500)

- Steel buffer storage tank for the hydraulic integration of energy generators, coating with water-based paint
- Cold insulation made of synthetic rubber (19 mm), glued on diffusion-proof, with outer plastic jacket (red)
- 8 connection flanges DN 80 (PN 6)
- 2 connection flanges DN 100 (PN 6)
- 1 sleeve G 1½″ (IT) for electric heating element
- 5 sleeves G ½″ (IT) for sensor/thermometer
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed

Delivery
- Cold storage tank mounted with cold insulation (glued on diffusion-proof)

Buffer storage tank – cold storage tank EnerVal G cool (4000,6000)

- Steel buffer storage tank for the hydraulic integration of energy generators, coating with water-based paint
- Cold insulation made of synthetic rubber (19 mm), glued on diffusion-proof, with outer plastic jacket (red)
- 8 connection flanges DN 100 (PN 6)
- 2 connection flanges DN 125 (PN 6)
- 1 sleeve G 1½″ (IT) for electric heating element
- 5 sleeves G ½″ (IT) for sensor/thermometer
- 1 sleeve G 1″ (IT) for ventilation
- Perforated separating plate in the central area for separation of the temperature zones
- Flow diversions permanently installed


Delivery
- Cold storage tank mounted with cold insulation (glued on diffusion-proof)



Range

EnerVal G cool type	Content l	Operating pressure bar
(800)	793	6
(1000)	889	6
(1500)	1440	6
(2500)	2518	6
(4000)	4035	6
(6000)	5849	6

Buffer storage tank – cold storage tank



EnerVal G cool (800-6000)

Steel tank raw on the inside
Cold storage tank mounted with cold insulation

EnerVal G cool type	Content l	Part No.
(800)	793	6059 871
(1000)	889	6059 872
(1500)	1440	6059 933
(2500)	2518	6059 934
(4000)	4035	6059 935
(6000)	5849	6059 936

Electric heating elements
see chapter “Electric heating elements”

Accessories



Protective tube immersion
sleeve set 200 ½″, 4 x
For installation of maximum 4 sensors
Nickel-plated brass
Installation length = 187 mm
Outer Ø: 18 mm, inner Ø: 16 mm
including 3 segment springs 90°,
1 Omega clamping spring

6061 045



Protective tube immersion sleeve SB280 ½″
Nickel-plated brass
Installation length = 280 mm
Outer Ø: 9 mm, inner Ø: 7 mm

2018 837

Thermal insulation for EnerVal G cool
made of polyester fibre fleece
Outer plastic jacket colour red with patented aluminium sealing bracket

Type	Polyester fibre fleece	
(800)	120 mm	6061 134
(1000)	120 mm	6061 135
(1500)	140 mm	6061 136
(2500)	140 mm	6061 137
(4000)	140 mm	6061 138
(6000)	140 mm	6061 139

Services


Services and associated scope of services
see separate catalogue “Hoval Services”

Commissioning by Hoval customer service is a prerequisite for warranty/guarantee activation.


EnerVal G cool (800-6000)

Type		(800)	(1000)	(1500)	(2500)	(4000)	(6000)
• Volume	l	793	889	1440	2518	4035	5849
• Max. operating/test pressure	bar	6/8	6/8	6/8	6/8	6/8	6/8
• Min. operating temperature	°C	5	5	5	5	5	5
• Max. operating temperature	°C	85	85	85	85	85	85
• Cold insulation synthetic rubber	mm	19	19	19	19	19	19
• Cold insulation λ 0 °C	W/mK	0.033	0.033	0.033	0.033	0.033	0.033
• Cold insulation λ 40 °C	W/mK	0.037	0.037	0.037	0.037	0.037	0.037
• Fire protection class		B-s3,d0	B-s3,d0	B-s3,d0	B-s3,d0	B-s3,d0	B-s3,d0
• Transport weight	kg	171	189	306	468	694	902
• Water vapour diffusion resistance μ		≥ 7000	≥ 7000	≥ 7000	≥ 7000	≥ 7000	≥ 7000
• Dimensions		see dimensional drawing					


Velocity into the connection nozzle and inflow velocity with flow diversion
EnerVal G cool (800-2500)



EnerVal G cool (4000,6000)




Example of inlet velocity distribution by flow diversions EnerVal G cool (800,1000)





EnerVal G cool (800-6000)

Dimensions incl. cold insulation (series)
(Dimensions in mm)

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm







Type (800-6000)	pitch circle Ø
DN 65, PN 6	130 mm
DN 80, PN 6	150 mm
DN 100, PN 6	170 mm
DN 125, PN 6	200 mm


		Type (800,1000)	Type (1500,2500)	Type (4000,6000)
1	Cooling connection flow discharge (bend pipe)	DN 80, 4 x M16*	DN 100, 4 x M16*	DN 125, 8 x M16*
2	Cooling connection return discharge (bend pipe)	DN 80, 4 x M16*	DN 100, 4 x M16*	DN 125, 8 x M16*
3	Cold generator connection return top (inflow restrictor)	DN 65, 4 x M12*	DN 80, 4 x M16*	DN 100, 4 x M16*
4	Cold generator connection flow top (inflow restrictor)	DN 65, 4 x M12*	DN 80, 4 x M16*	DN 100, 4 x M16*
5	Cold generator connection return bottom (inflow restrictor)	DN 65, 4 x M12*	DN 80, 4 x M16*	DN 100, 4 x M16*
6	Cold generator connection flow bottom (inflow restrictor)	DN 65, 4 x M12*	DN 80, 4 x M16*	DN 100, 4 x M16*
7	Sleeve for immersion sleeve, thermostat or thermometer	G ½″ (IT)	G ½″ (IG)	G ½″ (IT)
10	Possible air vent	G 1″ (IT)	G 1″ (IG)	G 1″ (IT)
11	Separating plate			
11a	Holes in the separating plate	12 x	12 x	24 x
12	Connection for electric heating element	G 1½″ (IT)	G 1½″ (IT)	G 1½″ (IT)
14	Connection for circulation lance, **attention:** only for type (800,1000)	G 1″ (IT)		
16	Cold insulation, thickness 19 mm			
*	The screw holes have threads			
**	Dimension for transport into building = D			


EnerVal G cool


type	D**	d	H	a	b	c	e	f	g	i	k	Tilting measure
(800)	828	790	1866	327	496	810	1041	1269	1402	1527	1684	1882
(1000)	828	790	2066	369	569	955	1186	1472	1596	1759	1894	2080
(1500)	1028	990	2140	378	549	914	1164	1380	-	1699	1916	2158
(2500)	1288	1250	2448	435	645	1050	1302	1595	-	1903	2211	2475
(4000)	1438	1400	2975	485	780	1386	1638	2227	-	2535	2735	2999
(6000)	1638	1600	3303	523	840	1473	1873	2523	-	2823	3023	3342

EnerVal G cool (800-6000)

Dimensions with thermal insulation (optional)
(Dimensions in mm)







Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

	Type (800,1000)	Type (1500,2500)	Type (4000,6000)
17 Thermal insulation, thickness (in addition to the 19 mm cold insulation)	120 mm	140 mm	140 mm

EnerVal G cool

type	D	d	H
(800)	1068	790	1961
(1000)	1068	790	2161
(1500)	1308	990	2255
(2500)	1568	1250	2563
(4000)	1718	1400	3090
(6000)	1918	1600	3418

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval DuoVal

Compact storage tanks for heat pumps
DuoVal E (100/300), DuoVal C (100/300)



Table of contents

- Description 5
- Part numbers 6
- Technical data 10
- Dimensions 13

Hoval DuoVal E (100/300) compact storage tank

Compact storage tank for heat pumps with integrated buffer storage tank (100 litres) and calorifier made of steel, enamelled inside (300 litres)

- Floor-mounted compact storage tank
- Thermal insulation made from polyurethane rigid foam, foam-lined on the storage tank
- Removable foil jacket, colour flame red (RAL 3000)
- Integrated 100 litre buffer storage tank made of steel for heating/cooling
  - 4 heating connections G 1¼″
  - 1 sleeve G 1½″ for electric heating element
  - 2 sensor immersion sleeves welded in
  - 2 sleeves G ½″ for venting/draining
- Integrated 300 litre calorifier made of steel, enamelled on the inside
  - Plain-tube heat exchanger, enamelled, permanently installed
  - 2 heating connections G 1¼″
  - 1 cold water connection G 1¼″
  - 1 domestic hot water connection G 1¼″
  - 1 circulation connection G ½″
  - 2 sleeves G ½″ for sensors
  - 1 sleeve G ½″ for thermometer
  - 1 connection G 1¼″ magnesium protection anode or Correx® impressed current anode
  - 1 hand-hole flange (flange-mounted electric heating element), Ø 180/120 mm

DuoVal C (100/300)

Compact storage tank for heat pumps with integrated buffer storage tank (100 litres) and calorifier made of stainless steel (300 litres)

- Floor-mounted compact storage tank
- Thermal insulation made from polyurethane rigid foam, foam-lined on the storage tank
- Removable foil jacket, colour flame red (RAL 3000)
- Integrated 100 litre buffer storage tank made of steel for heating/cooling
  - 4 heating connections G 1¼″
  - 1 sleeve G 1½″ for electric heating element
  - 2 sensor immersion sleeves welded in
  - 2 sleeves G ½″ for venting/draining
- Integrated 300 litre calorifier made of stainless steel
  - Plain tube heat exchanger made of stainless steel, permanently installed
  - 2 heating connections G 1¼″
  - 1 cold water connection G 1¼″
  - 1 domestic hot water connection G 1¼″
  - 1 circulation connection G ½″
  - 2 sleeves G ½″ for sensors
  - 1 sleeve G ½″ for thermometer
  - 1 connection G 1¼″ Correx® impressed current anode
  - 1 hand-hole flange (flange-mounted electric heating element), Ø 180/120 mm



Model range

DuoVal type		
E	(100/300)	B
C	(100/300)	B

A⁺ → F

DuoVal E/C (100/300)
Compact storage tanks for the following Hoval heat pumps

- Hoval UltraSource® B comfort C (8,11)
- Hoval Belaria® pro comfort (8,13)
- Hoval Belaria® comfort ICM (8,13)
- Daikin Altherma 3 H HT W (14,18)
- Hoval UltraSource® T comfort (8,13)

Delivery

- Compact storage tank with foil jacket, completely installed and packed
- Foil jacket can be removed for installation
- DuoVal E (100/300) with enclosed magnesium protection anode for on-site installation

Included in the scope of delivery:

- 3 adjustable feet
- 2 sensor immersion sleeves ½″ incl. PG screw connection for calorifier
- 2 sensor clamping springs for the welded-in immersion sleeves in the buffer
- 1 thermometer incl. immersion sleeve ½″

Compact storage tank



Hoval DuoVal
Compact storage tank for heat pumps with integrated buffer storage tank and calorifier

DuoVal	Buffer storage tank l	Calorifier l	Part No.
E (100/300)	101	295	7019 485
C (100/300)	101	293	7019 486

Energy efficiency class
see “Description”

Authorisation number


DuoVal E/C	*SVGW test number*
DuoVal E (100/300)	2409-7360
DuoVal C (100/300)	2409-7361

Accessories



Kit Correx® impressed current anode UP2.3-919-L395/1
for long-term corrosion protection for installation in the enamelled calorifier
with reduction R 1¼″ (ET) - Rp 1″ (IT)
and R 1″ (ET) - Rp ¾″ (IT)
Installation length: 395 mm
Connection cable length: 1 x 2000 mm
1 Correx® impressed current anode

684 760



Kit Correx® impressed current anode UP1.9-924-L395/1
for long-term corrosion protection for installation in the stainless steel calorifier
with reduction R 1½″ - Rp ¾″
and R 1¼″ - Rp ¾″
Installation length: 395 mm
Connection cable length: 1 x 3500 mm
1 Correx® impressed current anode
(up to 800 l)

6031 813

With the DuoVal E, either the supplied magnesium protection anode or (optionally) a Correx® impressed current anode must be used.
With the DuoVal C, a Correx® impressed current anode can be used as an option.



Screw set
for flange-mounted electric heating element
- EFHK-E (4-180)
- EFHK-C (4-180)
- EFHK-E/C (3.5-180-PV)
- EFHK-E/C (4.4-180-PV)

Consisting of:
8 hexagon head screws M12 x 30 including washers

6063 095

Electric heating elements for calorifier DuoVal E (100/300)

*The following flange-mounted electric heating elements can be installed in the **calorifier:***



Flange-mounted electric heating element
for enamelled calorifiers
and buffer storage tanks
- Incoloy® alloy 825 heating rods
- Stainless steel flange Ø 180 mm, pitch circle 150 mm
- Medium: DHW and heating water
- Unheated zone: 100 mm
- Setting range: 7... 34 ... 80°C
- Safety temperature limiter: 95 °C
- Protection class: IPX0
- Casing: approx. Ø 185 x 103 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EFHK-E type	Heat output 3 x 400 V kW	changeable to	Installation length mm	Part No.
4-180	4.0		380	6053 353
		2.6 kW/3 x 400 V		
		2.0 kW/3 x 400 V		
		1.3 kW/3 x 400 V		
		1.3 kW/1 x 230 V		



Photovoltaic flange-mounted electric heating element
for enamelled calorifiers, stainless steel calorifiers and buffer storage tanks
- Incoloy® alloy 825 heating rods
- Ø 180 mm flange, pitch circle 150 mm
- LAN, Modbus TCP, 0-10 V DC
- Medium: DHW and heating water
- Voltage: 3 x 400 V
- Unheated zone: 70 mm
- Setting range: 0 … 60 … 85 °C
- Safety temperature limiter: 110 °C
- Protection class: IP21
- Casing: Ø 186 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EFHK-E/C type	Heat output 3 x 400 V kW	Output levels kW	Installation length mm	Part No.
3.5-180-PV	3.5	7 x 0.50	360	6063 624
4.4-180-PV	4.4	7 x 0.65	420	6063 625

Electric heating elements for calorifier DuoVal C (100/300)

*The following flange-mounted electric heating elements can be installed in the **calorifier:***



Flange-mounted electric heating element
for stainless steel calorifiers
- Incoloy® alloy 825 heating rods
- Stainless steel flange Ø 180 mm, pitch circle 150 mm
- Medium: DHW and heating water
- Unheated zone: 100 mm
- Setting range: 7 ... 34 ... 80°C
- Safety temperature limiter: 95 °C
- Protection class: IPX0
- Casing: approx. Ø 185 x 103 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EFHK-C type	Heat output 3 x 400 V kW	changeable to	Installation length mm	Part No.
4-180	4.0		380	6049 564
		2.6 kW/3 x 400 V		
		2.0 kW/3 x 400 V		
		1.3 kW/3 x 400 V		
		1.3 kW/1 x 230 V		



Photovoltaic flange-mounted electric heating element
for enamelled calorifiers, stainless steel calorifiers and buffer storage tanks
- Incoloy® alloy 825 heating rods
- Ø 180 mm flange, pitch circle 150 mm
- LAN, Modbus TCP, 0-10 V DC
- Medium: DHW and heating water
- Voltage: 3 x 400 V
- Unheated zone: 70 mm
- Setting range: 0 … 60 … 85 °C
- Safety temperature limiter: 110 °C
- Protection class: IP21
- Casing: Ø 186 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EFHK-E/C type	Heat output 3 x 400 V kW	Output levels kW	Installation length mm	Part No.
3.5-180-PV	3.5	7 x 0.50	360	6063 624
4.4-180-PV	4.4	7 x 0.65	420	6063 625

Electric heating elements for buffer storage tanks DuoVal E/C (100/300)

*The following screw-in electric heating elements can be installed in the **buffer storage tank:***



Screw-in electric heating element
for enamelled calorifiers, stainless steel calorifiers and buffer storage tank
- Incoloy® alloy 825 heating rods
- Brass nipple G 1½″
- Medium: DHW and heating water
- Unheated zone: 150 mm
- Setting range: 7 ... 34 ... 80 °C
- Safety temperature limiter: 95 °C
- Protection class: IP54
- Casing: approx. 90 x 90 x 140 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EP type	Heat output kW	Output levels V	Installation length mm	Part No.
2.5	2.35	3 x 400 (1 x 230)	390	6059 778
3.5	3.6	3 x 400	500	6059 779



Photovoltaic screw-in electric heating element
for enamelled calorifiers and stainless steel calorifiers
- Incoloy® alloy 825 heating rods
- Brass nipple R 1½″
- LAN, Modbus TCP, 0-10 V DC
- Medium: DHW and heating water
- Voltage: 3 x 400 V
- Unheated zone: 150 mm
- Setting range: 0 … 60 … 85 °C
- Safety temperature limiter: 110 °C
- Protection class: IP41
- Casing: 126 x 135 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EP type	Heat output 3 x 400 V kW	Output levels kW	Installation length mm	Part No.
3.5-1½″-PV	3.5	7 x 0.50	600	6063 629

DuoVal E (100/300), DuoVal C (100/300)

Type		E (100/300)	C (100/300)
Storage tank			
• Transport weight	kg	174	130
• Tilting measure	mm	1970	1970
• Thermal insulation polyurethane rigid foam, foam-lined	mm	80	80
• Thermal insulation λ	W/mK	0.024	0.024
• Fire protection class	-	B2	B2
• Heat loss at 65 °C	W	76	76
Buffer storage tank			
• Volume	l	101	101
• Max. operating/test pressure	bar	3/4.5	3/4.5
• Min./max. operating temperature	°C	7/95	7/95
Calorifier			
• Volume	l	295	293
• Max. operating/test pressure	bar	10/15	6/12
• Max. operating temperature	°C	95	95
Heating coil (built-in)			
• Heating surface	m²	3.5	3.12
• Heating water	l	21	19
• Pressure drop		see diagram	
• Max. operating/test pressure	bar	10/15	10/15
• Max. operating temperature	°C	110	110
• Dimensions		see dimensional drawing	

Performance figure

at a hot water temperature of 45 °C

Reading example
see engineering


	Comfort [1]			Standard [2]		
T >	60°C	70°C	80°C	60°C	70°C	80°C
NL ˅						
1						
2						
3						
4	300			300		
5						
6						
7						
8						
9		300			300	
10			300			300
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						

T = heating flow
NL = performance figure
Performance figure NL acc. to DIN 4708 = number of flats which can be supplied with domestic hot water when the calorifier is heated and permanently reheated with the heat generator (standard flat: 1 bathroom – 4 rooms – 3.5 persons)
[1] Calculation with simultaneity factor according to DIN 4708 (preferred for Switzerland)
[2] Calculation with simultaneity factor according to Dresden Technical University

10 min peak output/N number with domestic hot water 45 °C

according to DIN 4708 (Comfort) and Dresden Technical University (Standard)

Reading example
see Engineering



DuoVal E/C


Hot water output
Continuous output

Reading example
see engineering


Heat input [kW]

Continuous output [l/h] with heating flow ...


Warmwasser 45 °C




10 min peak output – hot water 45 °C *




Hot water 55 °C



Pressure drop heating coil – delivery head charging pump




Hot water 60 °C




* Calorifier heated to 60 °C

DuoVal E/C (100/300)

(Dimensions in mm)





1	Anode connection	G 1¼″ (IT)
2	Hot water	G 1¼″ (IT)
3	Circulation	G ½″ (IT)
4	Hot water reheating flow	G 1¼″ (IT)
5	Hot water reheating return	G 1¼″ (IT)
6	Sensor hot water top	G ½″ (IT)
7	Sensor hot water bottom	G ½″ (IT)
8	Cold water	G 1¼″ (IT)
9	Heating flow (heat pump flow)	G 1¼″ (IT)
10	Heating return (heat pump return)	G 1¼″ (IT)
11	Venting/draining	G ½″ (IT)
12	Buffer sensor top	Inner Ø 13 mm
13	Buffer sensor bottom	Inner Ø 13 mm
14	Electric heating cartridge (optional)	G 1½″ (IT)
15	Flange/electric heating cartridge (optional)	180/120 mm
16	Thermometer	G ½″ (IT)

Deviations possible as a result of manufacturing tolerances.
Dimensions ± 10 mm

DuoVal E/C

type	D	d	H	a	b	c	e	f	g	i	k	m	n	p	q	r	s	Tilting measure
(100/300)	760	600	1800	170	240	350	420	655	755	1000	1300	1435	1525	1615	250	810	1525	1970

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval electric heating elements

Screw-in and flange-mounted electric heating elements



Table of contents

- Description 5
- Part numbers 6
- Dimensions 10
- Engineering 12

Hoval electric heating element

Screw-in electric heating element
Type EP 2.5 to EP 7.5
The electric heating element consists of three U-shaped round heating rods and a thermostat protection tube mounted in a 1½″ brass nipple, a flat seal is included in the scope of delivery. Due to the insulated installation of the round heating rods, the units are also suitable for enamelled calorifiers. The unheated zone is 150 mm for all outputs.

Flange-mounted electric heating element
Type EFHK-E/-C 4 to 9
The electric heating element consists of three U-shaped round heating rods, each pressed into a press nipple. These are screwed onto a stainless steel flange with thermostat protection tube, a flange seal (EPDM) is included in the scope of delivery. A food-safe plastic disc (PVDF) serves as insulation. The unheated zone is 100 mm for all outputs.

Features for all electric heating element types
- TR: Electromechanical temperature controller
- STB: Electromechanical safety temperature limiter
- Rotary knob with temperature display
- Incoloy® alloy 825 heating rods
- Connection 3 x 400 V
- Not suitable for exclusively electric heating (risk of limescale buildup)

Delivery
Included in separate packaging

On site
Observe the position and installation of the electric heating element in the buffer storage tank/storage tank with heating coil, if necessary according to the schematic diagram and/or structural conditions.



EP EFHK-E/C

Range type	Output kW	Installation length mm
Screw-in electric heating element for enamelled calorifiers, stainless steel calorifiers and buffer storage tank		
EP-2.5-1½″	2.35	390
EP-3.5-1½″	3.6	500
EP-5.0-1½″	4.9	620
EP-7.5-1½″	7.5	850
Flange-mounted electric heating element for enamelled calorifiers and buffer storage tank		
EFHK-E-4-180	4.0	380
EFHK-E-6-180	6.0	460
EFHK-E-9-180	9.0	615
Flange-mounted electric heating element for stainless steel calorifier		
EFHK-C-4-180	4.0	380
EFHK-C-6-180	6.0	460
EFHK-C-9-180	8.5	670
Flange-mounted electric heating element for buffer storage tanks		
EFHK-E-9-250	8.5	615

Electric heating elements



Screw-in electric heating element
for enamelled calorifiers, stainless steel calorifiers and buffer storage tank
- Incoloy® alloy 825 heating rods
- Brass nipple G 1½"
- Medium: DHW and heating water
- Unheated zone: 150 mm
- Setting range: 7... 34 ... 80 °C
- Safety temperature limiter: 95 °C
- Protection class: IP54
- Casing: approx. 90 x 90 x 140 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EP type	Heat output kW	Output levels V	Installation length mm	Part No.
2.5	2.35	3 x 400 (1 x 230)	390	6059 778
3.5	3.6	3 x 400	500	6059 779
5.0	4.9	3 x 400	620	6059 780
7.5	7.5	3 x 400	850	6059 781



Flange-mounted electric heating element
for enamelled calorifiers and buffer storage tanks
- Incoloy® alloy 825 heating rods
- Stainless steel flange Ø 180 mm, pitch circle 150 mm
- Medium: DHW and heating water
- Unheated zone: 100 mm
- Setting range: 7... 34 ... 80°C
- Safety temperature limiter: 95 °C
- Protection class: IPX0
- Casing: approx. Ø 185 x 103 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup)

EFHK-E type	Heat output 3 x 400 V kW	changeable to	Installation length mm	Part No.
4-180	4.0		380	6053 353
		2.6 kW/3 x 400 V		
		2.0 kW/3 x 400 V		
		1.3 kW/3 x 400 V		
		1.3 kW/1 x 230 V		
6-180	6.0		460	6053 354
		4.0 kW/3 x 400 V		
		3.0 kW/3 x 400 V		
		2.0 kW/3 x 400 V		
		2.0 kW/1 x 230 V		
9-180	9.0		615	6052 438
		5.7 kW/3 x 400 V		
		4.2 kW/3 x 400 V		
		2.8 kW/3 x 400 V		
		2.8 kW/1 x 230 V		



Flange-mounted electric heating element
EFHK-E-9-250
Output 8.5 kW, 3 x 400 V
For horizontal installation
in the enamelled calorifier and the
buffer storage tank with
flange diameter 257 mm,
pitch circle 225 mm

Consisting of:
1 adjustable temperature controller
3 heating rods made of material 2.4858
1 safety temperature limiter
1 glue-on rosette

Technical data:
Output 8.5 kW
Connection 3 x 400 V
Plastic cover
Installation length 615 mm


Suitable for EnerVal G (1500-6000)

Part No.
6053 355

Type		Screw-in electric heating element EP 2.5 to 5	Flange-mounted electric heating element EFHK-E/-C 4 to 9	Flange-mounted electric heating element EFHK-E-9-250
Temperature setting range	°C	7... 34 ... 80	7... 34 ... 80	7... 34 ... 80
Switch-off temperature	°C	95	95	95
Ambient temperature at the switchgear	°C	max. 80	max. 80	max. 80
Thermal switching difference	K	8 ± 4	8 ± 4	8 ± 4
Ambient temperature during storage and transport	°C	−12 ... 80	−12 ... 80	−12 ... 80
Flange/thread size		G 1½″ (conical)	Outside Ø 180 mm, pitch circle Ø 150 mm, 8 x M10	Outside Ø 257 mm, pitch circle Ø 225 mm, 10 x M10
Flange/thread connection material		Brass (CuZn40Pb2)	stainless steel (1.4404) Seal: EPDM (KTW approval)	stainless steel (1.4404) Seal: EPDM (KTW approval)
Round heating rods		Incoloy® alloy 825, 2.4858	Incoloy® alloy 825, 2.4858	Incoloy® alloy 825, 2.4858
Surface load	W/cm²	approx. 7	approx. 5	approx. 5
Electrical connection		Screw terminals, PG screwed cable gland	Spring-cage terminals, strain relief, lead-through	Spring-cage terminals, strain relief, lead-through
Operating pressure	bar	Max. 10	Max. 10	Max. 10
Casing top part		Polycarbonate, RAL 3000 (red)	ABS, black	ABS, black
Type of protection		IP54	IPX0	IPX0
Dimensions		See dimensional drawing	See dimensional drawing	See dimensional drawing

Screw-in electric heating element


1. Screw-in electric heating element with insulated installation of the round heating rods which are suitable for enamelled as well as black steel calorifiers and, thanks to DIP switch, also for stainless steel calorifiers
2. Standard hexagon profile for secure tightening with 60 mm open-end spanner
3. Cylindrical thread for precise casing position and tight mounting
4. Surface load 7 W/cm²
5. Sensor position in the immersion tube for identical temperature detection of safety temperature limiter and temperature controller



Shown without cover

Flange-mounted electric heating element


1. Standard flange outside Ø 180 mm or 257 mm, EFHK-E suitable for enamelled as well as black steel calorifiers and, with EFHK-C, also suitable for stainless steel calorifiers thanks to mounted plastic insulating plate
2. Low surface load 5 W/cm², for less calcification
3. Sensor position in the immersion tube for identical temperature detection of safety temperature limiter and temperature controller
4. Insulated mounting of the heating rods for reduced corrosion




Shown without cover

Connection diagram screw-in electric heating element

230 V: P to L1 / N to L2




3 ~ 400 V: L1 / L2 / L3




A) Temperature controller
B) Safety temperature limiter

Connection diagram flange-mounted electric heating element

3 x 400 V Δ: L1 / L2 / L3





230 V Δ: L1 su N




Screw-in electric heating element
(Dimensions in mm)

EP 2.5/3.5/5.0/7.5
for enamelled calorifiers, stainless steel calorifiers and buffer storage tanks







Installation length =	EL
EP 2.5	390
EP 3.5	500
EP 5.0	620
EP 7.5	850




Flange-mounted electric heating element
(Dimensions in mm)

EFHK-E-4/6/9-180
for enamelled calorifiers and buffer storage tanks










Installation length =	EL
EFHK-E-4-180	380
EFHK-E-6-180	460
EFHK-E-9-180	615

EFHK-C-4/6/9-180
for stainless steel calorifiers








Installation length =	EL
EFHK-C-4-180	380
EFHK-C-6-180	460
EFHK-C-9-180	670

Flange-mounted electric heating element

(Dimensions in mm)

EFHK-E-9-250
For horizontal installation in the enamelled calorifier



Installation length =	EL
EFHK-E-9-250	615

Calorifier/storage tank	Screw-in electric heating element				Flange-mounted electric heating element													
	EP 2.5 2.35 kW	EP 3.5 3.6 kW	EP 5 4.9 kW	EP 7.5 7.5 kW	EFHK-E- 4-180 4.0 kW		EFHK-E- 6-180 6.0 kW		EFHK-E- 9-180 9.0 kW		EFHK-C- 4-180 4.0 kW		EFHK-C- 6-180 6.0 kW		EFHK-C- 9-180 8.5 kW		EFHK-E- 9-250 8.5 kW	
Installation type	Sleeve 1½"				Flange Ø 180												Ø 257	
Installation position					t	b	t	b	t	b	t	b	t	b	t	b	t	b
Stainless steel calorifier																		
CombiVal C																		
CombiVal C (300)												●		●				
CombiVal C (400)												●		●				
CombiVal C (500)												●		●				
CombiVal C (750)												●		●		●		
CombiVal C (1000)												●		●		●		
CombiVal C (1500)											●	●	●	●	●	●		
CombiVal C (2000)											●	●	●	●	●	●		
CombiVal C (2500)												●*		●*		●*		
CombiVal CR																		
CombiVal CR (200)	●	●										●		●				
CombiVal CR (300)	●	●										●		●				
CombiVal CR (500)	●	●	●									●		●				
CombiVal CR (800)											●	●	●	●	●	●		
CombiVal CR (1000)											●	●	●	●	●	●		
CombiVal CSR																		
CombiVal CSR (300)	●	●										●		●				
CombiVal CSR (400)	●	●	●									●		●				
CombiVal CSR (500)	●	●	●									●		●				
CombiVal CSR (800)											●	●	●	●	●	●		
CombiVal CSR (1000)											●	●	●	●	●	●		
CombiVal CSR (1250)											●	●	●	●	●	●		
CombiVal CSR (1500)											●	●	●	●	●	●		
CombiVal CSR (2000)											●	●	●	●	●	●		
Enamelled calorifier																		
CombiVal E																		
CombiVal E (300)						●		●										
CombiVal E (500)						●		●										
CombiVal E (800)						●		●		●								
CombiVal E (1000)						●		●		●								
CombiVal E (1500)					●	●	●	●	●	●								
CombiVal E (2000)					●	●	●	●	●	●								
CombiVal ER																		
CombiVal ER (200)						●												
CombiVal ERW (200)						●												
CombiVal ER (300)						●		●										
CombiVal ER (400)						●		●										
CombiVal ER (500)						●		●										
CombiVal ER (800)						●		●		●								
CombiVal ER (1000)						●		●		●								
CombiVal ESR																		
CombiVal ESR (200)						●												
CombiVal ESR (300)						●		●										
CombiVal ESR (400)						●		●										
CombiVal ESSR																		
CombiVal ESSR (500)	●	●	●			●		●										
CombiVal ESSR (800)					●	●	●	●	●	●								
CombiVal ESSR (1000)					●	●	●	●	●	●								
MultiVal ERR																		
MultiVal ERR (300)	●	●				●												
MultiVal ERR (400)	●	●	●			●		●										
MultiVal ERR (500)	●	●	●			●		●										
MultiVal ESRR																		
MultiVal ESRR (500)	●	●				●		●										
MultiVal ESRR (800)					●	●	●	●	●	●								
MultiVal ESRR (1000)					●	●	●	●	●	●								

* On-site delivery of an adapter flange for the installation of the flange-mounted electric heating element

Calorifier/storage tank	Screw-in electric heating element								Flange-mounted electric heating element													
	EP 2.5 2.35 kW		EP 3.5 3.6 kW		EP 5 4.9 kW		EP 7.5 7.5 kW		EFHK-E- 4-180 4.0 kW		EFHK-E- 6-180 6.0 kW		EFHK-E- 9-180 9.0 kW		EFHK-C- 4-180 4.0 kW		EFHK-C- 6-180 6.0 kW		EFHK-C- 9-180 8.5 kW		EFHK-E- 9-250 8.5 kW	
Installation type	Sleeve 1½"								Flange Ø 180												Ø 257	
Installation position	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b
Buffer storage tank																						
EnerVal																						
EnerVal (200)	●		●																			
EnerVal (300)	●		●																			
EnerVal (500)	●	●	●	●	●	●																
EnerVal (800)	●	●	●	●	●	●	●	●														
EnerVal (1000)	●	●	●	●	●	●	●	●														
EnerVal (1500)	●	●	●	●	●	●	●	●														
EnerVal (2000)	●	●	●	●	●	●	●	●														
EnerVal G																						
EnerVal G (800)									●	●	●	●	●	●								
EnerVal G (1000)									●	●	●	●	●	●								
EnerVal G (1500)																					●	●
EnerVal G (2000)																					●	●
EnerVal G (2500)																					●	●
EnerVal G (4000)																					●	●
EnerVal G (6000)																					●	●
EnerVal G cool																						
EnerVal G cool (800)	●		●		●		●															
EnerVal G cool (1000)	●		●		●		●															
EnerVal G cool (1500)	●		●		●		●															
EnerVal G cool (2500)	●		●		●		●															
EnerVal G cool (4000)	●		●		●		●															
EnerVal G cool (6000)	●		●		●		●															
Stratified storage tank																						
VarioVal FLS/Rxx																						
VarioVal FLS (800)	●		●		●																	
VarioVal FLS (1000)	●		●		●																	
VarioVal RHS (800)	●		●		●																	
VarioVal RHS (1000)	●		●		●																	
VarioVal RL (600)	●		●		●																	
VarioVal RLS (800)	●		●		●																	
VarioVal RLS (1000)	●		●		●																	

Legend:
t: top, b: bottom

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Hoval

CATALOGUE

Hoval photovoltaic electric heating elements

Screw-in and flange-mounted electric heating elements with RemoteControl



Table of contents

- Description 5
- Part numbers 7
- Technical data 8
- Dimensions 15
- Engineering 16

Photovoltaic electric heating element

Screw-in electric heating element type EP 3.5 bis EP 9.0
Screw-in electric heating element EP: The electric heating element consists of three U-shaped round heating rods, which are mounted in a conical brass nipple 1½″ insulated by means of food-safe plastic sleeves. Thanks to the insulated installation of the round heating elements, the devices are also suitable for enamelled storage tanks. The unheated zone is 150 mm for all outputs.


Flange-mounted electric heating element type EFHK-E/-C 3.5 bis 9.0
Flange-mounted electric heating element EFHK: The electric heating element consists of three U-shaped round heating rods, each pressed into a press nipple. These are screwed with the immersion sleeve onto a steel flange. A food-safe plastic disc serves as insulation. The unheated zone is 70 mm for all outputs.

RemoteControl
The PV electric heating elements (screw-in/flange) are supplied with a control unit, the RC (RemoteControl) casing.
All control signals and optional temperature sensors are connected to this control unit.
The display shows the status of the PV electric heating element. Heat output, IP address, the heating status or any error messages can be displayed if required. The control unit is connected to the PV electric heating element, a 2.8 m long connection cable is included in the scope of delivery.

Application
- As supplementary heating of service and heating water in photovoltaic systems.
- For optimisation of the internal consumption of PV energy.
- To minimise the switch-ons/cycles of the main heat generator e.g. exclusively hot water production in summer.

Features
- TR: Electromechanical temperature controller according to EN 14597, not unbreakable.
- STB: Electromechanical temperature limiter according to EN 14597, unbreakable, if the excess temperature is exceeded, the switchgear switches OFF and remains locked in this position. Unlocking is done manually after the sensor tube has cooled down by approx. 10 K.
  - Time constant of the sensor tube according to EN 14597
  - Mode of operation TR type 2 B according to EN 14597
  - Mode of operation STB type 2 BK according to EN 14597

On site
Observe the position and installation of the electric heating element in the buffer storage tank/storage tank with heating coil, if necessary according to the schematic diagram and/or structural conditions.



EP-PV RemoteControl EFHK-E/C-PV

Range type	Output kW	Installation length mm
Photovoltaic screw-in electric heating element for enamelled calorifiers and stainless steel calorifiers		
EP-3.5-1½″-PV	3.5	600
EP-4.4-1½″-PV	4.4	700
EP-5.2-1½″-PV	5.2	750
EP-7.5-1½″-PV	7.5	700
EP-9.0-1½″-PV	9.0	750
Photovoltaic flange-mounted electric heating element for enamelled calorifiers, stainless steel calorifiers and buffer storage tanks		
EFHK-E/C-3.5-180-PV	3.5	360
EFHK-E/C-4.4-180-PV	4.4	420
EFHK-E/C-5.8-180-PV	5.8	540
EFHK-E/C-7.5-180-PV	7.5	420
EFHK-E/C-9.0-180-PV	9.0	490

Connections
The screw-in electric heating element is equipped with 2 connection sockets.
The flange-mounted electric heating element is equipped with 2 connection sockets.
All necessary plugs are included in the scope of delivery. After initial connection or commissioning by a qualified electrician, the device can be completely disconnected from the mains and the connection to the control unit by pulling out the plugs.

Function modes
Analog modes (0-10 V control signal)
The electric heating element can be controlled with a 0-10 V signal in 3 or 7 power levels (depending on the model).
7-stage: From a voltage of 1.25 V, the device switches to the first heating stage. Each additional stage requires a voltage increase of 1.25 V.

From a voltage of 8.75 V, the device switches to the seventh heating stage. To avoid flickering, a hysteresis of 0.25 V is programmed in.
3-stage: The electric heating element can be controlled with a 0-10 V signal in the 3 power levels. To avoid flickering, a hysteresis of 0.25 V is programmed in.

Modbus TCP
In this function, the device obtains an IP address via a local DHCP server (router). After the electric heating element has been integrated into the network, it can be controlled in 3 and 7 power levels (depending on the model) and the temperature of the sensors can be read out. The power levels can be controlled via a value 0-7 or 0-3 or via a reference value specification (here the electric heating element independently selects the suitable power level).

Legionella protection
The automatic legionella protection automatically heats the system to min. 65 °C daily/weekly or fortnightly. If the temperature of 65 °C is reached within the interval, regardless of the legionella protection program, the interval timer starts over from this point.
The parameters can be configured via Modbus or MQTT.

Request contact of the main heat generator
If a heat pump is available, the device can be used as a supplementary heater. The heat pump is controlled via a digital input, which activates the full heating output.

Emergency mode “Emergency On”
The “Emergency On” button can be used to switch on the maximum heating power immediately. This may be necessary in the event of a failure or if additional heat is required. To switch off, press the button again. The temperature is digitally limited to 60 °C in this mode. For safety reasons, the electric heating element automatically switches back to normal operation after 24 hours.

Corrosion protection
Please note: This electric heating element can be used for stainless steel storage tanks as well as for black steel/enamelled storage tanks.
For the installation of an electric heating element in a black steel or black steel enamelled storage tank, the red slide switch (DIP switch) must be left in the “black steel storage tank” position (factory setting). When the electric heating element is installed in a stainless steel storage tank, the slide switch (DIP switch) must be set to the “stainless steel storage tank” position.

Web interface
- Setting setpoint temperatures for minimum temperature, request temperature, legionella protection temperatures, low-tariff temperature
- Reading out the control signals
- Reading out actual temperatures
- Reading out operating hours
- Setting up the Modbus configuration or direct communication with SMA or SENEC

Photovoltaic electric heating elements



Photovoltaic screw-in electric heating element
for enamelled calorifiers and stainless steel calorifiers
- Incoloy® alloy 825 heating rods
- Brass nipple R 1½″
- LAN, Modbus TCP, 0-10 V DC
- Medium: DHW and heating water
- Voltage: 3 x 400 V
- Unheated zone: 150 mm
- Setting range: 0 … 60 … 85 °C
- Safety temperature limiter: 110 °C
- Protection class: IP41
- Casing: 126 x 135 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup).

EP type	Heat output 3 x 400 V kW	Output levels kW	Installation length mm	Part No.
3.5-1½″-PV	3.5	7 x 0.50	600	6063 629
4.4-1½″-PV	4.4	7 x 0.65	700	6063 630
5.2-1½″-PV	5.2	7 x 0.75	750	6063 631
7.5-1½″-PV	7.5	3 x 2.50	700	6063 632
9.0-1½″-PV	9.0	3 x 3.00	750	6063 633



Photovoltaic flange-mounted electric heating element
for enamelled calorifiers, stainless steel calorifiers and buffer storage tanks
- Incoloy® alloy 825 heating rods
- Ø 180 mm flange
- LAN, Modbus TCP, 0-10 V DC
- Medium: DHW and heating water
- Voltage: 3 x 400 V
- Unheated zone: 70 mm
- Setting range: 0 … 60 … 85 °C
- Safety temperature limiter: 110 °C
- Protection class: IP21
- Casing: Ø 186 mm
- Max. operating pressure: 10 bar
- Delivered separately, installation on site
- Not suitable for exclusively electric heating (risk of limescale buildup).

EFHK-E/C type	Heat output 3 x 400 V kW	Output levels kW	Installation length mm	Part No.
3.5-180-PV	3.5	7 x 0.50	360	6063 624
4.4-180-PV	4.4	7 x 0.65	420	6063 625
5.8-180-PV	5.8	7 x 0.83	540	6063 626
7.5-180-PV	7.5	3 x 2.50	420	6063 627
9.0-180-PV	9.0	3 x 3.00	490	6063 628




Flange adapter set Ø 257-180 — 6063 634
Adapter for reduction of the flange diameter from 257 to 180 mm.
Complete incl. seal and screws

Photovoltaic electric heating element

		Photovoltaic screw-in electric heating element	Photovoltaic flange-mounted electric heating element
Temperature setting range	°C	28 ... 85	28 ... 85
Switch-off temperature	°C	110	110
Ambient temperature at the switchgear	°C	max. 50	max. 50
Thermal switching difference	K	11.0 ± 5.5	11.0 ± 5.5
Ambient temperature during storage and transport	°C	−30 ... 90	−30 ... 90
Flange/thread size		R 1½″ (conical)	Outside Ø 180 mm, pitch circle Ø 150 mm, 8 x M12
Flange/thread connection material		Brass (CuZn40Pb2)	Black steel (St 37/1.0038, painted) Seal: EPDM (KTW approval)
Round heating rods		Incoloy® alloy 825, 2.4858	Incoloy® alloy 825, 2.4858
Surface load	W/cm²	8-9	7
Electrical connection		Connector plug with screw contacts	Connector plug with screw contacts
Operating pressure	bar	Max. 10	Max. 10
Casing top part		Polycarbonate, RAL 7035 (light grey)	Polycarbonate, RAL 7035 (light grey)
Casing bottom part		Polycarbonate, RAL 7016 (anthracite grey)	Polycarbonate, RAL 7016 (anthracite grey)
Type of protection		IP41	IP21
Dimensions		See dimensional drawing	See dimensional drawing

Photovoltaic screw-in electric heating element


1. Screw-in electric heating element with insulated installation of the round heating rods which are suitable for enamelled as well as black steel calorifiers and, thanks to DIP switch, also for stainless steel calorifiers
2. Standard hexagon profile for secure tightening with 60 mm open-end spanner
3. Conical thread for precise casing position and tight mounting (1½″ standard)
4. Surface load 8-9 W/cm², suitable for heating water
5. Optimum sensor position in the oval immersion tube for identical temperature detection of safety temperature limiter and temperature controller




Illustrations without cover


Photovoltaic flange-mounted electric heating element

1. Standard flange outside Ø 180 mm, suitable for enamelled as well as black steel calorifiers and, thanks to DIP switch, also for stainless steel calorifiers
2. Delivery incl. flat seal (included separately)
3. Deep surface load 7 W/cm², for lower limescale buildup
4. Optimum sensor position
5. Insulated mounting of the heating rods for reduced corrosion



Connection plugs photovoltaic flange-mounted electric heating element EP-3.5 to EP-5.2







RemoteControl control unit

X1 – RJ12 connection socket
Interface to screw-in electric heating element

X2 – M12 socket for control signals
Switch-on signal of the heat pump
Analogue signal 0-10 V
Power station block (digital input)
Output signal (5 V DC) for circulating pump

X3 – M12 plug for temperature sensor
Connection options for optional content sensors 1 to 4

X4 – M12 plug RS485 interface
Modbus RTU communication via RS485 interface

X5 – RJ45 connection socket
Network connection via LAN connection

Screw-in electric heating element

Z1 – mains supply
For power supply to the heating elements and internal circuit board

Z5 – RJ12 connection socket
Interface to RemoteControl control unit

Supplied plugs/connecting cable

Z1 – power supply heating element
Wieland RST 5-pin plug, IP66
load capacity: 250/400 V 16 A
screw connections max. 2.5 mm²
(up to 1.5 mm² end ferrules can be used)


Z5/X1 – communication
Pluggable RJ12 communication cable 2.9 m


X2: Round plug connector M12 (socket)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X2: Round plug connector M12 (plug)
3-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X4: Round plug connector M12 (plug)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

Connection plugs photovoltaic screw-in electric heating element EP-7.5 to EP-9.0







RemoteControl control unit

X1 – RJ12 connection socket
Interface to screw-in electric heating element

X2 – M12 socket for control signals
Switch-on signal of the heat pump
Analogue signal 0-10 V
Power station block (digital input)
Output signal (5 V DC) for circulating pump

X3 – M12 plug for temperature sensor
Connection options for optional content sensors 1 to 4

X4 – M12 plug RS485 interface
Modbus RTU communication via RS485 interface

X5 – RJ45 connection socket
Network connection via LAN connection

Screw-in electric heating element

Z1 – mains supply
For power supply to the heating elements and internal circuit board

Z5 – RJ12 connection socket
Interface to RemoteControl control unit

Supplied plugs/connecting cable

Z1 – power supply heating element
Wieland RST mini 1615,
5-pin plug with 2 m cable 2.5 mm²
Capacity: 250/400 V 16 A


Z5/X1 – communication
Pluggable RJ12 communication cable 2.9 m

X2: Round plug connector M12 (socket)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X2: Round plug connector M12 (plug)
3-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X4: Round plug connector M12 (plug)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

Connection plugs photovoltaic flange-mounted electric heating element EFHK-3.5 to EFHK-5.8







RemoteControl control unit

X1 – RJ12 connection socket
Interface to flange-mounted electric heating element

X2 – M12 socket for control signals
Switch-on signal of the heat pump
Analogue signal 0-10 V
Power station block (digital input)
Output signal (5 V DC) for circulating pump

X3 – M12 plug for temperature sensor
Connection options for optional content sensors 1 to 4

X4 – M12 plug RS485 interface
Modbus RTU communication via RS485 interface

X5 – RJ45 connection socket
Network connection via LAN connection

Flange-mounted electric heating element

Z1 – mains supply
For power supply to the heating elements and internal circuit board

Z5 – RJ12 connection socket
Interface to RemoteControl control unit

Supplied plugs/connecting cable

Z1 – power supply heating element
Wieland RST 5-pin plug,
IP66 load capacity: 250/400 V 16 A screw connections max. 2.5 mm²
(up to 1.5 mm² end ferrules can be used)


Z5/X1 – communication
Pluggable RJ12 communication cable 2.9 m

X2: Round plug connector M12 (socket)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X2: Round plug connector M12 (plug)
3-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X4: Round plug connector M12 (plug)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

Connection plugs photovoltaic flange-mounted electric heating element EFHK-7.5 and EFHK-9.0







RemoteControl control unit

X1 – RJ12 connection socket
Interface to flange-mounted electric heating element

X2 – M12 socket for control signals
Switch-on signal of the heat pump
Analogue signal 0-10 V
Power station block (digital input)
Output signal (5 V DC) for circulating pump

X3 – M12 plug for temperature sensor
Connection options for optional content sensors 1 to 4

X4 – M12 plug RS485 interface
Modbus RTU communication via RS485 interface

X5 – RJ45 connection socket
Network connection via LAN connection

Flange-mounted electric heating element

Z1 – mains supply
Zur Energieversorgung der Heizelemente und internen Platine

Z5 – RJ12 connection socket
Interface to RemoteControl control unit

Supplied plugs/connecting cable

Z1 – power supply heating element
Wieland RST mini 1615,
5-pin plug with 2 m cable 2.5 mm²
Capacity: 250/400 V 16 A


Z5/X1 – communication
Pluggable RJ12 communication cable 2.9 m

X2: Round plug connector M12 (socket)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X2: Round plug connector M12 (plug)
3-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20

X4: Round plug connector M12 (plug)
8-pin (A-coded) with screw contacts, IP68
connection size:
0.14-0.5 mm²/AWG 26-20


Connection diagrams EP-3.5 and EFHK-3.5




No external switching device (e.g. contactor or relay) is required, the heating element is switched exclusively via the integrated interfaces (e.g. Modbus, 0-10 V, switching contact, etc.).

Heat Pump request =
Potential-free request contact of the main heat generator

Connection diagrams EP-4.4 to EP-5.2 and EFHK-4.4 to EFHK-5.8




Connection diagrams EP-7.5 to EP-9.0 and EFHK-7.5 to EFHK-9.0



Input assignment of plug connections


Connector X2-signal inputs

Connection 1:	GND
Connection 2:	Analogue Input 0-10 V
Connection 3:	EW lock
Connection 4:	Relay K5 (5 V DC)
Connection 5:	GND
Connection 6:	Heatpump request
Connection 7:	GND
Connection 8:	5 V DC out




Connector X3-additional sensors

Connection 1:	GND
Connection 2:	Sensor 1
Connection 3:	GND
Connection 4:	Sensor 2
Connection 5:	GND
Connection 6:	Sensor 3
Connection 7:	GND
Connection 8:	Sensor 4





Connector Modbus RTU RS485

Connection 1:	GND
Connection 3:	RS485 B
Connection 4:	RS485 A




Photovoltaic screw-in electric heating element
(Dimensions in mm)






Installation length =	EL
EP-3.5-1½"-PV	600
EP-4.4-1½"-PV	700
EP-5.2-1½"-PV	750
EP-7.5-1½"-PV	700
EP-9.0-1½"-PV	750

Photovoltaic flange-mounted electric heating element
(Dimensions in mm)





Installation length =	EL
EFHK-E/C-3.5-180-PV	360
EFHK-E/C-4.4-180-PV	420
EFHK-E/C-5.8-180-PV	540
EFHK-E/C-7.5-180-PV	420
EFHK-E/C-9.0-180-PV	490

Calorifier/storage tank	Photovoltaic screw-in electric heating element					Photovoltaic flange-mounted electric heating element									
	EP-3.5-PV 3.5 kW	EP-4.4-PV 4.4 kW	EP-5.2-PV 5.2 kW	EP-7.5-PV 7.5 kW	EP-9.0-PV 9.0 kW	EFHK-E/C-3.5-180-PV 3.5 kW		EFHK-E/C-4.4-180-PV 4.4 kW		EFHK-E/C-5.8-180-PV 5.8 kW		EFHK-E/C-7.5-180-PV 7.5 kW		EFHK-E/C-9.0-180-PV 9.0 kW	
Installation type	Sleeve 1½″					Flange Ø 180									
Installation position						t	b	t	b	t	b	t	b	t	b
Stainless steel calorifier															
CombiVal C															
CombiVal C (300)							●		●						
CombiVal C (400)							●		●		●		●		●
CombiVal C (500)							●		●		●		●		●
CombiVal C (750)							●		●		●		●		●
CombiVal C (1000)							●		●		●		●		●
CombiVal C (1500)						●	●	●	●	●	●	●	●	●	●
CombiVal C (2000)						●	●	●	●	●	●	●	●	●	●
CombiVal C (2500)							●*		●*		●*		●*		●*
CombiVal CR															
CombiVal CR (200)							●		●		●		●		●
CombiVal CR (300)							●		●				●		●
CombiVal CR (500)	●						●		●		●		●		●
CombiVal CR (800)						●	●	●	●	●	●	●	●	●	●
CombiVal CR (1000)						●	●	●	●	●	●	●	●	●	●
CombiVal CSR															
CombiVal CSR (300)							●		●						
CombiVal CSR (400)	●						●		●		●		●		●
CombiVal CSR (500)	●						●		●		●		●		●
CombiVal CSR (800)						●	●	●	●	●	●	●	●	●	●
CombiVal CSR (1000)						●	●	●	●	●	●	●	●	●	●
CombiVal CSR (1250)						●	●	●	●	●	●	●	●	●	●
CombiVal CSR (1500)						●	●	●	●	●	●	●	●	●	●
CombiVal CSR (2000)						●	●	●	●	●	●	●	●	●	●
Enamelled calorifier															
CombiVal E															
CombiVal E (300)							●		●						
CombiVal E (500)							●		●		●		●		●
CombiVal E (800)							●		●		●		●		●
CombiVal E (1000)							●		●		●		●		●
CombiVal E (1500)						●	●	●	●	●	●	●	●	●	●
CombiVal E (2000)						●	●	●	●	●	●	●	●	●	●
CombiVal ER															
CombiVal ER (200)							●								
CombiVal ERW (200)							●								
CombiVal ER (300)							●		●						
CombiVal ER (400)							●		●						
CombiVal ER (500)							●		●						
CombiVal ER (800)							●		●		●		●		●
CombiVal ER (1000)							●		●		●		●		●
CombiVal ESR															
CombiVal ESR (200)							●								
CombiVal ESR (300)							●		●						
CombiVal ESR (400)							●		●						
CombiVal ESSR															
CombiVal ESSR (500)	●						●		●						
CombiVal ESSR (800)						●	●	●	●	●	●	●	●	●	●
CombiVal ESSR (1000)						●	●	●	●	●	●	●	●	●	●
MultiVal ERR															
MultiVal ERR (300)							●								
MultiVal ERR (400)	●						●		●						
MultiVal ERR (500)	●						●		●				●		●
MultiVal ESRR															
MultiVal ESRR (500)							●		●				●		●
MultiVal ESRR (800)						●	●	●	●	●	●	●	●	●	●
MultiVal ESRR (1000)						●	●	●	●	●	●	●	●	●	●
CombiVal WPEF															
CombiVal WPEF (300)							●		●						

* On-site delivery of an adapter flange for the installation of the flange-mounted electric heating element

Calorifier/storage tank	Photovoltaic screw-in electric heating element										Photovoltaic flange-mounted electric heating element									
	EP-3.5-PV 3.5 kW		EP-4.4-PV 4.4 kW		EP-5.2-PV 5.2 kW		EP-7.5-PV 7.5 kW		EP-9.0-PV 9.0 kW		EFHK-E/C-3.5-180-PV 3.5 kW		EFHK-E/C-4.4-180-PV 4.4 kW		EFHK-E/C-5.8-180-PV 5.8 kW		EFHK-E/C-7.5-180-PV 7.5 kW		EFHK-E/C-9.0-180-PV 9.0 kW	
Installation type	Sleeve 1½"										Flange Ø 180									
Installation position	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b	t	b
Buffer storage tank *EnerVal*																				
EnerVal (200)																				
EnerVal (300)																				
EnerVal (500)	●	●																		
EnerVal (800)	●	●	●	●	●	●	●	●	●	●										
EnerVal (1000)	●	●	●	●	●	●	●	●	●	●										
EnerVal (1500)	●	●	●	●	●	●	●	●	●	●										
EnerVal (2000)	●	●	●	●	●	●	●	●	●	●										
EnerVal G																				
EnerVal G (800)											●	●	●	●	●	●	●	●	●	●
EnerVal G (1000)											●	●	●	●	●	●	●	●	●	●
EnerVal G (1500)																	●*	●*	●*	●*
EnerVal G (2000)																	●*	●*	●*	●*
EnerVal G (2500)																	●*	●*	●*	●*
EnerVal G (4000)																	●*	●*	●*	●*
EnerVal G (6000)																	●*	●*	●*	●*
EnerVal G cool																				
EnerVal G cool (800)	●		●		●		●		●											
EnerVal G cool (1000)	●		●		●		●		●											
EnerVal G cool (1500)	●		●		●		●		●											
EnerVal G cool (2500)	●		●		●		●		●											
EnerVal G cool (4000)	●		●		●		●		●											
EnerVal G cool (6000)	●		●		●		●		●											
Stratified storage tank/stratified combination storage tank *VarioVal FLS/Rxx*																				
VarioVal FLS (800)	●		●		●		●		●											
VarioVal FLS (1000)	●		●		●		●		●											
VarioVal RHS (800)	●																			
VarioVal RHS (1000)	●																			
VarioVal RL (600)	●		●				●													
VarioVal RLS (800)	●		●				●													
VarioVal RLS (1000)	●		●				●													

* Must be ordered with flange adapter

Legend:
t: top, b: bottom

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 - 04 | Subject to modifications

Your Hoval partner

Instructions and guidelines

The following instructions and guidelines have to be observed:


- technical data and mounting instructions of Hoval
- hydraulic regulations and those pertaining to instrumentation and control of Hoval
- instructions of the local fire police as well as country specific instructions
- instructions of the power station (concerning heat input of the electric heating element)
- fire protection instructions
- VDI 2035 Prevention of damage from corrosion and stone formation in hot water plants
- VDE 0100
- instructions concerning operating pressure and operating temperature
- DIN 4708 Central domestic hot water systems, page 1-3

Plumbing

- For electrical heating a hot water distribution system without circulation is to be planned if possible.
- Maximum safety adjustment: 1 bar less than the maximum operating pressure
- Please select the material of the connection components (pipes, sealing, safety valve,...) so that it can't get damaged by excessive temperatures caused by a malfunction of the temperature control circuit.

Assembly of the heating system


- The calorifier or additional heater coils must be provided with charging pump.
- An automatic deaerator must be installed at the highest point in the heating water flow.
- Flow and return pipes are to be attached in such way that with turned off charging pump and during electrical heating no back circulation and force of gravity circulation can occur.
- Expansion of heating water must be always ensured (also during electric charging resp. heat pump operation).



1 Flow
2 Return
3 Charging pump
4 Non-return valve

Necessary space


- The inspection opening has to be well accessible.
- Distance to the wall for the installation and removal of the electric heating element (a)



Calorifier		Type	a
CombiVal	ER/ESR/ESSR	200-500	≥ 600
CombiVal	ER/ESSR	800-1000	≥ 950
CombiVal	CR	200-500	≥ 750
CombiVal	CR	800-2000	≥ 950
CombiVal	CSR	300-500	≥ 750
CombiVal	CSR	800-1000	≥ 950
CombiVal	E/C	300-500	≥ 750
CombiVal	E/C	800-2500	≥ 950
DuoVal	E/C	100-300	≥ 600


Notice on request contact:
When the main heat generator is requested via the "Heat Pump Request" switch contact, note that the PV heating rods are programmed with only 55 °C as the standard request temperature in the factory setting. The parameter must be adapted to the specific system in the web interface.

Calorifier with one coil



1 Cold water
2 Hot water
3 Circulation
4 Draining
5 Safety valve
6 Pressure reducing valve
7 Testing device
8 Backflow preventer
9 Pressure gauge connection; with a content of 1000 l and more a fixed installed pressure gauge is required.
10 Diaphragm pressure expansion tank (optional)

Calorifier with two coils (incl. solar)



1 Cold water
2 Hot water
3 Circulation
4 Draining
5 Safety valve
6 Pressure reducing valve
7 Testing device
8 Backflow preventer
9 Pressure gauge connection; with a content of 1000 l and more a fixed installed pressure gauge is required.
10 Diaphragm pressure expansion tank (optional)
11 Thermostatic water mixer

Reading examples for the design of the storage tank size

Domestic hot water temperature 45 °C

1) **Comfort** design
Calculation with simultaneity factor according to **DIN 4708**

① Performance figure NL = 23
② Heating flow T = 60 °C
► CombiVal CSR (500)
③ Heating flow T = 70 °C
► CombiVal CSR (400)
④ Heating flow T = 80 °C
► CombiVal CSR (300)

2) **Standard** design
Calculation with simultaneity factor according to **Dresden Technical University**

① Performance figure NL = 23
⑤ Heating flow T = 60 °C
► CombiVal CSR (400)
⑥ Heating flow T = 70 °C
► CombiVal CSR (300)
⑦ Heating flow T = 80 °C
► CombiVal CSR (300)

	Comfort [1]			Standard [2]		
T >	60 °C	70 °C	80 °C	60 °C	70 °C	80 °C
NL v	②	③	④	⑤	⑥	⑦
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13	300					
14						
15				300		
16						
17						
18						
19						
20						
21	400	300				
22						
23 ①						
24						
25						
26				400	300	
27						
28						
29			300			
30	500	400				
31						
32						
33						
34						
35						
36						
37						300
38				500	400	

Calculation of the continuous domestic hot water output for Hoval CombiVal CSR (500)

Reading example 2: domestic hot water output at 60 °C with flow temperature 70 °C

(1) Assumption of the charging flow rate 2 m³/h


(2) Intersection with curve $T_{heating\ flow}$ = 70 °C

(3) ► Continuous output of approx. 1150 l/h

(4) ► Heat output of approx. 66 kW without boiler supplement

(5) Read the spread between flow and return, approx. 28 K, i.e. return flow is at approx. 42 °C)


Domestic hot water 60 °C





Reading example Comfort

for Hoval CombiVal CSR (400)
N number = 23 = 650 l/10 min 45 °C
Heating flow T = 70 °C
Cold water inlet 10 °C

10 min peak output/N number with domestic hot water 45 °C
according to DIN 4708 (Comfort) and Dresden Technical University (Standard)









1. Transfer performance figure NL 23 to curve sheet
2. Read off peak output [l/10 min] from Comfort curve in the curve sheet
3. Transfer peak output [l/10 min] to the curve sheet up to intersection FL 70 °C
4. Read off flow rate charging pump (SLP) on curve sheet
5. Transfer flow rate charging pump to curve sheet intersection FL 70 °C
6. Read off heat output
7. Read off continuous output [l/h]


Reading example Standard

for Hoval CombiVal CSR (300)
N number = 23 = 555 l/10 min 45 °C
Heating flow T = 70 °C
Cold water inlet 10 °C

10 min peak output/N number with domestic hot water 45 °C
according to DIN 4708 (Comfort) and Dresden Technical University (Standard)







1. Transfer performance figure NL 23 to curve sheet
2. Read off peak output [l/10 min] from Comfort curve in the curve sheet
3. Transfer peak output [l/10 min] to the curve sheet up to intersection FL 70 °C
4. Read off flow rate charging pump (SLP) on curve sheet
5. Transfer flow rate charging pump to curve sheet intersection FL 70 °C
6. Read off heat output
7. Read off continuous output [l/h]

Fundamental selection criteria

Enamelled calorifiers must not be used where the water is completely softened.
If the pH value is below the balance pH value, the water is aggressive to metals. If the pH value is more than 0.3 below the balance pH value, an enamelled calorifier should not be used.
The water must comply with the limit values specified in the current drinking water ordinance.

Enamelled calorifiers

- If the **conductance** [1)] is < 200 µS/cm, enamelled calorifiers are no longer adequately protected by a magnesium protection anode. If the conductance is < 100 µS/cm, a Correx® impressed current anode also no longer offers adequate protection.
- If the **total hardness** [2)] is < 1 mmol/l, enamelled calorifiers are not adequately protected by a magnesium protection anode. If the total hardness is < 0.5 mmol/l, a Correx® impressed current anode also no longer offers adequate protection.
- Enamelled calorifiers must not be used where the water is completely softened. If the **residual hardness** [3)] is > 1 mmol/l or higher than 50 % of the total hardness of the crude water, a Correx® impressed current anode can help.
- If the **pH value** [4)] is more than 0.3 below the balance pH value, enamelled calorifiers should no longer be used. If the pH value is 0.1-0.3 below the balance pH value, a Correx® impressed current anode can help.
- Damage may result if the copper content is above 0.05 mg/l. The copper content must comply with the limit value specified in the current drinking water ordinance.

Limit values (in tabular form):

Type	Design	Corrosion protection	Conductance [1]	Total hardness [2]	Residual hardness [3] in proportion to total hardness of the tap water		pH value [4] below the balance pH value
			µS/cm	mmol/l	mmol/l	%	-
CombiVal ER (200-500)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal ER (800,1000)	S	2 Mg anodes	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal ESR (200-400)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal ESSR (500)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal ESSR (800,1000)	S	2 Correx® impressed current anodes	> 100	> 0.5	> 1.0	> 50	0.1-0.3
MultiVal ERR (300-500)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
MultiVal ESRR (500)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
MultiVal ESRR (800,1000)	S	2 Correx® impressed current anodes	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal E (300-1000)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
CombiVal E (1500,2000)	S	2 Mg anodes	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
DuoVal E (100/300)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3
	W	1 Correx® impressed current anode	> 100	> 0.5	> 1.0	> 50	0.1-0.3
TopVal (130,160)	S	1 Mg anode	> 200	> 1.0	> 1.0	> 50	< 0.3

If the values are outside of the limit values, a stainless steel calorifier must be used.

W Customised design
S Standard design

In every case, either a Correx® impressed current anode or one/two magnesium protection anodes are allowed to be used.

Stainless steel calorifiers

- The storage tank must be properly earthed separately.
- Possible functional separating gap (e.g. insulating screw)
- If insulating screw fittings are used, do not connect the earth cable.
- The chloride content of the cold water must be below 40 mg/l.
- No material that can release chlorides (e.g. seals) must be used.
- The pH value must not fall below 4.0.
- Ferritic deposits must not get onto or into the stainless component (CrNi).
- Water softeners > 20 °fH are recommended, the hardness must not fall below 12 °fH.
- The storage tank must be maintained in line with the “water composition”, according to the rules of technology and the protection anodes used must be checked/replaced.
- Cleaning must be carried out with suitable tools. Do not use steel tools for stainless steel calorifiers.
- The flange screws must be tightened to the correct torque.

Limit values domestic water:

Type	Design	Corrosion protection	Max. chloride content mg/l
CombiVal CR (200-800)	S	-	< 40
	W	1 Correx® impressed current anode	< 200
CombiVal CR (1000)	S	-	< 40
	W	2 Correx® impressed current anodes	< 200
CombiVal CSR (300-800)	S	-	< 40
	W	1 Correx® impressed current anode	< 200
CombiVal CSR (1000-2000)	S	-	< 40
	W	2 Correx® impressed current anodes	< 200
CombiVal C (300-2500)	S	-	< 40
	W	1 Correx® impressed current anode	< 200
DuoVal C (100/300)	S	-	< 40
	W	1 Correx® impressed current anode	< 200

W Customised design (on site)
S Standard design

Limit value filling and replacement water heating:
According to our heat generator project engineering.

Plate heat exchangers

Information about the quality of the plant water on the heating side and the tap water where plate heat exchangers are used.
Heat exchangers that do not contain non-ferrous metals should be used if corrosion problems affecting copper-soldered heat exchangers or copper pipes are known in the area of the drinking water supply where the plate heat exchangers will be used.

Heating water side:
The following applies:
- VDI 2035
- In addition, the EN 14868 standard must be applied, as well as the manufacturer-specific specifications

Domestic water side:
- All parts of the heat exchanger which come into contact with water are made of copper or stainless steel.
- To prevent deposits and abrasion, a filter < 100 µm must be installed upstream of the heat exchanger.
- The maximum temperature on the domestic water side is 60 °C, whereby the **total hardness** [3] of the water must not exceed 14 °dH (2.5 mmol/l). If, for hygiene reasons, hot water temperatures of over 60 °C are required, measures must be implemented to prevent the formation of deposits (calcification). However, a hot water temperature of 70 °C must never be exceeded.
- The **pH value** [2] of the domestic water must be between 7 and 9.
- Due to the risk of corrosion, the **sum of the chloride, nitrate and sulphate content** [1] of the domestic water must not exceed a total of 100/300 mg/l. The **maximum free chloride concentration** [4] is 0.5 mg/l.
- Due to the risk of deposits forming, the **mineral content** [5] of the tap water must not exceed 250 mg/l. The maximum **conductance** [6] is 500/1000 µS/cm.
- **Softened water** [7] must be blended with at least 50 % tap water to ensure that the ratio of [Ca^{2+} und Mg^{2+}] to [HCO_3^-] is over 0.5.
- If the sulphate [SO_4]$^{2-}$ content exceeds the carbonate [HCO_3^-] content, copper-soldered heat exchangers must not be used.

Limit values (in tabular form)

		Cu-soldered		Without non-ferrous metals
		Plate heat exchanger heating water side	Plate heat exchanger domestic water side	Plate heat exchanger domestic water side
Conductance [6] of the tap water	µS/cm	-	< 500	< 1000
Residual hardness [7]	mmol/l	-	> 0.5	-
in relation to the total hardness of the tap water	%	-	> 50	-
pH value [2]	-	8.2-10	7-9	6-10
Max. free chloride concentration [4]	mg/l	-	< 0.5	< 0.5
Chloride	mg/l	< 30	< 50	< 100
Nitrate	mg/l	< 50	< 100	< 300
Sulphate	mg/l	< 30	< 100	< 300
Sum of chloride, nitrate and sulphate content [1]	mg/l	< 50	< 100	< 300
Mineral content [5] of the tap water	mg/l	-	< 250	< 250
Total hardness [3]	°dH	-	< 14	< 15
	mmol/l	-	< 2.5	< 2.6

Electric heating elements

The electric heating elements are equipped with a temperature controller and a safety temperature limiter.

Safety temperature limiter
Switch-off temperature 98 °C – 6 K.
If the sanitary system cannot withstand these temperatures, a thermostatic water mixer must be built in.

Hoval quality.
You can count on us.

Hoval

Hoval is one of the leading international companies for heating and indoor climate solutions. Drawing on more than 80 years of experience and benefiting from a close-knit team culture, the Hoval Group delivers exciting solutions and develops technically superior products. This leadership role requires a sense of responsibility for energy and the environment, which is expressed in an intelligent combination of different heating technologies and customised indoor climate solutions.

Hoval also provides personal consultations and comprehensive customer service. With around 2500 employees in 15 companies around the world, Hoval sees itself not as a conglomerate, but as a large family that thinks and acts globally.
Hoval heating and indoor climate solutions are currently exported to more than 50 countries.

Responsibility for energy and environment

Liechtenstein
Hoval Aktiengesellschaft
9490 Vaduz
+423 399 24 00
hoval.com

United Kingdom
Hoval Ltd.
Newark Notts. NG 24 1JN
+44 1636 672 711
hoval.co.uk

2026 – 10 | Subject to modifications

Your Hoval partner